
web3.js Documentation

Release 1.0.0

Fabian Vogelsteller, Marek Kotewicz, Jeffrey Wilcke, Marian Oancea

Jul 05, 2021

1	Getting Started	3
1.1	Adding web3.js	3
2	Callbacks Promises Events	5
3	Glossary	7
3.1	json interface	7
4	Web3	9
4.1	Web3.modules	9
4.2	Web3 Instance	10
4.3	version	10
4.4	utils	11
4.5	setProvider	11
4.6	providers	12
4.7	givenProvider	14
4.8	currentProvider	14
4.9	BatchRequest	15
4.10	extend	15
5	web3.eth	19
5.1	Note on checksum addresses	19
5.2	subscribe	20
5.3	Contract	20
5.4	Iban	20
5.5	personal	20
5.6	accounts	20
5.7	ens	20
5.8	abi	20
5.9	net	21
5.10	setProvider	21
5.11	providers	22
5.12	givenProvider	24
5.13	currentProvider	24
5.14	BatchRequest	25
5.15	extend	25
5.16	defaultAccount	27

5.17	defaultBlock	27
5.18	defaultHardfork	28
5.19	defaultChain	29
5.20	defaultCommon	29
5.21	transactionBlockTimeout	30
5.22	transactionConfirmationBlocks	31
5.23	transactionPollingTimeout	31
5.24	handleRevert	32
5.25	maxListenersWarningThreshold	32
5.26	getProtocolVersion	33
5.27	isSyncing	33
5.28	getCoinbase	34
5.29	isMining	34
5.30	getHashrate	35
5.31	getGasPrice	35
5.32	getAccounts	35
5.33	getBlockNumber	36
5.34	getBalance	36
5.35	getStorageAt	37
5.36	getCode	37
5.37	getBlock	38
5.38	getBlockTransactionCount	40
5.39	getBlockUncleCount	40
5.40	getUncle	41
5.41	getTransaction	41
5.42	getPendingTransactions	42
5.43	getTransactionFromBlock	44
5.44	getTransactionReceipt	44
5.45	getTransactionCount	46
5.46	sendTransaction	46
5.47	sendSignedTransaction	49
5.48	sign	50
5.49	signTransaction	50
5.50	call	51
5.51	estimateGas	52
5.52	getPastLogs	53
5.53	getWork	54
5.54	submitWork	55
5.55	requestAccounts	55
5.56	getChainId	56
5.57	getNodeInfo	56
5.58	getProof	57
6	web3.eth.subscribe	59
6.1	subscribe	59
6.2	clearSubscriptions	60
6.3	subscribe(“pendingTransactions”)	61
6.4	subscribe(“newBlockHeaders”)	62
6.5	subscribe(“syncing”)	63
6.6	subscribe(“logs”)	64
7	web3.eth.Contract	67
7.1	new contract	67
7.2	= Properties =	68

7.3	defaultAccount	68
7.4	defaultBlock	69
7.5	defaultHardfork	69
7.6	defaultChain	70
7.7	defaultCommon	71
7.8	transactionBlockTimeout	71
7.9	transactionConfirmationBlocks	72
7.10	transactionPollingTimeout	72
7.11	handleRevert	72
7.12	options	73
7.13	options.address	74
7.14	options.jsonInterface	74
7.15	= Methods =	75
7.16	clone	75
7.17	deploy	76
7.18	methods	77
7.19	methods.myMethod.call	79
7.20	methods.myMethod.send	80
7.21	methods.myMethod.estimateGas	82
7.22	methods.myMethod.encodeABI	83
7.23	= Events =	84
7.24	once	84
7.25	events	85
7.26	events.allEvents	87
7.27	getPastEvents	87
8	web3.eth.accounts	89
8.1	create	89
8.2	privateKeyToAccount	90
8.3	signTransaction	91
8.4	recoverTransaction	93
8.5	hashMessage	94
8.6	sign	94
8.7	recover	95
8.8	encrypt	96
8.9	decrypt	97
8.10	wallet	98
8.11	wallet.create	99
8.12	wallet.add	99
8.13	wallet.remove	100
8.14	wallet.clear	101
8.15	wallet.encrypt	101
8.16	wallet.decrypt	102
8.17	wallet.save	103
8.18	wallet.load	104
9	web3.eth.personal	107
9.1	setProvider	107
9.2	providers	108
9.3	givenProvider	110
9.4	currentProvider	111
9.5	BatchRequest	111
9.6	extend	112
9.7	newAccount	113

9.8	sign	114
9.9	ecRecover	115
9.10	signTransaction	116
9.11	sendTransaction	117
9.12	unlockAccount	117
9.13	lockAccount	118
9.14	getAccounts	118
9.15	importRawKey	119
10	web3.eth.ens	121
10.1	registryAddress	121
10.2	registry	122
10.3	resolver	123
10.4	getResolver	123
10.5	setResolver	124
10.6	getOwner	124
10.7	setOwner	125
10.8	getTTL	126
10.9	setTTL	126
10.10	setSubnodeOwner	127
10.11	setRecord	127
10.12	setSubnodeRecord	128
10.13	setApprovalForAll	129
10.14	isApprovedForAll	129
10.15	recordExists	130
10.16	getAddress	131
10.17	setAddress	131
10.18	getPubkey	132
10.19	setPubkey	133
10.20	getContent	134
10.21	setContent	135
10.22	getContenthash	136
10.23	setContenthash	137
10.24	getMultihash	138
10.25	supportsInterface	139
10.26	setMultihash	140
10.27	ENS events	141
11	web3.eth.Iban	143
11.1	Iban instance	143
11.2	Iban constructor	143
11.3	toAddress	144
11.4	toIban	144
11.5	fromAddress	145
11.6	fromBban	146
11.7	createIndirect	146
11.8	isValid	147
11.9	prototype.isValid	147
11.10	prototype.isDirect	148
11.11	prototype.isIndirect	148
11.12	prototype.checksum	149
11.13	prototype.institution	149
11.14	prototype.client	150
11.15	prototype.toAddress	150

11.16	prototype.toString	151
12	web3.eth.abi	153
12.1	encodeFunctionSignature	153
12.2	encodeEventSignature	154
12.3	encodeParameter	155
12.4	encodeParameters	156
12.5	encodeFunctionCall	157
12.6	decodeParameter	158
12.7	decodeParameters	159
12.8	decodeLog	161
13	web3.*.net	163
13.1	getId	163
13.2	isListening	164
13.3	getPeerCount	164
14	web3.bzz	167
14.1	setProvider	167
14.2	givenProvider	168
14.3	currentProvider	169
14.4	upload	169
14.5	download	171
14.6	pick	172
15	web3.shh	173
15.1	setProvider	173
15.2	providers	174
15.3	givenProvider	176
15.4	currentProvider	177
15.5	BatchRequest	177
15.6	extend	178
15.7	getId	179
15.8	isListening	180
15.9	getPeerCount	180
15.10	getVersion	181
15.11	getInfo	181
15.12	setMaxMessageSize	182
15.13	setMinPoW	183
15.14	markTrustedPeer	183
15.15	newKeyPair	184
15.16	addPrivateKey	184
15.17	deleteKeyPair	185
15.18	hasKeyPair	185
15.19	getPublicKey	186
15.20	getPrivateKey	186
15.21	newSymKey	187
15.22	addSymKey	187
15.23	generateSymKeyFromPassword	188
15.24	hasSymKey	189
15.25	getSymKey	189
15.26	deleteSymKey	190
15.27	post	190
15.28	subscribe	192
15.29	clearSubscriptions	193

15.30	newMessageFilter	194
15.31	deleteMessageFilter	194
15.32	getFilterMessages	195
16	web3.utils	197
16.1	Bloom Filters	197
16.2	randomHex	198
16.3	_	199
16.4	BN	199
16.5	isBN	200
16.6	isBigNumber	200
16.7	sha3	201
16.8	sha3Raw	202
16.9	soliditySha3	202
16.10	soliditySha3Raw	204
16.11	isHex	204
16.12	isHexStrict	205
16.13	isAddress	206
16.14	toChecksumAddress	206
16.15	checkAddressChecksum	207
16.16	toHex	207
16.17	stripHexPrefix	208
16.18	toBN	208
16.19	hexToNumberString	209
16.20	hexToNumber	210
16.21	numberToHex	210
16.22	hexToUtf8	211
16.23	hexToAscii	211
16.24	utf8ToHex	212
16.25	asciiToHex	212
16.26	hexToBytes	213
16.27	bytesToHex	213
16.28	toWei	214
16.29	fromWei	215
16.30	unitMap	217
16.31	padLeft	218
16.32	padRight	219
16.33	toTwosComplement	219
Index		221

web3.js is a collection of libraries that allow you to interact with a local or remote ethereum node using HTTP, IPC or WebSocket.

The following documentation will guide you through *installing and running web3.js* as well as providing an API reference documentation with examples.

Contents:

Keyword Index, Search Page

The web3.js library is a collection of modules that contain functionality for the ethereum ecosystem.

- web3-eth is for the ethereum blockchain and smart contracts.
- web3-shh is for the whisper protocol, to communicate p2p and broadcast.
- web3-bzz is for the swarm protocol, the decentralized file storage.
- web3-utils contains useful helper functions for Dapp developers.

1.1 Adding web3.js

First you need to get web3.js into your project. This can be done using the following methods:

- npm: `npm install web3`
- yarn: `yarn add web3`
- pure js: link the `dist/web3.min.js`

After that you need to create a web3 instance and set a provider.

Most Ethereum-supported browsers like MetaMask have an [EIP-1193](#) compliant provider available at `window.ethereum`.

For web3.js, check `Web3.givenProvider`.

If this property is null you should connect to a remote/local node.

```
// In Node.js use: const Web3 = require('web3');  
  
let web3 = new Web3(Web3.givenProvider || "ws://localhost:8545");
```

That's it! now you can use the web3 object.

Callbacks Promises Events

To help web3 integrate into all kinds of projects with different standards we provide multiple ways to act on asynchronous functions.

Most web3.js objects allow a callback as the last parameter, as well as returning promises to chain functions.

Ethereum as a blockchain has different levels of finality and therefore needs to return multiple “stages” of an action. To cope with requirement we return a “promiEvent” for functions like `web3.eth.sendTransaction` or contract methods. This “promiEvent” is a promise combined with an event emitter to allow acting on different stages of action on the blockchain, like a transaction.

PromiEvents work like a normal promises with added `on`, `once` and `off` functions. This way developers can watch for additional events like on “receipt” or “transactionHash”.

```
web3.eth.sendTransaction({from: '0x123...', data: '0x432...'})
  .once('sending', function(payload){ ... })
  .once('sent', function(payload){ ... })
  .once('transactionHash', function(hash){ ... })
  .once('receipt', function(receipt){ ... })
  .on('confirmation', function(confNumber, receipt, latestBlockHash){ ... })
  .on('error', function(error){ ... })
  .then(function(receipt){
    // will be fired once the receipt is mined
  });
```


3.1 json interface

The json interface is a json object describing the [Application Binary Interface \(ABI\)](#) for an Ethereum smart contract.

Using this json interface web3.js is able to create JavaScript object representing the smart contract and its methods and events using the *web3.eth.Contract object*.

3.1.1 Specification

Functions:

- `type`: "function", "constructor" (can be omitted, defaulting to "function"; "fallback" also possible but not relevant in web3.js);
- `name`: the name of the function (only present for function types);
- `constant`: true if function is specified to not modify the blockchain state;
- `payable`: true if function accepts ether, defaults to false;
- `stateMutability`: a string with one of the following values: pure (specified to not read blockchain state), view (same as constant above), nonpayable and payable (same as payable above);
- `inputs`: an array of objects, each of which contains:
 - `name`: the name of the parameter;
 - `type`: the canonical type of the parameter.
- `outputs`: an array of objects same as `inputs`, can be omitted if no outputs exist.

Events:

- `type`: always "event"

- name: the name of the event;
- inputs: an array of objects, each of which contains:
 - name: the name of the parameter;
 - type: the canonical type of the parameter.
 - indexed: true if the field is part of the log's topics, false if it one of the log's data segment.
- anonymous: true if the event was declared as anonymous.

3.1.2 Example

```
contract Test {
  uint a;
  address d = 0x12345678901234567890123456789012;

  function Test(uint testInt) { a = testInt;}

  event Event(uint indexed b, bytes32 c);

  event Event2(uint indexed b, bytes32 c);

  function foo(uint b, bytes32 c) returns(address) {
    Event(b, c);
    return d;
  }
}

// would result in the JSON:
[
  {
    "type": "constructor",
    "payable": false,
    "stateMutability": "nonpayable",
    "inputs": [{"name": "testInt", "type": "uint256"}],
  },
  {
    "type": "function",
    "name": "foo",
    "constant": false,
    "payable": false,
    "stateMutability": "nonpayable",
    "inputs": [{"name": "b", "type": "uint256"}, {"name": "c", "type": "bytes32"}],
    "outputs": [{"name": "", "type": "address"}]
  },
  {
    "type": "event",
    "name": "Event",
    "inputs": [{"indexed": true, "name": "b", "type": "uint256"}, {"indexed": false, "name": "c",
    ↪ "type": "bytes32"}],
    "anonymous": false
  },
  {
    "type": "event",
    "name": "Event2",
    "inputs": [{"indexed": true, "name": "b", "type": "uint256"}, {"indexed": false, "name": "c",
    ↪ "type": "bytes32"}],
    "anonymous": false
  }
]
```

CHAPTER 4

Web3

This is the main (or ‘umbrella’) class of the web3.js library.

```
var Web3 = require('web3');  
  
> Web3.utils  
> Web3.version  
> Web3.givenProvider  
> Web3.providers  
> Web3.modules
```

4.1 Web3.modules

```
Web3.modules
```

Will return an object with the classes of all major sub modules, to be able to instantiate them manually.

4.1.1 Returns

Object: A list of module constructors:

- **Eth - Constructor:** The Eth module for interacting with the Ethereum network (*web3.eth*).
- **Net - Constructor:** The Net module for interacting with network properties (*web3.eth.net*).
- **Personal - Constructor:** The Personal module for interacting with the Ethereum accounts (*web3.eth.personal*).
- **Shh - Constructor:** The Shh module for interacting with the whisper protocol (*web3.shh*).
- **Bzz - Constructor:** The Bzz module for interacting with the swarm network (*web3.bzz*).

4.1.2 Example

```
Web3.modules
> {
  Eth: Eth(provider),
  Net: Net(provider),
  Personal: Personal(provider),
  Shh: Shh(provider),
  Bzz: Bzz(provider),
}
```

4.2 Web3 Instance

The Web3 class is an umbrella package to house all Ethereum related modules.

```
var Web3 = require('web3');

// "Web3.providers.givenProvider" will be set if in an Ethereum supported browser.
var web3 = new Web3(Web3.givenProvider || 'ws://some.local-or-remote.node:8546');

> web3.eth
> web3.shh
> web3.bzz
> web3.utils
> web3.version
```

4.3 version

Static accessible property of the Web3 class and property of the instance as well.

```
Web3.version
web3.version
```

Contains the current package version of the web3.js library.

4.3.1 Returns

String: The current version.

4.3.2 Example

```
web3.version;
> "1.2.3"
```

4.4 utils

Static accessible property of the Web3 class and property of the instance as well.

```
Web3.utils
web3.utils
```

Utility functions are also exposes on the Web3 class object directly.

See [web3.utils](#) for more.

4.5 setProvider

```
web3.setProvider(myProvider)
web3.eth.setProvider(myProvider)
web3.shh.setProvider(myProvider)
web3.bzz.setProvider(myProvider)
...
```

Will change the provider for its module.

Note: When called on the umbrella package web3 it will also set the provider for all sub modules web3.eth, web3.shh, etc. EXCEPT web3.bzz which needs a separate provider at all times.

4.5.1 Parameters

1. Object - myProvider: a valid provider.

4.5.2 Returns

Boolean

4.5.3 Example: Local Geth Node

```
var Web3 = require('web3');
var web3 = new Web3('http://localhost:8545');
// or
var web3 = new Web3(new Web3.providers.HttpProvider('http://localhost:8545'));

// change provider
web3.setProvider('ws://localhost:8546');
// or
web3.setProvider(new Web3.providers.WebsocketProvider('ws://localhost:8546'));

// Using the IPC provider in node.js
var net = require('net');
var web3 = new Web3('/Users/myuser/Library/Ethereum/geth.ipc', net); // mac os path
```

(continues on next page)

(continued from previous page)

```
// or
var web3 = new Web3(new Web3.providers.IpcProvider('/Users/myuser/Library/Ethereum/
↳ geth.ipc', net)); // mac os path
// on windows the path is: "\\.\pipe\geth.ipc"
// on linux the path is: "/users/myuser/.ethereum/geth.ipc"
```

4.5.4 Example: Remote Node Provider

```
// Using a remote node provider, like Alchemy (https://www.alchemyapi.io/supernode),
↳ is simple.
var Web3 = require('web3');
var web3 = new Web3("https://eth-mainnet.alchemyapi.io/v2/your-api-key");
```

4.6 providers

```
web3.providers
web3.eth.providers
web3.shh.providers
web3.bzz.providers
...
```

Contains the current available providers.

4.6.1 Value

Object with the following providers:

- Object - `HttpProvider`: The HTTP provider is **deprecated**, as it won't work for subscriptions.
- Object - `WebsocketProvider`: The Websocket provider is the standard for usage in legacy browsers.
- Object - `IpcProvider`: The IPC provider is used node.js dapps when running a local node. Gives the most secure connection.

4.6.2 Example

```
var Web3 = require('web3');
// use the given Provider, e.g in Mist, or instantiate a new websocket provider
var web3 = new Web3(Web3.givenProvider || 'ws://remotenode.com:8546');
// or
var web3 = new Web3(Web3.givenProvider || new Web3.providers.WebsocketProvider('ws://
↳ remotenode.com:8546'));

// Using the IPC provider in node.js
var net = require('net');

var web3 = new Web3('/Users/myuser/Library/Ethereum/geth.ipc', net); // mac os path
// or
```

(continues on next page)

(continued from previous page)

```
var web3 = new Web3(new Web3.providers.IpcProvider('/Users/myuser/Library/Ethereum/
↳geth.ipc', net)); // mac os path
// on windows the path is: "\\.\pipe\geth.ipc"
// on linux the path is: "/users/myuser/.ethereum/geth.ipc"
```

4.6.3 Configuration

```
// ====
// Http
// ====

var Web3HttpProvider = require('web3-providers-http');

var options = {
  keepAlive: true,
  withCredentials: false,
  timeout: 20000, // ms
  headers: [
    {
      name: 'Access-Control-Allow-Origin',
      value: '*'
    },
    {
      ...
    }
  ],
  agent: {
    http: http.Agent(...),
    baseUrl: ''
  }
};

var provider = new Web3HttpProvider('http://localhost:8545', options);

// =====
// Websockets
// =====

var Web3WsProvider = require('web3-providers-ws');

var options = {
  timeout: 30000, // ms

  // Useful for credentialed urls, e.g: ws://username:password@localhost:8546
  headers: {
    authorization: 'Basic username:password'
  },

  clientConfig: {
    // Useful if requests are large
    maxReceivedFrameSize: 100000000, // bytes - default: 1MiB
    maxReceivedMessageSize: 100000000, // bytes - default: 8MiB

    // Useful to keep a connection alive
    keepalive: true,
```

(continues on next page)

(continued from previous page)

```
    keepaliveInterval: 60000 // ms
  },

  // Enable auto reconnection
  reconnect: {
    auto: true,
    delay: 5000, // ms
    maxAttempts: 5,
    onTimeout: false
  }
};

var ws = new Web3WsProvider('ws://localhost:8546', options);
```

More information for the Http and Websocket provider modules can be found here:

- [HttpProvider](#)
 - [WebsocketProvider](#)
-

4.7 givenProvider

```
web3.givenProvider
web3.eth.givenProvider
web3.shh.givenProvider
web3.bzz.givenProvider
...
```

When using web3.js in an Ethereum compatible browser, it will set with the current native provider by that browser. Will return the given provider by the (browser) environment, otherwise `null`.

4.7.1 Returns

Object: The given provider set or `null`;

4.7.2 Example

4.8 currentProvider

```
web3.currentProvider
web3.eth.currentProvider
web3.shh.currentProvider
web3.bzz.currentProvider
...
```

Will return the current provider, otherwise `null`.

4.8.1 Returns

Object: The current provider set or null.

4.8.2 Example

4.9 BatchRequest

```
new web3.BatchRequest()
new web3.eth.BatchRequest()
new web3.shh.BatchRequest()
new web3.bzz.BatchRequest()
```

Class to create and execute batch requests.

4.9.1 Parameters

none

4.9.2 Returns

Object: With the following methods:

- `add(request)`: To add a request object to the batch call.
- `execute()`: Will execute the batch request.

4.9.3 Example

```
var contract = new web3.eth.Contract(abi, address);

var batch = new web3.BatchRequest();
batch.add(web3.eth.getBalance.request('0x0000000000000000000000000000000000000000',
  ↳ 'latest', callback));
batch.add(contract.methods.balance(address).call.request({from:
  ↳ '0x0000000000000000000000000000000000000000'}, callback2));
batch.execute();
```

4.10 extend

```
web3.extend(methods)
web3.eth.extend(methods)
web3.shh.extend(methods)
web3.bzz.extend(methods)
...
```

Allows extending the web3 modules.

Note: You also have `*.extend.formatters` as additional formatter functions to be used for input and output formatting. Please see the [source file](#) for function details.

4.10.1 Parameters

1. **methods - Object:** Extension object with array of methods description objects as follows:

- **property - String:** (optional) The name of the property to add to the module. If no property is set it will be added to the module directly.
- **methods - Array:** The array of method descriptions:
 - **name - String:** Name of the method to add.
 - **call - String:** The RPC method name.
 - **params - Number:** (optional) The number of parameters for that function. Default 0.
 - **inputFormatter - Array:** (optional) Array of inputformatter functions. Each array item responds to a function parameter, so if you want some parameters not to be formatted, add a null instead.
 - **outputFormatter - ``Function:** (optional) Can be used to format the output of the method.

4.10.2 Returns

Object: The extended module.

4.10.3 Example

```
web3.extend({
  property: 'myModule',
  methods: [{
    name: 'getBalance',
    call: 'eth_getBalance',
    params: 2,
    inputFormatter: [web3.extend.formatters.inputAddressFormatter, web3.extend.
    ↪formatters.inputDefaultBlockNumberFormatter],
    outputFormatter: web3.utils.hexToNumberString
  }, {
    name: 'getGasPriceSuperFunction',
    call: 'eth_gasPriceSuper',
    params: 2,
    inputFormatter: [null, web3.utils.numberToHex]
  }]
});

web3.extend({
  methods: [{
    name: 'directCall',
    call: 'eth_callForFun',
```

(continues on next page)

(continued from previous page)

```
    ]]  
  });  
  
  console.log(web3);  
> Web3 {  
  myModule: {  
    getBalance: function() {},  
    getGasPriceSuperFunction: function() {}  
  },  
  directCall: function() {},  
  eth: Eth {...},  
  bzz: Bzz {...},  
  ...  
}
```


The web3-eth package allows you to interact with an Ethereum blockchain and Ethereum smart contracts.

```
var Eth = require('web3-eth');

// "Eth.providers.givenProvider" will be set if in an Ethereum supported browser.
var eth = new Eth(Eth.givenProvider || 'ws://some.local-or-remote.node:8546');

// or using the web3 umbrella package

var Web3 = require('web3');
var web3 = new Web3(Web3.givenProvider || 'ws://some.local-or-remote.node:8546');

// -> web3.eth
```

5.1 Note on checksum addresses

All Ethereum addresses returned by functions of this package are returned as checksum addresses. This means some letters are uppercase and some are lowercase. Based on that it will calculate a checksum for the address and prove its correctness. Incorrect checksum addresses will throw an error when passed into functions. If you want to circumvent the checksum check you can make an address all lower- or uppercase.

5.1.1 Example

```
web3.eth.getAccounts(console.log);
> ["0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe" ,
  ↪ "0x85F43D8a49eeB85d32Cf465507DD71d507100C1d"]
```

5.2 subscribe

For `web3.eth.subscribe` see the *Subscribe reference documentation*.

5.3 Contract

For `web3.eth.Contract` see the *Contract reference documentation*.

5.4 Iban

For `web3.eth.Iban` see the *Iban reference documentation*.

5.5 personal

For `web3.eth.personal` see the *personal reference documentation*.

5.6 accounts

For `web3.eth.accounts` see the *accounts reference documentation*.

5.7 ens

For `web3.eth.ens` see the *ENS reference documentation*.

5.8 abi

For `web3.eth.abi` see the *ABI reference documentation*.

5.9 net

For `web3.eth.net` see the net reference documentation.

5.10 setProvider

```
web3.setProvider(myProvider)
web3.eth.setProvider(myProvider)
web3.shh.setProvider(myProvider)
web3.bzz.setProvider(myProvider)
...
```

Will change the provider for its module.

Note: When called on the umbrella package `web3` it will also set the provider for all sub modules `web3.eth`, `web3.shh`, etc. EXCEPT `web3.bzz` which needs a separate provider at all times.

5.10.1 Parameters

1. Object - `myProvider`: a valid provider.

5.10.2 Returns

Boolean

5.10.3 Example: Local Geth Node

```
var Web3 = require('web3');
var web3 = new Web3('http://localhost:8545');
// or
var web3 = new Web3(new Web3.providers.HttpProvider('http://localhost:8545'));

// change provider
web3.setProvider('ws://localhost:8546');
// or
web3.setProvider(new Web3.providers.WebsocketProvider('ws://localhost:8546'));

// Using the IPC provider in node.js
var net = require('net');
var web3 = new Web3('/Users/myuser/Library/Ethereum/geth.ipc', net); // mac os path
// or
var web3 = new Web3(new Web3.providers.IpcProvider('/Users/myuser/Library/Ethereum/
↳ geth.ipc', net)); // mac os path
// on windows the path is: "\\.\pipe\geth.ipc"
// on linux the path is: "/users/myuser/.ethereum/geth.ipc"
```

5.10.4 Example: Remote Node Provider

```
// Using a remote node provider, like Alchemy (https://www.alchemyapi.io/supernode),  
↪ is simple.  
var Web3 = require('web3');  
var web3 = new Web3("https://eth-mainnet.alchemyapi.io/v2/your-api-key");
```

5.11 providers

```
web3.providers  
web3.eth.providers  
web3.shh.providers  
web3.bzz.providers  
...
```

Contains the current available providers.

5.11.1 Value

Object with the following providers:

- Object - `HttpProvider`: The HTTP provider is **deprecated**, as it won't work for subscriptions.
- Object - `WebsocketProvider`: The Websocket provider is the standard for usage in legacy browsers.
- Object - `IpcProvider`: The IPC provider is used node.js dapps when running a local node. Gives the most secure connection.

5.11.2 Example

```
var Web3 = require('web3');  
// use the given Provider, e.g in Mist, or instantiate a new websocket provider  
var web3 = new Web3(Web3.givenProvider || 'ws://remotenode.com:8546');  
// or  
var web3 = new Web3(Web3.givenProvider || new Web3.providers.WebsocketProvider('ws://  
↪remotenode.com:8546'));  
  
// Using the IPC provider in node.js  
var net = require('net');  
  
var web3 = new Web3('/Users/myuser/Library/Ethereum/geth.ipc', net); // mac os path  
// or  
var web3 = new Web3(new Web3.providers.IpcProvider('/Users/myuser/Library/Ethereum/  
↪geth.ipc', net)); // mac os path  
// on windows the path is: "\\.\pipe\geth.ipc"  
// on linux the path is: "/users/myuser/.ethereum/geth.ipc"
```

5.11.3 Configuration

```
// ====
// Http
// ====

var Web3HttpProvider = require('web3-providers-http');

var options = {
  keepAlive: true,
  withCredentials: false,
  timeout: 20000, // ms
  headers: [
    {
      name: 'Access-Control-Allow-Origin',
      value: '*'
    },
    {
      ...
    }
  ],
  agent: {
    http: http.Agent(...),
    baseUrl: ''
  }
};

var provider = new Web3HttpProvider('http://localhost:8545', options);

// =====
// Websockets
// =====

var Web3WsProvider = require('web3-providers-ws');

var options = {
  timeout: 30000, // ms

  // Useful for credentialed urls, e.g: ws://username:password@localhost:8546
  headers: {
    authorization: 'Basic username:password'
  },

  clientConfig: {
    // Useful if requests are large
    maxReceivedFrameSize: 100000000, // bytes - default: 1MiB
    maxReceivedMessageSize: 100000000, // bytes - default: 8MiB

    // Useful to keep a connection alive
    keepalive: true,
    keepaliveInterval: 60000 // ms
  },

  // Enable auto reconnection
  reconnect: {
    auto: true,
    delay: 5000, // ms
  }
};
```

(continues on next page)

(continued from previous page)

```
        maxAttempts: 5,  
        onTimeout: false  
      }  
    };  
  
var ws = new Web3WsProvider('ws://localhost:8546', options);
```

More information for the Http and Websocket provider modules can be found here:

- [HttpProvider](#)
 - [WebsocketProvider](#)
-

5.12 givenProvider

```
web3.givenProvider  
web3.eth.givenProvider  
web3.shh.givenProvider  
web3.bzz.givenProvider  
...
```

When using web3.js in an Ethereum compatible browser, it will set with the current native provider by that browser. Will return the given provider by the (browser) environment, otherwise null.

5.12.1 Returns

Object: The given provider set or null;

5.12.2 Example

5.13 currentProvider

```
web3.currentProvider  
web3.eth.currentProvider  
web3.shh.currentProvider  
web3.bzz.currentProvider  
...
```

Will return the current provider, otherwise null.

5.13.1 Returns

Object: The current provider set or null.

5.13.2 Example

5.14 BatchRequest

```
new web3.BatchRequest()
new web3.eth.BatchRequest()
new web3.shh.BatchRequest()
new web3.bzz.BatchRequest()
```

Class to create and execute batch requests.

5.14.1 Parameters

none

5.14.2 Returns

Object: With the following methods:

- `add(request)`: To add a request object to the batch call.
- `execute()`: Will execute the batch request.

5.14.3 Example

```
var contract = new web3.eth.Contract(abi, address);

var batch = new web3.BatchRequest();
batch.add(web3.eth.getBalance.request('0x0000000000000000000000000000000000000000',
  ↳ 'latest', callback));
batch.add(contract.methods.balance(address).call.request({from:
  ↳ '0x0000000000000000000000000000000000000000'}, callback2));
batch.execute();
```

5.15 extend

```
web3.extend(methods)
web3.eth.extend(methods)
web3.shh.extend(methods)
web3.bzz.extend(methods)
...
```

Allows extending the web3 modules.

Note: You also have `*.extend.formatters` as additional formatter functions to be used for input and output formatting. Please see the [source file](#) for function details.

5.15.1 Parameters

1. **methods - Object:** Extension object with array of methods description objects as follows:

- **property - String:** (optional) The name of the property to add to the module. If no property is set it will be added to the module directly.
- **methods - Array:** The array of method descriptions:
 - **name - String:** Name of the method to add.
 - **call - String:** The RPC method name.
 - **params - Number:** (optional) The number of parameters for that function. Default 0.
 - **inputFormatter - Array:** (optional) Array of inputformatter functions. Each array item responds to a function parameter, so if you want some parameters not to be formatted, add a null instead.
 - **outputFormatter - Function:** (optional) Can be used to format the output of the method.

5.15.2 Returns

Object: The extended module.

5.15.3 Example

```
web3.extend({
  property: 'myModule',
  methods: [{
    name: 'getBalance',
    call: 'eth_getBalance',
    params: 2,
    inputFormatter: [web3.extend.formatters.inputAddressFormatter, web3.extend.
    ↪formatters.inputDefaultBlockNumberFormatter],
    outputFormatter: web3.utils.hexToNumberString
  }, {
    name: 'getGasPriceSuperFunction',
    call: 'eth_gasPriceSuper',
    params: 2,
    inputFormatter: [null, web3.utils.numberToHex]
  }]
});

web3.extend({
  methods: [{
    name: 'directCall',
    call: 'eth_callForFun',
  }]
});

console.log(web3);
> Web3 {
  myModule: {
    getBalance: function() {},
    getGasPriceSuperFunction: function() {}
  }
}
```

(continues on next page)

(continued from previous page)

```

    },
    directCall: function() {},
    eth: Eth {...},
    bzz: Bzz {...},
    ...
  }

```

5.16 defaultAccount

```
web3.eth.defaultAccount
```

This default address is used as the default "from" property, if no "from" property is specified in for the following methods:

- `web3.eth.sendTransaction()`
- `web3.eth.call()`
- `new web3.eth.Contract() -> myContract.methods.myMethod().call()`
- `new web3.eth.Contract() -> myContract.methods.myMethod().send()`

5.16.1 Property

String - 20 Bytes: Any ethereum address. You should have the private key for that address in your node or keystore. (Default is undefined)

5.16.2 Example

```

web3.eth.defaultAccount;
> undefined

// set the default account
web3.eth.defaultAccount = '0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe';

```

5.17 defaultBlock

```
web3.eth.defaultBlock
```

The default block is used for certain methods. You can override it by passing in the defaultBlock as last parameter. The default value is "latest".

- `web3.eth.getBalance()`
- `web3.eth.getCode()`

- `web3.eth.getTransactionCount()`
- `web3.eth.getStorageAt()`
- `web3.eth.call()`
- `new web3.eth.Contract() -> myContract.methods.myMethod().call()`

5.17.1 Property

Default block parameters can be one of the following:

- `Number | BN | BigNumber`: A block number
- `"earliest"` - String: The genesis block
- `"latest"` - String: The latest block (current head of the blockchain)
- `"pending"` - String: The currently mined block (including pending transactions)

Default is `"latest"`

5.17.2 Example

```
web3.eth.defaultBlock;  
> "latest"  
  
// set the default block  
web3.eth.defaultBlock = 231;
```

5.18 defaultHardfork

```
web3.eth.defaultHardfork
```

The default hardfork property is used for signing transactions locally.

5.18.1 Property

The default hardfork property can be one of the following:

- `"chainstart"` - String
- `"homestead"` - String
- `"dao"` - String
- `"tangerineWhistle"` - String
- `"spuriousDragon"` - String
- `"byzantium"` - String
- `"constantinople"` - String
- `"petersburg"` - String
- `"istanbul"` - String

Default is "petersburg"

5.18.2 Example

```
web3.eth.defaultHardfork;  
> "petersburg"  
  
// set the default block  
web3.eth.defaultHardfork = 'istanbul';
```

5.19 defaultChain

```
web3.eth.defaultChain
```

The default chain property is used for signing transactions locally.

5.19.1 Property

The default chain property can be one of the following:

- "mainnet" - String
- "goerli" - String
- "kovan" - String
- "rinkeby" - String
- "ropsten" - String

Default is "mainnet"

5.19.2 Example

```
web3.eth.defaultChain;  
> "mainnet"  
  
// set the default chain  
web3.eth.defaultChain = 'goerli';
```

5.20 defaultCommon

```
web3.eth.defaultCommon
```

The default common property is used for signing transactions locally.

5.20.1 Property

The default common property does contain the following Common object:

- **customChain - Object: The custom chain properties**
 - name - string: (optional) The name of the chain
 - networkId - number: Network ID of the custom chain
 - chainId - number: Chain ID of the custom chain
- baseChain - string: (optional) mainnet, goerli, kovan, rinkeby, or ropsten
- hardfork - string: (optional) chainstart, homestead, dao, tangerineWhistle, spuriousDragon, byzantium, constantinople, petersburg, or istanbul

Default is undefined.

5.20.2 Example

```
web3.eth.defaultCommon;  
> {customChain: {name: 'custom-network', chainId: 1, networkId: 1}, baseChain:  
  ↪ 'mainnet', hardfork: 'petersburg'}  
  
// set the default common  
web3.eth.defaultCommon = {customChain: {name: 'custom-network', chainId: 1,  
  ↪ networkId: 1}, baseChain: 'mainnet', hardfork: 'petersburg'};
```

5.21 transactionBlockTimeout

```
web3.eth.transactionBlockTimeout
```

The transactionBlockTimeout is used over socket-based connections. This option defines the amount of new blocks it should wait until the first confirmation happens, otherwise the PromiEvent rejects with a timeout error.

5.21.1 Returns

number: The current value of transactionBlockTimeout (default: 50)

5.21.2 Example

```
web3.eth.transactionBlockTimeout;  
> 50  
  
// set the transaction block timeout  
web3.eth.transactionBlockTimeout = 100;
```

5.22 transactionConfirmationBlocks

```
web3.eth.transactionConfirmationBlocks
```

This defines the number of blocks it requires until a transaction is considered confirmed.

5.22.1 Returns

number: The current value of transactionConfirmationBlocks (default: 24)

5.22.2 Example

```
web3.eth.transactionConfirmationBlocks;  
> 24  
  
// set the transaction confirmations blocks  
web3.eth.transactionConfirmationBlocks = 50;
```

5.23 transactionPollingTimeout

```
web3.eth.transactionPollingTimeout
```

The transactionPollingTimeout is used over HTTP connections. This option defines the number of seconds Web3 will wait for a receipt which confirms that a transaction was mined by the network. Note: If this method times out, the transaction may still be pending.

5.23.1 Returns

number: The current value of transactionPollingTimeout (default: 750)

5.23.2 Example

```
web3.eth.transactionPollingTimeout;  
> 750  
  
// set the transaction polling timeout  
web3.eth.transactionPollingTimeout = 1000;
```

5.24 handleRevert

```
web3.eth.handleRevert
```

The `handleRevert` options property defaults to `false` and returns the revert reason string if enabled for the following methods:

- `web3.eth.call()`
- `web3.eth.sendTransaction()`
- `contract.methods.myMethod(...).send(...)`
- `contract.methods.myMethod(...).call(...)`

Note: The revert reason string and signature exist as a property on the returned error.

5.24.1 Returns

boolean: The current value of `handleRevert` (default: `false`)

5.24.2 Example

```
web3.eth.handleRevert;  
> false  
  
// turn revert handling on  
web3.eth.handleRevert = true;
```

5.25 maxListenersWarningThreshold

```
web3.eth.maxListenersWarningThreshold
```

This defines the threshold above which a warning about the number of event listeners attached to a provider which supports sockets subscriptions will be written to the console. You may see this warning if you call `setProvider` on large numbers of Web3 contract objects.

5.25.1 Returns

number: The current value of `maxListenersWarningThreshold` (default: 100)

5.25.2 Example

```
web3.eth.maxListenersWarningThreshold;  
> 100  
  
// set the max listeners warning threshold  
web3.eth.maxListenersWarningThreshold = 200;
```

5.26 getProtocolVersion

```
web3.eth.getProtocolVersion([callback])
```

Returns the ethereum protocol version of the node.

5.26.1 Returns

Promise returns String: the protocol version.

5.26.2 Example

```
web3.eth.getProtocolVersion()  
.then(console.log);  
> "63"
```

5.27 isSyncing

```
web3.eth.isSyncing([callback])
```

Checks if the node is currently syncing and returns either a syncing object, or false.

5.27.1 Returns

Promise returns Object | Boolean - A sync object when the node is currently syncing or false:

- `startingBlock` - Number: The block number where the sync started.
- `currentBlock` - Number: The block number where the node is currently synced to.
- `highestBlock` - Number: The estimated block number to sync to.
- `knownStates` - Number: The number of estimated states to download.
- `pulledStates` - Number: The number of already downloaded states.

5.27.2 Example

```
web3.eth.isSyncing()  
.then(console.log);  
  
> {  
  startingBlock: 100,  
  currentBlock: 312,  
  highestBlock: 512,  
  knownStates: 234566,  
  pulledStates: 123455  
}
```

5.28 getCoinbase

```
getCoinbase([callback])
```

Returns the coinbase address to which mining rewards will go.

5.28.1 Returns

Promise returns String - bytes 20: The coinbase address set in the node for mining rewards.

5.28.2 Example

```
web3.eth.getCoinbase()  
.then(console.log);  
> "0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe"
```

5.29 isMining

```
web3.eth.isMining([callback])
```

Checks whether the node is mining or not.

5.29.1 Returns

Promise returns Boolean: true if the node is mining, otherwise false.

5.29.2 Example

```
web3.eth.isMining()  
.then(console.log);  
> true
```

5.30 getHashrate

```
web3.eth.getHashrate([callback])
```

Returns the number of hashes per second that the node is mining with.

5.30.1 Returns

Promise returns Number: Number of hashes per second.

5.30.2 Example

```
web3.eth.getHashrate()  
.then(console.log);  
> 493736
```

5.31 getGasPrice

```
web3.eth.getGasPrice([callback])
```

Returns the current gas price oracle. The gas price is determined by the last few blocks median gas price.

5.31.1 Returns

Promise returns String - Number string of the current gas price in wei.

See the *A note on dealing with big numbers in JavaScript*.

5.31.2 Example

```
web3.eth.getGasPrice()  
.then(console.log);  
> "20000000000"
```

5.32 getAccounts

```
web3.eth.getAccounts([callback])
```

Returns a list of accounts the node controls.

5.32.1 Returns

Promise returns Array - An array of addresses controlled by node.

5.32.2 Example

```
web3.eth.getAccounts()  
.then(console.log);  
> ["0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe",  
↪ "0xDCc6960376d6C6dEa93647383FfB245CfCed97Cf"]
```

5.33 getBlockNumber

```
web3.eth.getBlockNumber([callback])
```

Returns the current block number.

5.33.1 Returns

Promise returns Number - The number of the most recent block.

5.33.2 Example

```
web3.eth.getBlockNumber()  
.then(console.log);  
> 2744
```

5.34 getBalance

```
web3.eth.getBalance(address [, defaultBlock] [, callback])
```

Get the balance of an address at a given block.

5.34.1 Parameters

1. String - The address to get the balance of.
2. Number|String|BN|BigNumber - (optional) If you pass this parameter it will not use the default block set with [web3.eth.defaultBlock](#). Pre-defined block numbers as "earliest", "latest" and "pending" can also be used.
3. Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.34.2 Returns

Promise returns String - The current balance for the given address in wei.

See the A note on dealing with big numbers in JavaScript.

5.34.3 Example

```
web3.eth.getBalance("0x407d73d8a49eeb85d32cf465507dd71d507100c1")
  .then(console.log);
> "10000000000000"
```

5.35 getStorageAt

```
web3.eth.getStorageAt(address, position [, defaultBlock] [, callback])
```

Get the storage at a specific position of an address.

5.35.1 Parameters

1. String - The address to get the storage from.
2. Number|String|BN|BigNumber - The index position of the storage.
3. Number|String|BN|BigNumber - (optional) If you pass this parameter it will not use the default block set with [web3.eth.defaultBlock](#). Pre-defined block numbers as "earliest", "latest" and "pending" can also be used.
4. Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.35.2 Returns

Promise returns String - The value in storage at the given position.

5.35.3 Example

```
web3.eth.getStorageAt("0x407d73d8a49eeb85d32cf465507dd71d507100c1", 0)
  .then(console.log);
> "0x033456732123ffff2342342dd12342434324234234fd234fd23fd4f23d4234"
```

5.36 getCode

```
web3.eth.getCode(address [, defaultBlock] [, callback])
```

Get the code at a specific address.

5.36.1 Parameters

1. String - The address to get the code from.
2. Number|String|BN|BigNumber - (optional) If you pass this parameter it will not use the default block set with *web3.eth.defaultBlock*. Pre-defined block numbers as "earliest", "latest" and "pending" can also be used.
3. Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.36.2 Returns

Promise returns String - The data at given address address.

5.36.3 Example

```
web3.eth.getCode("0xd5677cf67b5aa051bb40496e68ad359eb97cfbf8")
.then(console.log);
>
↪ "0x600160008035811a818181146012578301005b601b6001356025565b8060005260206000f25b60006007820290509190"
↪ "
```

5.37getBlock

```
web3.eth.getBlock(blockHashOrBlockNumber [, returnTransactionObjects] [, callback])
```

Returns a block matching the block number or block hash.

5.37.1 Parameters

1. String|Number|BN|BigNumber - The block number or block hash. Or the string "earliest", "latest" or "pending" as in the *default block parameter*.
2. Boolean - (optional, default false) If specified true, the returned block will contain all transactions as objects. If false it will only contains the transaction hashes.
3. Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.37.2 Returns

Promise returns Object - The block object:

- number - Number: The block number. null if a pending block.
- hash 32 Bytes - String: Hash of the block. null if a pending block.
- parentHash 32 Bytes - String: Hash of the parent block.
- nonce 8 Bytes - String: Hash of the generated proof-of-work. null if a pending block.
- sha3Uncles 32 Bytes - String: SHA3 of the uncles data in the block.

- `logsBloom` 256 Bytes - String: The bloom filter for the logs of the block. `null` if a pending block.
- `transactionsRoot` 32 Bytes - String: The root of the transaction trie of the block.
- `stateRoot` 32 Bytes - String: The root of the final state trie of the block.
- `miner` - String: The address of the beneficiary to whom the mining rewards were given.
- `difficulty` - String: Integer of the difficulty for this block.
- `totalDifficulty` - String: Integer of the total difficulty of the chain until this block.
- `extraData` - String: The “extra data” field of this block.
- `size` - Number: Integer the size of this block in bytes.
- `gasLimit` - Number: The maximum gas allowed in this block.
- `gasUsed` - Number: The total used gas by all transactions in this block.
- `timestamp` - Number: The unix timestamp for when the block was collated.
- `transactions` - Array: Array of transaction objects, or 32 Bytes transaction hashes depending on the `returnTransactionObjects` parameter.
- `uncles` - Array: Array of uncle hashes.

5.37.3 Example

[illegible]

5.38 getBlockTransactionCount

```
web3.eth.getBlockTransactionCount(blockHashOrBlockNumber [, callback])
```

Returns the number of transaction in a given block.

5.38.1 Parameters

1. `String|Number|BN|BigNumber` - The block number or hash. Or the string "earliest", "latest" or "pending" as in the *default block parameter*.
2. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.38.2 Returns

Promise returns `Number` - The number of transactions in the given block.

5.38.3 Example

```
web3.eth.getBlockTransactionCount("0x407d73d8a49eeb85d32cf465507dd71d507100c1")  
.then(console.log);  
> 1
```

5.39 getBlockUncleCount

```
web3.eth.getBlockUncleCount(blockHashOrBlockNumber [, callback])
```

Returns the number of uncles in a block from a block matching the given block hash.

5.39.1 Parameters

1. `String|Number|BN|BigNumber` - The block number or hash. Or the string "earliest", "latest" or "pending" as in the *default block parameter*.
2. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.39.2 Returns

Promise returns `Number` - The number of transactions in the given block.

5.39.3 Example

```
web3.eth.getBlockUncleCount("0x407d73d8a49eeb85d32cf465507dd71d507100c1")
  .then(console.log);
> 1
```

5.40 getUncle

```
web3.eth.getUncle(blockHashOrBlockNumber, uncleIndex [, returnTransactionObjects] [,   
↪callback])
```

Returns a blocks uncle by a given uncle index position.

5.40.1 Parameters

1. String|Number|BN|BigNumber - The block number or hash. Or the string "earliest", "latest" or "pending" as in the *default block parameter*.
2. Number - The index position of the uncle.
3. Boolean - (optional, default false) If specified true, the returned block will contain all transactions as objects. By default it is false so, there is no need to explicitly specify false. And, if false it will only contains the transaction hashes.
4. Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.40.2 Returns

Promise returns Object - the returned uncle. For a return value see *web3.eth.getBlock()*.

Note: An uncle doesn't contain individual transactions.

5.40.3 Example

```
web3.eth.getUncle(500, 0)
  .then(console.log);
> // see web3.eth.getBlock
```

5.41 getTransaction

```
web3.eth.getTransaction(transactionHash [, callback])
```

Returns a transaction matching the given transaction hash.

5.41.1 Parameters

1. String - The transaction hash.
2. Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.41.2 Returns

Promise returns Object - A transaction object its hash transactionHash:

- hash 32 Bytes - String: Hash of the transaction.
- nonce - Number: The number of transactions made by the sender prior to this one.
- blockHash 32 Bytes - String: Hash of the block where this transaction was in. null if pending.
- blockNumber - Number: Block number where this transaction was in. null if pending.
- transactionIndex - Number: Integer of the transactions index position in the block. null if pending.
- from - String: Address of the sender.
- to - String: Address of the receiver. null if it's a contract creation transaction.
- value - String: Value transferred in wei.
- gasPrice - String: Gas price provided by the sender in wei.
- gas - Number: Gas provided by the sender.
- input - String: The data sent along with the transaction.

5.41.3 Example

```
web3.eth.getTransaction(
  ↪ '0x9fc76417374aa880d4449a1f7f31ec597f00b1f6f3dd2d66f4c9c6c445836d8b5234')
  .then(console.log);

> {
  "hash": "0x9fc76417374aa880d4449a1f7f31ec597f00b1f6f3dd2d66f4c9c6c445836d8b",
  "nonce": 2,
  "blockHash": "0xef95f2f1ed3ca60b048b4bf67cde2195961e0bba6f70bcbea9a2c4e133e34b46",
  "blockNumber": 3,
  "transactionIndex": 0,
  "from": "0xa94f5374fce5edbc8e2a8697c15331677e6ebf0b",
  "to": "0x6295ee1b4f6dd65047762f924ecd367c17eabf8f",
  "value": '123450000000000000',
  "gas": 314159,
  "gasPrice": '2000000000000',
  "input": "0x57cb2fc4"
}
```

5.42 getPendingTransactions

```
web3.eth.getPendingTransactions([, callback])
```

Returns a list of pending transactions.

5.42.1 Parameters

1. **Function** - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.42.2 Returns

Promise<object[]> - Array of pending transactions:

- **hash** 32 Bytes - String: Hash of the transaction.
- **nonce** - Number: The number of transactions made by the sender prior to this one.
- **blockHash** 32 Bytes - String: Hash of the block where this transaction was in. null if pending.
- **blockNumber** - Number: Block number where this transaction was in. null if pending.
- **transactionIndex** - Number: Integer of the transactions index position in the block. null if pending.
- **from** - String: Address of the sender.
- **to** - String: Address of the receiver. null when it's a contract creation transaction.
- **value** - String: Value transferred in wei.
- **gasPrice** - String: The wei per unit of gas provided by the sender in wei.
- **gas** - Number: Gas provided by the sender.
- **input** - String: The data sent along with the transaction.

5.42.3 Example

```
web3.eth.getPendingTransactions().then(console.log);
> [
  {
    hash: '0x9fc76417374aa880d4449a1f7f31ec597f00b1f6f3dd2d66f4c9c6c445836d8b',
    nonce: 2,
    blockHash:
    ↪ '0xef95f2f1ed3ca60b048b4bf67cde2195961e0bba6f70bcbea9a2c4e133e34b46',
    blockNumber: 3,
    transactionIndex: 0,
    from: '0xa94f5374fce5edbc8e2a8697c15331677e6ebf0b',
    to: '0x6295ee1b4f6dd65047762f924ecd367c17eabf8f',
    value: '123450000000000000',
    gas: 314159,
    gasPrice: '20000000000000',
    input: '0x57cb2fc4'
    v: '0x3d',
    r: '0xaabc9ddaafffb2ae0bac4107697547d22d9383667d9e97f5409dd6881ce08f13f',
    s: '0x69e43116be8f842dcd4a0b2f760043737a59534430b762317db21d9ac8c5034'
  }, ..., {
    hash: '0x9fc76417374aa880d4449a1f7f31ec597f00b1f6f3dd2d66f4c9c6c445836d8b',
    nonce: 3,
```

(continues on next page)

(continued from previous page)

```
    blockHash:
    ↪ '0xef95f2f1ed3ca60b048b4bf67cde2195961e0bba6f70bcbea9a2c4e133e34b46',
    blockNumber: 4,
    transactionIndex: 0,
    from: '0xa94f5374fcea5edbc8e2a8697c15331677e6ebf0b',
    to: '0x6295eelb4f6dd65047762f924ecd367c17eabf8f',
    value: '123450000000000000',
    gas: 314159,
    gasPrice: '2000000000000',
    input: '0x57cb2fc4'
    v: '0x3d',
    r: '0xaabc9ddaafffb2ae0bac4107697547d22d9383667d9e97f5409dd6881ce08f13f',
    s: '0x69e43116be8f842dcd4a0b2f760043737a59534430b762317db21d9ac8c5034'
  }
]
```

5.43 getTransactionFromBlock

```
getTransactionFromBlock(hashStringOrNumber, indexNumber [, callback])
```

Returns a transaction based on a block hash or number and the transaction's index position.

5.43.1 Parameters

1. String|Number|BN|BigNumber - A block number or hash. Or the string "earliest", "latest" or "pending" as in the *default block parameter*.
2. Number - The transaction's index position.
3. Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.43.2 Returns

Promise returns Object - A transaction object, see *web3.eth.getTransaction*:

5.43.3 Example

```
var transaction = web3.eth.getTransactionFromBlock('0x4534534534', 2)
  .then(console.log);
> // see web3.eth.getTransaction
```

5.44 getTransactionReceipt

```
web3.eth.getTransactionReceipt(hash [, callback])
```

Returns the receipt of a transaction by transaction hash.

Note: The receipt is not available for pending transactions and returns `null`.

5.44.1 Parameters

1. `String` - The transaction hash.
2. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.44.2 Returns

Promise returns Object - A transaction receipt object, or `null` if no receipt was found:

- `status` - `Boolean`: `TRUE` if the transaction was successful, `FALSE` if the EVM reverted the transaction.
- `blockHash` 32 Bytes - `String`: Hash of the block where this transaction was in.
- `blockNumber` - `Number`: Block number where this transaction was in.
- `transactionHash` 32 Bytes - `String`: Hash of the transaction.
- `transactionIndex` - `Number`: Integer of the transactions index position in the block.
- `from` - `String`: Address of the sender.
- `to` - `String`: Address of the receiver. `null` when it's a contract creation transaction.
- `contractAddress` - `String`: The contract address created, if the transaction was a contract creation, otherwise `null`.
- `cumulativeGasUsed` - `Number`: The total amount of gas used when this transaction was executed in the block.
- `gasUsed` - `Number`: The amount of gas used by this specific transaction alone.
- `logs` - `Array`: Array of log objects, which this transaction generated.

5.44.3 Example

```
var receipt = web3.eth.getTransactionReceipt(
  ↪ '0x9fc76417374aa880d4449a1f7f31ec597f00b1f6f3dd2d66f4c9c6c445836d8b')
  .then(console.log);

> {
  "status": true,
  "transactionHash":
  ↪ '0x9fc76417374aa880d4449a1f7f31ec597f00b1f6f3dd2d66f4c9c6c445836d8b',
  "transactionIndex": 0,
  "blockHash": "0xef95f2f1ed3ca60b048b4bf67cde2195961e0bba6f70bcbea9a2c4e133e34b46",
  "blockNumber": 3,
  "contractAddress": "0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe",
  "cumulativeGasUsed": 314159,
```

(continues on next page)

(continued from previous page)

```
"gasUsed": 30234,  
"logs": [{  
    // logs as returned by getPastLogs, etc.  
    }, ...]  
}
```

5.45 getTransactionCount

```
web3.eth.getTransactionCount(address [, defaultBlock] [, callback])
```

Get the number of transactions sent from this address.

5.45.1 Parameters

1. String - The address to get the numbers of transactions from.
2. Number|String|BN|BigNumber - (optional) If you pass this parameter it will not use the default block set with *web3.eth.defaultBlock*. Pre-defined block numbers as "earliest", "latest" and "pending" can also be used.
3. Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.45.2 Returns

Promise returns Number - The number of transactions sent from the given address.

5.45.3 Example

```
web3.eth.getTransactionCount("0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe")  
  .then(console.log);  
> 1
```

5.46 sendTransaction

```
web3.eth.sendTransaction(transactionObject [, callback])
```

Sends a transaction to the network.

5.46.1 Parameters

1. Object - The transaction object to send:

- `from` - `String|Number`: The address for the sending account. Uses the `web3.eth.defaultAccount` property, if not specified. Or an address or index of a local wallet in `web3.eth.accounts.wallet`.
- `to` - `String`: (optional) The destination address of the message, left undefined for a contract-creation transaction.
- `value` - `Number|String|BN|BigNumber`: (optional) The value transferred for the transaction in wei, also the endowment if it's a contract-creation transaction.
- `gas` - `Number`: (optional, default: To-Be-Determined) The amount of gas to use for the transaction (unused gas is refunded).
- `gasPrice` - `Number|String|BN|BigNumber`: (optional) The price of gas for this transaction in wei, defaults to [web3.eth.gasPrice](#).
- `data` - `String`: (optional) Either a [ABI byte string](#) containing the data of the function call on a contract, or in the case of a contract-creation transaction the initialisation code.
- `nonce` - `Number`: (optional) Integer of the nonce. This allows to overwrite your own pending transactions that use the same nonce.
- `chain` - `String`: (optional) Defaults to `mainnet`.
- `hardfork` - `String`: (optional) Defaults to `petersburg`.
- **common - Object: (optional) The common object**
 - **customChain - Object: The custom chain properties**
 - * `name` - `string`: (optional) The name of the chain
 - * `networkId` - `number`: Network ID of the custom chain
 - * `chainId` - `number`: Chain ID of the custom chain
 - `baseChain` - `string`: (optional) `mainnet`, `goerli`, `kovan`, `rinkeby`, or `ropsten`
 - `hardfork` - `string`: (optional) `chainstart`, `homestead`, `dao`, `tangerineWhistle`, `spuriousDragon`, `byzantium`, `constantinople`, `petersburg`, or `istanbul`

2. `callback` - `Function`: (optional) Optional callback, returns an error object as first parameter and the result as second.

Note: The `from` property can also be an address or index from the `web3.eth.accounts.wallet`. It will then sign locally using the private key of that account, and send the transaction via [web3.eth.sendSignedTransaction\(\)](#). If the properties `chain` and `hardfork` or `common` are not set, Web3 will try to set appropriate values by querying the network for its `chainId` and `networkId`.

5.46.2 Returns

The **callback** will return the 32 bytes transaction hash.

PromiEvent: A [promise combined event emitter](#). Resolves when the transaction [receipt](#) is available. The following events are also available:

- `sending` returns payload: `Object`: Fired immediately before transmitting the transaction request.

- `sent` returns `payload: Object`: Fired immediately after the request body has been written to the client, but before the transaction hash is received.
- `"transactionHash"` returns `transactionHash: String`: Fired when the transaction hash is available.
- `"receipt"` returns `receipt: Object`: Fired when the transaction receipt is available.
- `"confirmation"` returns `confirmationNumber: Number`, `receipt: Object`, `latestBlockHash: String`: Fired for every confirmation up to the 12th confirmation. Receives the confirmation number as the first and the *receipt* as the second argument. Fired from confirmation 0 on, which is the block where it's mined.

"error" returns error: Error: Fired if an error occurs during sending. If the transaction was rejected by the network with a receipt, the receipt will be available as a property on the error object.

5.46.3 Example

[illegible]

5.48 sign

```
web3.eth.sign(dataToSign, address [, callback])
```

Signs data using a specific account. This account needs to be unlocked.

5.48.1 Parameters

1. `String` - Data to sign. If it is a string it will be converted using *web3.utils.utf8ToHex*.
2. `String|Number` - Address to sign data with. Can be an address or the index of a local wallet in `web3.eth.accounts.wallet`.
3. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.48.2 Returns

Promise returns `String` - The signature.

5.48.3 Example

```
web3.eth.sign("Hello world", "0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe")
.then(console.log);
>
↪ "0x30755ed65396facf86c53e6217c52b4daebe72aa4941d89635409de4c9c7f9466d4e9aaec7977f05e923889b33c0d0d
↪ "

// the below is the same
web3.eth.sign(web3.utils.utf8ToHex("Hello world"),
↪ "0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe")
.then(console.log);
>
↪ "0x30755ed65396facf86c53e6217c52b4daebe72aa4941d89635409de4c9c7f9466d4e9aaec7977f05e923889b33c0d0d
↪ "
```

5.49 signTransaction

```
web3.eth.signTransaction(transactionObject, address [, callback])
```

Signs a transaction. This account needs to be unlocked.

5.49.1 Parameters

1. **Object** - The transaction data to sign. See [web3.eth.sendTransaction\(\)](#) for more.
2. **String** - Address to sign transaction with.
3. **Function** - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.49.2 Returns

Promise returns Object - The RLP encoded transaction. The `raw` property can be used to send the transaction using `web3.eth.sendSignedTransaction`.

5.49.3 Example

[illegible]

5.50 call

```
web3.eth.call(callObject [, defaultBlock] [, callback])
```

Executes a message call transaction, which is directly executed in the VM of the node, but never mined into the blockchain.

5.50.1 Parameters

1. **Object** - A transaction object, see [web3.eth.sendTransaction](#). For calls the `from` property is optional however it is highly recommended to explicitly set it or it may default to `address(0)` depending on your node or provider.
2. **Number|String|BN|BigNumber** - (optional) If you pass this parameter it will not use the default block set with [web3.eth.defaultBlock](#). Pre-defined block numbers as "earliest", "latest" and "pending" can also be used.
3. **Function** - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.50.2 Returns

Promise returns **String**: The returned data of the call, e.g. a smart contract functions return value.

5.50.3 Example

```
web3.eth.call({
  to: "0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe", // contract address
  data: "0xc6888fa100000000000000000000000000000000000000000000000000000003"
})
.then(console.log);
> "0x000000000000000000000000000000000000000000000000000000000000000a"
```

5.51 estimateGas

```
web3.eth.estimateGas(callObject [, callback])
```

Executes a message call or transaction and returns the amount of the gas used. Note: You must specify a `from` address otherwise you may experience odd behavior.

5.51.1 Parameters

1. **Object** - A transaction object, see [web3.eth.sendTransaction](#) with the difference that for calls the `from` property is optional as well.
2. **Function** - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.51.2 Returns

Promise returns **Number** - the used gas for the simulated call/transaction.

5.51.3 Example

```
web3.eth.estimateGas({
  to: "0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe",
  data: "0xc6888fa100000000000000000000000000000000000000000000000000000003"
})
.then(console.log);
> "0x0000000000000000000000000000000000000000000000000000000000000015"
```

5.52 getPastLogs

```
web3.eth.getPastLogs(options [, callback])
```

Gets past logs, matching the given options.

5.52.1 Parameters

1. Object - The filter options as follows:

- `fromBlock` - Number|String: The number of the earliest block ("latest" may be given to mean the most recent and "pending" currently mining, block). By default "latest".
- `toBlock` - Number|String: The number of the latest block ("latest" may be given to mean the most recent and "pending" currently mining, block). By default "latest".
- `address` - String|Array: An address or a list of addresses to only get logs from particular account(s).
- `topics` - Array: An array of values which must each appear in the log entries. The order is important, if you want to leave topics out use null, e.g. [null, '0x12...']. You can also pass an array for each topic with options for that topic e.g. [null, ['option1', 'option2']]

5.52.2 Returns

Promise returns Array - Array of log objects.

The structure of the returned event Object in the Array looks as follows:

- `address` - String: From which this event originated from.
- `data` - String: The data containing non-indexed log parameter.
- `topics` - Array: An array with max 4 32 Byte topics, topic 1-3 contains indexed parameters of the log.
- `logIndex` - Number: Integer of the event index position in the block.
- `transactionIndex` - Number: Integer of the transaction's index position, the event was created in.
- `transactionHash` 32 Bytes - String: Hash of the transaction this event was created in.
- `blockHash` 32 Bytes - String: Hash of the block where this event was created in. null if still pending.
- `blockNumber` - Number: The block number where this log was created in. null if still pending.

5.52.3 Example

```
web3.eth.getPastLogs({
  address: "0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe",
  topics: ["0x033456732123ffff2342342dd12342434324234234fd234fd23fd4f23d4234"]
})
.then(console.log);

> [{
  data: '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385',
  topics: ['0xfd43adelc09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
    ↪ '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385'],
  logIndex: 0,
  transactionIndex: 0,
  transactionHash:
    ↪ '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385',
  blockHash: '0xfd43adelc09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
  blockNumber: 1234,
  address: '0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'
}, {...}]
```

5.53 getWork

```
web3.eth.getWork([callback])
```

Gets work for miners to mine on. Returns the hash of the current block, the seedHash, and the boundary condition to be met (“target”).

5.53.1 Parameters

1. Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.53.2 Returns

Promise returns Array - the mining work with the following structure:

- String 32 Bytes - at **index 0**: current block header pow-hash
- String 32 Bytes - at **index 1**: the seed hash used for the DAG.
- String 32 Bytes - at **index 2**: the boundary condition (“target”), 2^{256} / difficulty.

5.53.3 Example

```
web3.eth.getWork()
.then(console.log);

> [
  "0x1234567890abcdef1234567890abcdef1234567890abcdef1234567890abcdef",
  "0x5EED000000000000000000000000000000000000000000000000000000000000",
  "0xd1ff1c0171000000000000000000000000d1ff1c017100000000000000000000"
]
```

5.54 submitWork

```
web3.eth.submitWork(nonce, powHash, digest, [callback])
```

Used for submitting a proof-of-work solution.

5.54.1 Parameters

1. String 8 Bytes: The nonce found (64 bits)
2. String 32 Bytes: The header's pow-hash (256 bits)
3. String 32 Bytes: The mix digest (256 bits)
4. Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.54.2 Returns

Promise returns Boolean - Returns TRUE if the provided solution is valid, otherwise FALSE.

5.54.3 Example

```
web3.eth.submitWork([
  "0x0000000000000001",
  "0x1234567890abcdef1234567890abcdef1234567890abcdef1234567890abcdef",
  "0xD1FE5700000000000000000000000000D1FE57000000000000000000000000"
])
.then(console.log);
> true
```

5.55 requestAccounts

```
web3.eth.requestAccounts([callback])
```

This method will request/enable the accounts from the current environment. This method will only work if you're using the injected provider from a application like Metamask, Status or TrustWallet. It doesn't work if you're connected to a node with a default Web3.js provider (WebsocketProvider, HttpProvider and IpcProvider).

For more information about the behavior of this method please read [EIP-1102: Opt-in account exposure](#).

5.55.1 Parameters

1. Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.55.2 Returns

Promise<Array> - Returns an array of enabled accounts.

5.55.3 Example

```
web3.eth.requestAccounts().then(console.log);  
> [ '0aae0B295369a9FD31d5F28D9Ec85E40f4cb692BAf',  
  ↪ '0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe' ]
```

5.56 getChainId

```
web3.eth.getChainId([callback])
```

Returns the chain ID of the current connected node as described in the [EIP-695](#).

5.56.1 Returns

Promise<Number> - Returns chain ID.

5.56.2 Example

```
web3.eth.getChainId().then(console.log);  
> 61
```

5.57 getNodeInfo

```
web3.eth.getNodeInfo([callback])
```

5.57.1 Returns

Promise<String> - The current client version.

5.57.2 Example

```
web3.eth.getNodeInfo().then(console.log);  
> "Mist/v0.9.3/darwin/go1.4.1"
```

5.58 getProof

```
web3.eth.getProof(address, storageKey, blockNumber, [callback])
```

Returns the account and storage-values of the specified account including the Merkle-proof as described in [EIP-1186](#).

5.58.1 Parameters

1. String 20 Bytes: The Address of the account or contract.
2. Number[] | BigNumber[] | BN[] | String[] 32 Bytes: Array of storage-keys which should be proofed and included. See `web3.eth.getStorageAt`.
3. Number | String | BN | BigNumber: Integer block number. Pre-defined block numbers as "earliest", "latest" and "pending" can also be used.
4. Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.58.2 Returns

Promise<Object> - A account object.

- address - String: The address of the account.
- balance - String: The balance of the account. See `web3.eth.getBalance`.
- codeHash - String: hash of the code of the account. For a simple account without code it will return "0xc5d2460186f7233c927e7db2dcc703c0e500b653ca82273b7bfad8045d85a470".
- nonce - String: Nonce of the account.
- storageHash - String: SHA3 of the StorageRoot. All storage will deliver a MerkleProof starting with this rootHash.
- accountProof - String[]: Array of rlp-serialized MerkleTree-Nodes, starting with the stateRoot-Node, following the path of the SHA3 (address) as key.
- **storageProof - Object [] Array of storage-entries as requested.**
 - key - String The requested storage key.
 - value - String The storage value.

5.58.3 Example

```
web3.eth.getProof(
  "0x1234567890123456789012345678901234567890",
  ["0x0000000000000000000000000000000000000000000000000000000000000000",
  ↪ "0x0000000000000000000000000000000000000000000000000000000000000001"],
  "latest"
).then(console.log);
> {
  "address": "0x1234567890123456789012345678901234567890",
  "accountProof": [
    ↪ "0xf90211a090dcdf88c40c7bb95a912cbdde67c175767b31173df9ee4b0d733bfdd511c43a0babe369f6b12092f49181a",
    ↪ "0x",
```

(continues on next page)

(continued from previous page)

[illegible]

web3.eth.subscribe

The `web3.eth.subscribe` function lets you subscribe to specific events in the blockchain.

6.1 subscribe

```
web3.eth.subscribe(type [, options] [, callback]);
```

6.1.1 Parameters

1. `String` - The subscription you want to subscribe to.
2. `Mixed` - (optional) Optional additional parameters, depending on the subscription type.
3. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second. Will be called for each incoming subscription, and the subscription itself as the 3rd parameter.

6.1.2 Returns

`EventEmitter` - A Subscription instance

- `subscription.id`: The subscription id, used to identify and unsubscribing the subscription.
- `subscription.subscribe([callback])`: Can be used to re-subscribe with the same parameters.
- `subscription.unsubscribe([callback])`: Unsubscribes the subscription and returns *TRUE* in the callback if successful.
- `subscription.arguments`: The subscription arguments, used when re-subscribing.
- `on("data")` returns `Object`: Fires on each incoming log with the log object as argument.
- `on("changed")` returns `Object`: Fires on each log which was removed from the blockchain. The log will have the additional property `"removed: true"`.

- `on("error")` returns `Object`: Fires when an error in the subscription occurs.
- `on("connected")` returns `String`: Fires once after the subscription successfully connected. Returns the subscription id.

6.1.3 Notification returns

- Mixed - depends on the subscription, see the different subscriptions for more.

6.1.4 Example

```
var subscription = web3.eth.subscribe('logs', {
  address: '0x123456..',
  topics: ['0x12345...']
}, function(error, result){
  if (!error)
    console.log(result);
});

// unsubscribes the subscription
subscription.unsubscribe(function(error, success){
  if(success)
    console.log('Successfully unsubscribed!');
});
```

6.2 clearSubscriptions

```
web3.eth.clearSubscriptions()
```

Resets subscriptions.

Note: This will not reset subscriptions from other packages like `web3-shh`, as they use their own `requestManager`.

6.2.1 Parameters

1. Boolean: If `true` it keeps the "syncing" subscription.

6.2.2 Returns

Boolean

6.2.3 Example

```
web3.eth.subscribe('logs', {}, function(){ ... });

...

web3.eth.clearSubscriptions();
```

6.3 subscribe(“pendingTransactions”)

```
web3.eth.subscribe('pendingTransactions' [, callback]);
```

Subscribes to incoming pending transactions.

6.3.1 Parameters

1. String - "pendingTransactions", the type of the subscription.
2. Function - (optional) Optional callback, returns an error object as first parameter and the result as second. Will be called for each incoming subscription.

6.3.2 Returns

EventEmitter: An *subscription instance* as an event emitter with the following events:

- "data" returns String: Fires on each incoming pending transaction and returns the transaction hash.
- "error" returns Object: Fires when an error in the subscription occurs.

6.3.3 Notification returns

1. Object|Null - First parameter is an error object if the subscription failed.
2. String - Second parameter is the transaction hash.

6.3.4 Example

```
var subscription = web3.eth.subscribe('pendingTransactions', function(error, result){
  if (!error)
    console.log(result);
})
.on("data", function(transaction){
  console.log(transaction);
});

// unsubscribes the subscription
subscription.unsubscribe(function(error, success){
  if (success)
    console.log('Successfully unsubscribed!');
});
```

6.4 subscribe("newBlockHeaders")

```
web3.eth.subscribe('newBlockHeaders' [, callback]);
```

Subscribes to incoming block headers. This can be used as timer to check for changes on the blockchain.

6.4.1 Parameters

1. **String** - "newBlockHeaders", the type of the subscription.
2. **Function** - (optional) Optional callback, returns an error object as first parameter and the result as second. Will be called for each incoming subscription.

6.4.2 Returns

EventEmitter: An *subscription instance* as an event emitter with the following events:

- "data" returns **Object**: Fires on each incoming block header.
- "error" returns **Object**: Fires when an error in the subscription occurs.
- "connected" returns **Number**: Fires once after the subscription successfully connected. Returns the subscription id.

The structure of a returned block header is as follows:

- **number** - **Number**: The block number. `null` when its pending block.
- **hash** 32 Bytes - **String**: Hash of the block. `null` when its pending block.
- **parentHash** 32 Bytes - **String**: Hash of the parent block.
- **nonce** 8 Bytes - **String**: Hash of the generated proof-of-work. `null` when its pending block.
- **sha3Uncles** 32 Bytes - **String**: SHA3 of the uncles data in the block.
- **logsBloom** 256 Bytes - **String**: The bloom filter for the logs of the block. `null` when its pending block.
- **transactionsRoot** 32 Bytes - **String**: The root of the transaction trie of the block
- **stateRoot** 32 Bytes - **String**: The root of the final state trie of the block.
- **receiptsRoot** 32 Bytes - **String**: The root of the receipts.
- **miner** - **String**: The address of the beneficiary to whom the mining rewards were given.
- **extraData** - **String**: The "extra data" field of this block.
- **gasLimit** - **Number**: The maximum gas allowed in this block.
- **gasUsed** - **Number**: The total used gas by all transactions in this block.
- **timestamp** - **Number**: The unix timestamp for when the block was collated.

6.4.3 Notification returns

1. **Object | Null** - First parameter is an error object if the subscription failed.
2. **Object** - The block header object like above.

6.4.4 Example

```
var subscription = web3.eth.subscribe('newBlockHeaders', function(error, result){
  if (!error) {
    console.log(result);

    return;
  }

  console.error(error);
})
.on("connected", function(subscriptionId){
  console.log(subscriptionId);
})
.on("data", function(blockHeader){
  console.log(blockHeader);
})
.on("error", console.error);

// unsubscribes the subscription
subscription.unsubscribe(function(error, success){
  if (success) {
    console.log('Successfully unsubscribed!');
  }
});
```

6.5 subscribe(“syncing”)

```
web3.eth.subscribe('syncing' [, callback]);
```

Subscribe to syncing events. This will return an object when the node is syncing and when it's finished syncing will return FALSE.

6.5.1 Parameters

1. String - "syncing", the type of the subscription.
2. Function - (optional) Optional callback, returns an error object as first parameter and the result as second. Will be called for each incoming subscription.

6.5.2 Returns

EventEmitter: An *subscription instance* as an event emitter with the following events:

- "data" returns Object: Fires on each incoming sync object as argument.
- "changed" returns Object: Fires when the synchronisation is started with `true` and when finished with `false`.
- "error" returns Object: Fires when an error in the subscription occurs.

For the structure of a returned event Object see [web3.eth.isSyncing return values](#).

6.5.3 Notification returns

1. `Object|Null` - First parameter is an error object if the subscription failed.
2. `Object|Boolean` - The syncing object, when started it will return `true` once or when finished it will return `false` once.

6.5.4 Example

```
var subscription = web3.eth.subscribe('syncing', function(error, sync){
  if (!error)
    console.log(sync);
})
.on("data", function(sync){
  // show some syncing stats
})
.on("changed", function(isSyncing){
  if(isSyncing) {
    // stop app operation
  } else {
    // regain app operation
  }
});

// unsubscribes the subscription
subscription.unsubscribe(function(error, success){
  if(success)
    console.log('Successfully unsubscribed!');
});
```

6.6 subscribe("logs")

```
web3.eth.subscribe('logs', options [, callback]);
```

Subscribes to incoming logs, filtered by the given options. If a valid numerical `fromBlock` options property is set, Web3 will retrieve logs beginning from this point, backfilling the response as necessary.

6.6.1 Parameters

1. `"logs"` - String, the type of the subscription.
2. `Object` - The subscription options
 - `fromBlock` - Number: The `fromBlock` dictates at which block the subscription will start from, if it is left empty, the default is `latest` (a.k.a the chain head)
 - `address` - String|Array: An address or a list of addresses to only get logs from particular account(s).
 - `topics` - Array: An array of values which must each appear in the log entries. The order is important, if you want to leave topics out use `null`, e.g. `[null, '0x00...']`. You can also pass another array for each topic with options for that topic e.g. `[null, ['option1', 'option2']]`

3. `callback` - Function: (optional) Optional callback, returns an error object as first parameter and the result as second. Will be called for each incoming subscription.

6.6.2 Returns

EventEmitter: A *subscription instance* as an event emitter with the following events:

- `"data"` returns Object: Fires on each incoming log with the log object as argument.
- `"changed"` returns Object: Fires on each log which was removed from the blockchain. The log will have the additional property `"removed: true"`.
- `"error"` returns Object: Fires when an error in the subscription occurs.
- `"connected"` returns Number: Fires once after the subscription successfully connected. Returns the subscription id.

For the structure of a returned event Object see *web3.eth.getPastEvents return values*.

6.6.3 Notification returns

1. Object | Null - First parameter is an error object if the subscription failed.
2. Object - The log object like in *web3.eth.getPastEvents return values*.

6.6.4 Example

```
var subscription = web3.eth.subscribe('logs', {
  address: '0x123456..',
  topics: ['0x12345...']
}, function(error, result){
  if (!error)
    console.log(result);
})
.on("connected", function(subscriptionId){
  console.log(subscriptionId);
})
.on("data", function(log){
  console.log(log);
})
.on("changed", function(log){
});

// unsubscribes the subscription
subscription.unsubscribe(function(error, success){
  if (success)
    console.log('Successfully unsubscribed!');
});
```


CHAPTER 7

web3.eth.Contract

The `web3.eth.Contract` object makes it easy to interact with smart contracts on the ethereum blockchain. When you create a new contract object you give it the json interface of the respective smart contract and web3 will auto convert all calls into low level ABI calls over RPC for you.

This allows you to interact with smart contracts as if they were JavaScript objects.

To use it standalone:

```
var Contract = require('web3-eth-contract');

// set provider for all later instances to use
Contract.setProvider('ws://localhost:8546');

var contract = new Contract(jsonInterface, address);

contract.methods.somFunc().send({from: ....})
.on('receipt', function(){
  ...
});
```

7.1 new contract

```
new web3.eth.Contract(jsonInterface[, address][, options])
```

Creates a new contract instance with all its methods and events defined in its *json interface* object.

7.1.1 Parameters

1. `jsonInterface` - Object: The json interface for the contract to instantiate

2. `address` - `String` (optional): The address of the smart contract to call.
3. **`options` - `Object` (optional): The options of the contract. Some are used as fallbacks for calls and transactions:**
 - `from` - `String`: The address transactions should be made from.
 - `gasPrice` - `String`: The gas price in wei to use for transactions.
 - `gas` - `Number`: The maximum gas provided for a transaction (gas limit).
 - `data` - `String`: The byte code of the contract. Used when the contract gets *deployed*.

7.1.2 Returns

`Object`: The contract instance with all its methods and events.

7.1.3 Example

```
var myContract = new web3.eth.Contract([...],
  ↪ '0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe', {
    from: '0x1234567890123456789012345678901234567891', // default from address
    gasPrice: '20000000000' // default gas price in wei, 20 gwei in this case
  });
```

7.2 = Properties =

7.3 defaultAccount

```
web3.eth.Contract.defaultAccount
contract.defaultAccount // on contract instance
```

This default address is used as the default `"from"` property, if no `"from"` property is specified in for the following methods:

- `web3.eth.sendTransaction()`
- `web3.eth.call()`
- `new web3.eth.Contract()` -> `myContract.methods.myMethod().call()`
- `new web3.eth.Contract()` -> `myContract.methods.myMethod().send()`

7.3.1 Property

`String` - 20 Bytes: Any ethereum address. You should have the private key for that address in your node or keystore. (Default is undefined)

7.3.2 Example

```
web3.eth.defaultAccount;  
> undefined  
  
// set the default account  
web3.eth.defaultAccount = '0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe';
```

7.4 defaultBlock

```
web3.eth.Contract.defaultBlock  
contract.defaultBlock // on contract instance
```

The default block is used for certain methods. You can override it by passing in the defaultBlock as last parameter. The default value is "latest".

7.4.1 Property

The default block parameters can be one of the following:

- Number|BN|BigNumber: A block number
- "earliest" - String: The genesis block
- "latest" - String: The latest block (current head of the blockchain)
- "pending" - String: The currently mined block (including pending transactions)

Default is "latest".

7.4.2 Example

```
contract.defaultBlock;  
> "latest"  
  
// set the default block  
contract.defaultBlock = 231;
```

7.5 defaultHardfork

```
contract.defaultHardfork
```

The default hardfork property is used for signing transactions locally.

7.5.1 Property

The default hardfork property can be one of the following:

- "chainstart" - String
- "homestead" - String
- "dao" - String
- "tangerineWhistle" - String
- "spuriousDragon" - String
- "byzantium" - String
- "constantinople" - String
- "petersburg" - String
- "istanbul" - String

Default is "petersburg"

7.5.2 Example

```
contract.defaultHardfork;  
> "petersburg"  
  
// set the default block  
contract.defaultHardfork = 'istanbul';
```

7.6 defaultChain

```
contract.defaultChain
```

The default chain property is used for signing transactions locally.

7.6.1 Property

The default chain property can be one of the following:

- "mainnet" - String
- "goerli" - String
- "kovan" - String
- "rinkeby" - String
- "ropsten" - String

Default is "mainnet"

7.6.2 Example

```
contract.defaultChain;
> "mainnet"

// set the default chain
contract.defaultChain = 'goerli';
```

7.7 defaultCommon

```
contract.defaultCommon
```

The default common property is used for signing transactions locally.

7.7.1 Property

The default common property does contain the following `Common` object:

- **customChain - Object:** The custom chain properties
 - name - string: (optional) The name of the chain
 - networkId - number: Network ID of the custom chain
 - chainId - number: Chain ID of the custom chain
- baseChain - string: (optional) mainnet, goerli, kovan, rinkeby, or ropsten
- hardfork - string: (optional) chainstart, homestead, dao, tangerineWhistle, spuriousDragon, byzantium, constantinople, petersburg, or istanbul

Default is undefined.

7.7.2 Example

```
contract.defaultCommon;
> {customChain: {name: 'custom-network', chainId: 1, networkId: 1}, baseChain:
  ↪ 'mainnet', hardfork: 'petersburg'}

// set the default common
contract.defaultCommon = {customChain: {name: 'custom-network', chainId: 1,
  ↪ networkId: 1}, baseChain: 'mainnet', hardfork: 'petersburg'};
```

7.8 transactionBlockTimeout

```
web3.eth.Contract.transactionBlockTimeout
contract.transactionBlockTimeout // on contract instance
```

The `transactionBlockTimeout` is used over socket-based connections. This option defines the amount of new blocks it should wait until the first confirmation happens, otherwise the `PromiEvent` rejects with a timeout error.

7.8.1 Returns

number: The current value of transactionBlockTimeout (default: 50)

7.9 transactionConfirmationBlocks

```
web3.eth.Contract.transactionConfirmationBlocks
contract.transactionConfirmationBlocks // on contract instance
```

This defines the number of blocks it requires until a transaction is considered confirmed.

7.9.1 Returns

number: The current value of transactionConfirmationBlocks (default: 24)

7.10 transactionPollingTimeout

```
web3.eth.Contract.transactionPollingTimeout
contract.transactionPollingTimeout // on contract instance
```

The transactionPollingTimeout is used over HTTP connections. This option defines the number of seconds Web3 will wait for a receipt which confirms that a transaction was mined by the network. Note: If this method times out, the transaction may still be pending.

7.10.1 Returns

number: The current value of transactionPollingTimeout (default: 750)

7.11 handleRevert

```
web3.eth.Contract.handleRevert
contract.handleRevert // on contract instance
```

The handleRevert options property defaults to false and returns the revert reason string if enabled on *send* or *call* of a contract method.

Note: The revert reason string and signature are properties on the returned error.

7.11.1 Returns

`boolean`: The current value of `handleRevert` (default: `false`)

7.12 options

```
myContract.options
```

The `options` object for the contract instance. `from`, `gas` and `gasPrice` are used as fallback values when sending transactions.

7.12.1 Properties

Object - `options`:

- `address` - String: The address where the contract is deployed. See [options.address](#).
- `jsonInterface` - Array: The json interface of the contract. See [options.jsonInterface](#).
- `data` - String: The byte code of the contract. Used when the contract gets *deployed*.
- `from` - String: The address transactions should be made from.
- `gasPrice` - String: The gas price in wei to use for transactions.
- `gas` - Number: The maximum gas provided for a transaction (gas limit).
- `handleRevert` - Boolean: It will otherwise use the default value provided from the Eth module. See [handleRevert](#).
- `transactionBlockTimeout` - Number: It will otherwise use the default value provided from the Eth module. See [transactionBlockTimeout](#).
- `transactionConfirmationBlocks` - Number: It will otherwise use the default value provided from the Eth module. See [transactionConfirmationBlocks](#).
- `transactionPollingTimeout` - Number: It will otherwise use the default value provided from the Eth module. See [transactionPollingTimeout](#).
- `chain` - Number: It will otherwise use the default value provided from the Eth module. See [defaultChain](#).
- `hardfork` - Number: It will otherwise use the default value provided from the Eth module. See [defaultHardfork](#).
- `common` - Number: It will otherwise use the default value provided from the Eth module. See [defaultCommon](#).

7.12.2 Example

```
myContract.options;
> {
  address: '0x1234567890123456789012345678901234567891',
  jsonInterface: [...],
  from: '0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe',
  gasPrice: '1000000000000000',
  gas: 1000000
}
```

(continues on next page)

(continued from previous page)

```
}  
  
myContract.options.from = '0x1234567890123456789012345678901234567891'; // default_  
↪from address  
myContract.options.gasPrice = '20000000000000'; // default gas price in wei  
myContract.options.gas = 5000000; // provide as fallback always 5M gas
```

7.13 options.address

```
myContract.options.address
```

The address used for this contract instance. All transactions generated by web3.js from this contract will contain this address as the "to".

The address will be stored in lowercase.

7.13.1 Property

address - String|null: The address for this contract, or null if not yet set.

7.13.2 Example

```
myContract.options.address;  
> '0xde0b295669a9fd93d5f28d9ec85e40f4cb697bae'  
  
// set a new address  
myContract.options.address = '0x1234FFDD...';
```

7.14 options.jsonInterface

```
myContract.options.jsonInterface
```

The *json interface* object derived from the [ABI](#) of this contract.

7.14.1 Property

jsonInterface - Array: The *json interface* for this contract. Re-setting this will regenerate the methods and events of the contract instance.

7.14.2 Example

```
myContract.options.jsonInterface;
> [{
  "type": "function",
  "name": "foo",
  "inputs": [{ "name": "a", "type": "uint256" }],
  "outputs": [{ "name": "b", "type": "address" }]
}, {
  "type": "event",
  "name": "Event",
  "inputs": [{ "name": "a", "type": "uint256", "indexed": true }, { "name": "b", "type":
  ↳ "bytes32", "indexed": false }],
}]

// set a new interface
myContract.options.jsonInterface = [...];
```

7.15 = Methods =

7.16 clone

```
myContract.clone()
```

Clones the current contract instance.

7.16.1 Parameters

none

7.16.2 Returns

Object: The new contract instance.

7.16.3 Example

```
var contract1 = new eth.Contract(abi, address, {gasPrice: '12345678', from:
  ↳ fromAddress});

var contract2 = contract1.clone();
contract2.options.address = address2;

(contract1.options.address !== contract2.options.address);
> true
```

7.17 deploy

```
myContract.deploy(options)
```

Call this function to deploy the contract to the blockchain. After successful deployment the promise will resolve with a new contract instance.

7.17.1 Parameters

1. **options - Object:** The options used for deployment.

- **data - String:** The byte code of the contract.
- **arguments - Array (optional):** The arguments which get passed to the constructor on deployment.

7.17.2 Returns

Object: The transaction object:

- **Array - arguments:** The arguments passed to the method before. They can be changed.
- **Function - *send*:** Will deploy the contract. The promise will resolve with the new contract instance, instead of the receipt!
- **Function - *estimateGas*:** Will estimate the gas used for deploying. Note: You must specify a `from` address otherwise you may experience odd behavior.
- **Function - *encodeABI*:** Encodes the ABI of the deployment, which is contract data + constructor parameters

7.17.3 Example

```
myContract.deploy({
  data: '0x12345...',
  arguments: [123, 'My String']
})
.send({
  from: '0x1234567890123456789012345678901234567891',
  gas: 1500000,
  gasPrice: '30000000000000'
}, function(error, transactionHash){ ... })
.on('error', function(error){ ... })
.on('transactionHash', function(transactionHash){ ... })
.on('receipt', function(receipt){
  console.log(receipt.contractAddress) // contains the new contract address
})
.on('confirmation', function(confirmationNumber, receipt){ ... })
.then(function(newContractInstance){
  console.log(newContractInstance.options.address) // instance with the new
  ↪ contract address
});

// When the data is already set as an option to the contract itself
```

(continues on next page)

(continued from previous page)

```

myContract.options.data = '0x12345...';

myContract.deploy({
  arguments: [123, 'My String']
})
.send({
  from: '0x1234567890123456789012345678901234567891',
  gas: 1500000,
  gasPrice: '30000000000000'
})
.then(function(newContractInstance) {
  console.log(newContractInstance.options.address) // instance with the new
↳ contract address
});

// Simply encoding
myContract.deploy({
  data: '0x12345...',
  arguments: [123, 'My String']
})
.encodeABI();
> '0x12345...0000012345678765432'

// Gas estimation
myContract.deploy({
  data: '0x12345...',
  arguments: [123, 'My String']
})
.estimateGas(function(err, gas) {
  console.log(gas);
});

```

7.18 methods

```
myContract.methods.myMethod([param1[, param2[, ...]])
```

Creates a transaction object for that method, which then can be *called*, *send*, *estimated*, or *ABI encoded*.

The methods of this smart contract are available through:

- The name: `myContract.methods.myMethod(123)`
- The name with parameters: `myContract.methods['myMethod(uint256)'](123)`
- The signature: `myContract.methods['0x58cf5f10'](123)`

This allows calling functions with same name but different parameters from the JavaScript contract object.

7.18.1 Parameters

Parameters of any method depend on the smart contracts methods, defined in the *JSON interface*.

7.18.2 Returns

Object: The transaction object:

- Array - arguments: The arguments passed to the method before. They can be changed.
- Function - *call*: Will call the “constant” method and execute its smart contract method in the EVM without sending a transaction (Can’t alter the smart contract state).
- Function - *send*: Will send a transaction to the smart contract and execute its method (Can alter the smart contract state).
- Function - *estimateGas*: Will estimate the gas used when the method would be executed on chain. Note: You must specify a from address otherwise you may experience odd behavior.
- Function - *encodeABI*: Encodes the ABI for this method. This can be send using a transaction, call the method or passing into another smart contracts method as argument.

7.18.3 Example

```
// calling a method

myContract.methods.myMethod(123).call({from:
  ↪'0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'}, function(error, result){
  ...
});

// or sending and using a promise
myContract.methods.myMethod(123).send({from:
  ↪'0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'})
.then(function(receipt){
  // receipt can also be a new contract instance, when coming from a "contract.
  ↪deploy({...}).send() "
});

// or sending and using the events

myContract.methods.myMethod(123).send({from:
  ↪'0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'})
.on('transactionHash', function(hash) {
  ...
})
.on('receipt', function(receipt) {
  ...
})
.on('confirmation', function(confirmationNumber, receipt) {
  ...
})
.on('error', function(error, receipt) {
  ...
});
```

7.19 methods.myMethod.call

```
myContract.methods.myMethod([param1[, param2[, ...]]]).call(options [, defaultBlock]
↳[, callback])
```

Will call a “constant” method and execute its smart contract method in the EVM without sending any transaction. Note calling cannot alter the smart contract state.

7.19.1 Parameters

1. **options - Object (optional):** The options used for calling.

- **from** - String (optional): The address the call “transaction” should be made from. For calls the **from** property is optional however it is highly recommended to explicitly set it or it may default to *address(0)* depending on your node or provider.
- **gasPrice** - String (optional): The gas price in wei to use for this call “transaction”.
- **gas** - Number (optional): The maximum gas provided for this call “transaction” (gas limit).

2. **defaultBlock** - Number|String|BN|BigNumber (optional): If you pass this parameter it will not use the default block set with `contract.defaultBlock`. Pre-defined block numbers as “earliest”, “latest”, and “pending” can also be used. Useful for requesting data from or replaying transactions in past blocks.

3. **callback** - Function (optional): This callback will be fired with the result of the smart contract method execution as the second argument, or with an error object as the first argument.

7.19.2 Returns

Promise returns Mixed: The return value(s) of the smart contract method. If it returns a single value, it’s returned as is. If it has multiple return values they are returned as an object with properties and indices:

7.19.3 Example

```
// using the callback
myContract.methods.myMethod(123).call({from:
↳'0xde0B2956669a9FD93d5F28D9Ec85E40f4cb697BAe'}, function(error, result){
    ...
});

// using the promise
myContract.methods.myMethod(123).call({from:
↳'0xde0B2956669a9FD93d5F28D9Ec85E40f4cb697BAe'})
.then(function(result){
    ...
});

// MULTI-ARGUMENT RETURN:

// Solidity
contract MyContract {
    function myFunction() returns(uint256 myNumber, string myString) {
        return (23456, "Hello!%");
    }
}
```

(continues on next page)

(continued from previous page)

```
    }  
  }  
  
  // web3.js  
  var MyContract = new web3.eth.Contract(abi, address);  
  MyContract.methods.myFunction().call()  
  .then(console.log);  
  > Result {  
    myNumber: '23456',  
    myString: 'Hello!%',  
    0: '23456', // these are here as fallbacks if the name is not know or given  
    1: 'Hello!%'  
  }  
  
  // SINGLE-ARGUMENT RETURN:  
  
  // Solidity  
  contract MyContract {  
    function myFunction() returns(string myString) {  
      return "Hello!%";  
    }  
  }  
  
  // web3.js  
  var MyContract = new web3.eth.Contract(abi, address);  
  MyContract.methods.myFunction().call()  
  .then(console.log);  
  > "Hello!%"
```

7.20 methods.myMethod.send

```
myContract.methods.myMethod([param1[, param2[, ...]]]).send(options[, callback])
```

Will send a transaction to the smart contract and execute its method. Note this can alter the smart contract state.

7.20.1 Parameters

1. options - Object: The options used for sending.

- from - String: The address the transaction should be sent from.
- gasPrice - String (optional): The gas price in wei to use for this transaction.
- gas - Number (optional): The maximum gas provided for this transaction (gas limit).
- value - “Number|String|BN|BigNumber” (optional): The value transferred for the transaction in wei.

2. callback - Function (optional): This callback will be fired first with the “transactionHash”, or with an error object as the first argument.

7.20.2 Returns

The **callback** will return the 32 bytes transaction hash.

PromiEvent: A *promise combined event emitter*. Resolves when the transaction *receipt* is available, OR if this `send()` is called from a `someContract.deploy()`, then the promise will resolve with the *new contract instance*. Additionally the following events are available:

- `sending` returns `payload: Object`: Fired immediately before transmitting the transaction request.
- `sent` returns `payload: Object`: Fired immediately after the request body has been written to the client, but before the transaction hash is received.
- `"transactionHash"` returns `transactionHash: String`: Fired when the transaction hash is available.
- `"receipt"` returns `receipt: Object`: Fired when the transaction *receipt* is available. Receipts from contracts will have no `logs` property, but instead an `events` property with event names as keys and events as properties. See *getPastEvents return values* for details about the returned event object.
- `"confirmation"` returns `confirmation: Number, receipt: Object, latestBlockHash: String`: Fired for every confirmation up to the 24th confirmation.
- `"error"` returns `error: Error`: Fired if an error occurs during sending. If the transaction was rejected by the network with a receipt, the receipt will be available as a property on the error object.

7.20.3 Example

```
// using the callback
myContract.methods.myMethod(123).send({from:
  ↪'0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'}, function(error, transactionHash){
  ...
});

// using the promise
myContract.methods.myMethod(123).send({from:
  ↪'0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'})
.then(function(receipt){
  // receipt can also be a new contract instance, when coming from a "contract.
  ↪deploy({...}).send() "
});

// using the event emitter
myContract.methods.myMethod(123).send({from:
  ↪'0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'})
.on('transactionHash', function(hash){
  ...
})
.on('confirmation', function(confirmationNumber, receipt){
  ...
})
.on('receipt', function(receipt){
  // receipt example
  console.log(receipt);
  > {
    "transactionHash":
    ↪"0x9fc76417374aa880d4449a1f7f31ec597f00b1f6f3dd2d66f4c9c6c445836d8b",
```

(continues on next page)

(continued from previous page)

```

        "transactionIndex": 0,
        "blockHash":
        ↪ "0xef95f2f1ed3ca60b048b4bf67cde2195961e0bba6f70bcbea9a2c4e133e34b46",
        "blockNumber": 3,
        "contractAddress": "0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe",
        "cumulativeGasUsed": 314159,
        "gasUsed": 30234,
        "events": {
            "MyEvent": {
                returnValues: {
                    myIndexedParam: 20,
                    myOtherIndexedParam: '0x123456789...',
                    myNonIndexParam: 'My String'
                },
                raw: {
                    data:
                    ↪ '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385',
                    topics: [
                    ↪ '0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
                    ↪ '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385']
                },
                event: 'MyEvent',
                signature:
                ↪ '0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
                logIndex: 0,
                transactionIndex: 0,
                transactionHash:
                ↪ '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385',
                blockHash:
                ↪ '0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
                blockNumber: 1234,
                address: '0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'
            },
            "MyOtherEvent": {
                ...
            },
            "MyMultipleEvent": [{...}, {...}] // If there are multiple of the same
            ↪ event, they will be in an array
        }
    }
}
)
)
.on('error', function(error, receipt) { // If the transaction was rejected by the
    ↪ network with a receipt, the second parameter will be the receipt.
        ...
    });
});

```

7.21 methods.myMethod.estimateGas

```

myContract.methods.myMethod([param1[, param2[, ...]]]).estimateGas(options[,
    ↪ callback])

```

Will call to estimate the gas a method execution will take when executed in the EVM. The estimation can differ from the actual gas used when later sending a transaction, as the state of the smart contract can be different at that time.

Note: You must specify a `from` address otherwise you may experience odd behavior.

7.21.1 Parameters

1. **options - Object (optional): The options used for calling.**

- `from - String (optional)`: The address the call “transaction” should be made from.
- `gas - Number (optional)`: The maximum gas provided for this call “transaction” (gas limit). Setting a specific value helps to detect out of gas errors. If all gas is used it will return the same number.
- `value - Number | String | BN | BigNumber (optional)`: The value transferred for the call “transaction” in wei.

2. **callback - Function (optional)**: This callback will be fired with the result of the gas estimation as the second argument, or with an error object as the first argument.

7.21.2 Returns

Promise returns Number: The gas amount estimated.

7.21.3 Example

```
// using the callback
myContract.methods.myMethod(123).estimateGas({gas: 5000000}, function(error, ↵
↵ gasAmount) {
  if(gasAmount == 5000000)
    console.log('Method ran out of gas');
});

// using the promise
myContract.methods.myMethod(123).estimateGas({from:
↵ '0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'})
.then(function(gasAmount) {
  ...
})
.catch(function(error) {
  ...
});
```

7.22 methods.myMethod.encodeABI

```
myContract.methods.myMethod([param1[, param2[, ...]]]).encodeABI()
```

Encodes the ABI for this method. The resulting hex string is 32-bit function signature hash plus the passed parameters in Solidity tightly packed format. This can be used to send a transaction, call a method, or pass it into another smart contract’s method as arguments. Set the `data` field on `web3.eth.sendTransaction` options as the `encodeABI()` result and it is the same as calling the contract method with `contract.myMethod.send()`.

Some use cases for `encodeABI()` include: preparing a smart contract transaction for a multisignature wallet, working with offline wallets and cold storage and creating transaction payload for complex smart contract proxy calls.

7.22.1 Parameters

none

7.22.2 Returns

String: The encoded ABI byte code to send via a transaction or call.

7.22.3 Example

```
myContract.methods.myMethod(123).encodeABI();  
> '0x58cf5f100000000000000000000000000000000000000000000000000000007B'
```

7.23 = Events =

7.24 once

```
myContract.once(event[, options], callback)
```

Subscribes to an event and unsubscribes immediately after the first event or error. Will only fire for a single event.

7.24.1 Parameters

1. **event** - String: The name of the event in the contract, or "allEvents" to get all events.
2. **options** - Object (optional): The options used for deployment.
 - **filter** - Object (optional): Lets you filter events by indexed parameters, e.g. `{filter: {myNumber: [12, 13]}}` means all events where "myNumber" is 12 or 13.
 - **topics** - Array (optional): This allows you to manually set the topics for the event filter. If given the filter property and event signature, `topic[0]` will not be set automatically. Each topic can also be a nested array of topics that behaves as "or" operation between the given nested topics.
3. **callback** - Function: This callback will be fired for the first *event* as the second argument, or an error as the first argument. See *[getPastEvents](#)* *[return values](#)* for details about the event structure.

7.24.2 Returns

undefined

7.24.3 Example

```

myContract.once('MyEvent', {
  filter: {myIndexedParam: [20,23], myOtherIndexedParam: '0x123456789...'}, //
  ↳ Using an array means OR: e.g. 20 or 23
  fromBlock: 0
}, function(error, event){ console.log(event); });

// event output example
> {
  returnValues: {
    myIndexedParam: 20,
    myOtherIndexedParam: '0x123456789...',
    myNonIndexParam: 'My String'
  },
  raw: {
    data: '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385',
    topics: ['0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7
  ↳ ', '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385']
  },
  event: 'MyEvent',
  signature: '0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
  logIndex: 0,
  transactionIndex: 0,
  transactionHash:
  ↳ '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385',
  blockHash: '0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
  blockNumber: 1234,
  address: '0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'
}

```

7.25 events

```
myContract.events.MyEvent([options][, callback])
```

Subscribe to an event.

7.25.1 Parameters

1. options - Object (optional): The options used for deployment.

- **filter** - Object (optional): Let you filter events by indexed parameters, e.g. {filter: {myNumber: [12,13]}} means all events where “myNumber” is 12 or 13.
- **fromBlock** - Number|String|BN|BigNumber (optional): The block number (greater than or equal to) from which to get events on. Pre-defined block numbers as "earliest", "latest" and "pending" can also be used. For specific range use `getPastEvents`.
- **topics** - Array (optional): This allows to manually set the topics for the event filter. If given the filter property and event signature, (topic[0]) will not be set automatically. Each topic can also be a nested array of topics that behaves as “or” operation between the given nested topics.

2. **callback** - Function (optional): This callback will be fired for each *event* as the second argument, or an error as the first argument.

7.25.2 Returns

EventEmitter: The event emitter has the following events:

- "data" returns Object: Fires on each incoming event with the event object as argument.
- "changed" returns Object: Fires on each event which was removed from the blockchain. The event will have the additional property "removed: true".
- "error" returns Object: Fires when an error in the subscription occurs.
- "connected" returns String: Fires once after the subscription successfully connected. Returns the subscription id.

The structure of the returned event Object looks as follows:

- event - String: The event name.
- signature - String|Null: The event signature, null if it's an anonymous event.
- address - String: Address this event originated from.
- returnValues - Object: The return values coming from the event, e.g. {myVar: 1, myVar2: '0x234...'}.
- logIndex - Number: Integer of the event index position in the block.
- transactionIndex - Number: Integer of the transaction's index position the event was created in.
- transactionHash 32 Bytes - String: Hash of the transaction this event was created in.
- blockHash 32 Bytes - String: Hash of the block this event was created in. null when it's still pending.
- blockNumber - Number: The block number this log was created in. null when still pending.
- raw.data - String: The data containing non-indexed log parameter.
- raw.topics - Array: An array with max 4 32 Byte topics, topic 1-3 contains indexed parameters of the event.

7.25.3 Example

```
myContract.events.MyEvent({
  filter: {myIndexedParam: [20,23], myOtherIndexedParam: '0x123456789...'}, // ↳Using an array means OR: e.g. 20 or 23
  fromBlock: 0
}, function(error, event){ console.log(event); })
.on("connected", function(subscriptionId){
  console.log(subscriptionId);
})
.on('data', function(event){
  console.log(event); // same results as the optional callback above
})
.on('changed', function(event){
  // remove event from local database
})
.on('error', function(error, receipt) { // If the transaction was rejected by the network
  ↳network with a receipt, the second parameter will be the receipt.
  ...
});

// event output example
```

(continues on next page)

(continued from previous page)

```

> {
  returnValues: {
    myIndexedParam: 20,
    myOtherIndexedParam: '0x123456789...',
    myNonIndexParam: 'My String'
  },
  raw: {
    data: '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385',
    topics: ['0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7c2c2eb7b11a91385',
    ↪ '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385'],
    event: 'MyEvent',
    signature: '0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
    logIndex: 0,
    transactionIndex: 0,
    transactionHash:
    ↪ '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385',
    blockHash: '0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
    blockNumber: 1234,
    address: '0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'
  }
}

```

7.26 events.allEvents

```
myContract.events.allEvents([options][, callback])
```

Same as [events](#) but receives all events from this smart contract. Optionally the filter property can filter those events.

7.27 getPastEvents

```
myContract.getPastEvents(event[, options][, callback])
```

Gets past events for this contract.

7.27.1 Parameters

1. `event` - String: The name of the event in the contract, or "allEvents" to get all events.
2. **options** - Object (optional): The options used for deployment.
 - `filter` - Object (optional): Lets you filter events by indexed parameters, e.g. `{filter: {myNumber: [12, 13]}}` means all events where "myNumber" is 12 or 13.
 - `fromBlock` - Number|String|BN|BigNumber (optional): The block number (greater than or equal to) from which to get events on. Pre-defined block numbers as "earliest", "latest" and "pending" can also be used.

- `toBlock` - `Number|String|BN|BigNumber` (optional): The block number (less than or equal to) to get events up to (Defaults to "latest"). Pre-defined block numbers as "earliest", "latest" and "pending" can also be used.
 - `topics` - `Array` (optional): This allows manually setting the topics for the event filter. If given the filter property and event signature, (`topic[0]`) will not be set automatically. Each topic can also be a nested array of topics that behaves as "or" operation between the given nested topics.
3. `callback` - `Function` (optional): This callback will be fired with an array of event logs as the second argument, or an error as the first argument.

7.27.2 Returns

Promise returns Array: An array with the past event Objects, matching the given event name and filter.

For the structure of a returned event Object see [getPastEvents return values](#).

7.27.3 Example

```
myContract.getPastEvents('MyEvent', {
  filter: {myIndexedParam: [20,23], myOtherIndexedParam: '0x123456789...'}, // 
  ↪ Using an array means OR: e.g. 20 or 23
  fromBlock: 0,
  toBlock: 'latest'
}, function(error, events){ console.log(events); })
.then(function(events) {
  console.log(events) // same results as the optional callback above
});

> [{
  returnValues: {
    myIndexedParam: 20,
    myOtherIndexedParam: '0x123456789...',
    myNonIndexParam: 'My String'
  },
  raw: {
    data: '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385',
    topics: ['0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7
  ↪ ', '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385']
  },
  event: 'MyEvent',
  signature: '0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
  logIndex: 0,
  transactionIndex: 0,
  transactionHash:
  ↪ '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385',
  blockHash: '0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
  blockNumber: 1234,
  address: '0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'
}, {
  ...
}]
```

CHAPTER 8

web3.eth.accounts

The `web3.eth.accounts` contains functions to generate Ethereum accounts and sign transactions and data.

Note: This package has NOT been audited and might potentially be unsafe. Take precautions to clear memory properly, store the private keys safely, and test transaction receiving and sending functionality properly before using in production!

To use this package standalone use:

```
var Accounts = require('web3-eth-accounts');

// Passing in the eth or web3 package is necessary to allow retrieving chainId, ↵
↪ gasPrice and nonce automatically
// for accounts.signTransaction().
var accounts = new Accounts('ws://localhost:8546');
```

8.1 create

```
web3.eth.accounts.create([entropy]);
```

Generates an account object with private key and public key.

8.1.1 Parameters

1. `entropy - String` (optional): A random string to increase entropy. If given it should be at least 32 characters. If none is given a random string will be generated using `randomhex`.

8.1.2 Returns

Object - The account object with the following structure:

- address - string: The account address.
- privateKey - string: The accounts private key. This should never be shared or stored unencrypted in localStorage! Also make sure to null the memory after usage.
- signTransaction(tx [, callback]) - Function: The function to sign transactions. See *web3.eth.accounts.signTransaction()* for more.
- sign(data) - Function: The function to sign transactions. See *web3.eth.accounts.sign()* for more.

8.1.3 Example

```
web3.eth.accounts.create();
> {
  address: "0xb8CE9ab6943e0eCED004cDe8e3bBed6568B2Fa01",
  privateKey: "0x348ce564d427a3311b6536bbcff9390d69395b06ed6c486954e971d960fe8709",
  signTransaction: function(tx){...},
  sign: function(data){...},
  encrypt: function(password){...}
}

web3.eth.accounts.create('24350#@#@±±±±!!!!
↪678543213456764321$34567543213456785432134567');
> {
  address: "0xF2CD2AA0c7926743B1D4310b2BC984a0a453c3d4",
  privateKey: "0xd7325de5c2c1cf0009fac77d3d04a9c004b038883446b065871bc3e831dcd098",
  signTransaction: function(tx){...},
  sign: function(data){...},
  encrypt: function(password){...}
}

web3.eth.accounts.create(web3.utils.randomHex(32));
> {
  address: "0xe78150FaCD36E8EB00291e251424a0515AA1FF05",
  privateKey: "0xcc505ee6067fba3f6fc2050643379e190e087aeffe5d958ab9f2f3ed3800fa4e",
  signTransaction: function(tx){...},
  sign: function(data){...},
  encrypt: function(password){...}
}
```

8.2 privateKeyToAccount

```
web3.eth.accounts.privateKeyToAccount(privateKey [, ignoreLength ]);
```

Creates an account object from a private key.

For more advanced hierarchial address derivation, see [truffle-hd-wallet-provider](<https://github.com/trufflesuite/truffle/tree/develop/packages/hdwallet-provider>) package.

8.2.1 Parameters

1. `privateKey` - String: The private key to import. This is 32 bytes of random data. If you are supplying a hexadecimal number, it must have `0x` prefix in order to be in line with other Ethereum libraries. 2. `ignoreLength` - Boolean: If set to true does the `privateKey` length not get validated.

8.2.2 Returns

Object - The account object with the *structure seen here*.

8.2.3 Example

```
web3.eth.accounts.privateKeyToAccount (
  ↪ '0x348ce564d427a3311b6536bbcff9390d69395b06ed6c486954e971d960fe8709');
> {
  address: '0xb8CE9ab6943e0eCED004cDe8e3bBed6568B2Fa01',
  privateKey: '0x348ce564d427a3311b6536bbcff9390d69395b06ed6c486954e971d960fe8709',
  signTransaction: function(tx) {...},
  sign: function(data) {...},
  encrypt: function(password) {...}
}
```

8.3 signTransaction

```
web3.eth.accounts.signTransaction(tx, privateKey [, callback]);
```

Signs an Ethereum transaction with a given private key.

8.3.1 Parameters

1. **tx** - Object: The transaction object as follows:

- `nonce` - String: (optional) The nonce to use when signing this transaction. Default will use *web3.eth.getTransactionCount()*.
- `chainId` - String: (optional) The chain id to use when signing this transaction. Default will use *web3.eth.net.getId()*.
- `to` - String: (optional) The receiver of the transaction, can be empty when deploying a contract.
- `data` - String: (optional) The call data of the transaction, can be empty for simple value transfers.
- `value` - String: (optional) The value of the transaction in wei.
- `gasPrice` - String: (optional) The gas price set by this transaction, if empty, it will use *web3.eth.getGasPrice()*
- `gas` - String: The gas provided by the transaction.
- `chain` - String: (optional) Defaults to mainnet.
- `hardfork` - String: (optional) Defaults to petersburg.

- **common - Object: (optional) The common object**
 - **customChain - Object: The custom chain properties**
 - * name - string: (optional) The name of the chain
 - * networkId - number: Network ID of the custom chain
 - * chainId - number: Chain ID of the custom chain
 - baseChain - string: (optional) mainnet, goerli, kovan, rinkeby, or ropsten
 - hardfork - string: (optional) chainstart, homestead, dao, tangerineWhistle, spuriousDragon, byzantium, constantinople, petersburg, or istanbul

2. privateKey - String: The private key to sign with.

3. callback - Function: (optional) Optional callback, returns an error object as first parameter and the result as second.

8.3.2 Returns

Promise returning Object: The signed data RLP encoded transaction, or if `returnSignature` is `true` the signature value

- messageHash - String: The hash of the given message.
- r - String: First 32 bytes of the signature
- s - String: Next 32 bytes of the signature
- v - String: Recovery value + 27
- rawTransaction - String: The RLP encoded transaction, ready to be send using [web3.eth.sendSignedTransaction](#).
- transactionHash - String: The transaction hash for the RLP encoded transaction.

8.3.3 Example

```
web3.eth.accounts.signTransaction({
  to: '0xF0109fC8DF283027b6285cc889F5aA624EaC1F55',
  value: '1000000000',
  gas: 2000000
}, '0x4c0883a69102937d6231471b5dbb6204fe5129617082792ae468d01a3f362318')
.then(console.log);
> {
  messageHash: '0x31c2f03766b36f0346a850e78d4f7db2d9f4d7d54d5f272a750ba44271e370b1',
  v: '0x25',
  r: '0xc9cf86333bcb065d140032ecaab5d9281bde80f21b9687b3e94161de42d51895',
  s: '0x727a108a0b8d101465414033c3f705a9c7b826e596766046ee1183dbc8aeaa68',
  rawTransaction:
    → '0xf869808504e3b29200831e848094f0109fc8df283027b6285cc889f5aa624eac1f55843b9aca008025a0c9cf86333bcb065d140032ecaab5d9281bde80f21b9687b3e94161de42d51895',
    → '
  transactionHash:
    → '0xde8db924885b0803d2edc335f745b2b8750c8848744905684c20b987443a9593'
}
```

(continues on next page)

(continued from previous page)

```

web3.eth.accounts.signTransaction({
  to: '0xF0109fC8DF283027b6285cc889F5aA624EaC1F55',
  value: '1000000000',
  gas: 2000000,
  gasPrice: '234567897654321',
  nonce: 0,
  chainId: 1
}, '0x4c0883a69102937d6231471b5dbb6204fe5129617082792ae468d01a3f362318')
.then(console.log);
> {
  messageHash: '0x6893a6ee8df79b0f5d64a180cd1ef35d030f3e296a5361cf04d02ce720d32ec5',
  r: '0x9ebb6ca057a0535d6186462bc0b465b561c94a295bdb0621fc19208ab149a9c',
  s: '0x440ffd775ce91a833ab410777204d5341a6f9fa91216a6f3ee2c051fea6a0428',
  v: '0x25',
  rawTransaction:
    ↪ '0xf86a8086d55698372431831e848094f0109fc8df283027b6285cc889f5aa624eac1f55843b9aca008025a009ebb6ca03
    ↪ '
    transactionHash:
    ↪ '0xd8f64a42b57be0d565f385378db2f6bf324ce14a594afc05de90436e9ce01f60'
}

// or with a common
web3.eth.accounts.signTransaction({
  to: '0xF0109fC8DF283027b6285cc889F5aA624EaC1F55',
  value: '1000000000',
  gas: 2000000
  common: {
    baseChain: 'mainnet',
    hardfork: 'petersburg',
    customChain: {
      name: 'custom-chain',
      chainId: 1,
      networkId: 1
    }
  }
}, '0x4c0883a69102937d6231471b5dbb6204fe5129617082792ae468d01a3f362318')
.then(console.log);

```

8.4 recoverTransaction

```
web3.eth.accounts.recoverTransaction(rawTransaction);
```

Recovers the Ethereum address which was used to sign the given RLP encoded transaction.

8.4.1 Parameters

1. signature - String: The RLP encoded transaction.

8.4.2 Returns

String: The Ethereum address used to sign this transaction.

8.4.3 Example

```
web3.eth.accounts.recoverTransaction(  
  ↪ '0xf86180808401ef364594f0109fc8df283027b6285cc889f5aa624eac1f5580801ca031573280d608f75137e33fc1465  
  ↪ ');  
> "0xF0109fC8DF283027b6285cc889F5aA624EaC1F55"
```

8.5 hashMessage

```
web3.eth.accounts.hashMessage(message);
```

Hashes the given message to be passed *web3.eth.accounts.recover()* function. The data will be UTF-8 HEX decoded and enveloped as follows: "\x19Ethereum Signed Message:\n" + message.length + message and hashed using keccak256.

8.5.1 Parameters

1. message - String: A message to hash, if its HEX it will be UTF8 decoded before.

8.5.2 Returns

String: The hashed message

8.5.3 Example

```
web3.eth.accounts.hashMessage("Hello World")  
> "0xa1de988600a42c4b4ab089b619297c17d53cffae5d5120d82d8a92d0bb3b78f2"  
  
// the below results in the same hash  
web3.eth.accounts.hashMessage(web3.utils.utf8ToHex("Hello World"))  
> "0xa1de988600a42c4b4ab089b619297c17d53cffae5d5120d82d8a92d0bb3b78f2"
```

8.6 sign

```
web3.eth.accounts.sign(data, privateKey);
```

Signs arbitrary data.

8.6.1 Parameters

1. `data` - String: The data to sign.
2. `privateKey` - String: The private key to sign with.

Note: The value passed as the `data` parameter will be UTF-8 HEX decoded and wrapped as follows: `"\x19Ethereum Signed Message:\n" + message.length + message`.

8.6.2 Returns

Object: The signature object

- `message` - String: The the given message.
- `messageHash` - String: The hash of the given message.
- `r` - String: First 32 bytes of the signature
- `s` - String: Next 32 bytes of the signature
- `v` - String: Recovery value + 27

8.6.3 Example

```
web3.eth.accounts.sign('Some data',
  → '0x4c0883a69102937d6231471b5dbb6204fe5129617082792ae468d01a3f362318');
> {
  message: 'Some data',
  messageHash: '0x1da44b586eb0729ff70a73c326926f6ed5a25f5b056e7f47fbc6e58d86871655',
  v: '0x1c',
  r: '0xb91467e570a6466aa9e9876cbcd013baba02900b8979d43fe208a4a4f339f5fd',
  s: '0x6007e74cd82e037b800186422fc2da167c747ef045e5d18a5f5d4300f8e1a029',
  signature:
  → '0xb91467e570a6466aa9e9876cbcd013baba02900b8979d43fe208a4a4f339f5fd6007e74cd82e037b800186422fc2da1
  → '
}
```

8.7 recover

```
web3.eth.accounts.recover(signatureObject);
web3.eth.accounts.recover(message, signature [, preFixed]);
web3.eth.accounts.recover(message, v, r, s [, preFixed]);
```

Recovers the Ethereum address which was used to sign the given data.

8.7.1 Parameters

1. `message|signatureObject` - String|Object: Either signed message or hash, or the signature object as following

- `messageHash` - String: The hash of the given message already prefixed with `"\x19Ethereum Signed Message:\n" + message.length + message`.
 - `r` - String: First 32 bytes of the signature
 - `s` - String: Next 32 bytes of the signature
 - `v` - String: Recovery value + 27
2. `signature` - String: The raw RLP encoded signature, OR parameter 2-4 as `v`, `r`, `s` values.
 3. `preFixed` - Boolean (optional, default: `false`): If the last parameter is `true`, the given message will NOT automatically be prefixed with `"\x19Ethereum Signed Message:\n" + message.length + message`, and assumed to be already prefixed.

8.7.2 Returns

String: The Ethereum address used to sign this data.

8.7.3 Example

```
web3.eth.accounts.recover({
  messageHash: '0x1da44b586eb0729ff70a73c326926f6ed5a25f5b056e7f47fbc6e58d86871655',
  v: '0x1c',
  r: '0xb91467e570a6466aa9e9876cbcd013baba02900b8979d43fe208a4a4f339f5fd',
  s: '0x6007e74cd82e037b800186422fc2da167c747ef045e5d18a5f5d4300f8e1a029'
})
> "0x2c7536E3605D9C16a7a3D7b1898e529396a65c23"

// message, signature
web3.eth.accounts.recover('Some data',
  ↪ '0xb91467e570a6466aa9e9876cbcd013baba02900b8979d43fe208a4a4f339f5fd6007e74cd82e037b800186422fc2da167c747ef045e5d18a5f5d4300f8e1a029',
  ↪ ');
> "0x2c7536E3605D9C16a7a3D7b1898e529396a65c23"

// message, v, r, s
web3.eth.accounts.recover('Some data', '0x1c',
  ↪ '0xb91467e570a6466aa9e9876cbcd013baba02900b8979d43fe208a4a4f339f5fd',
  ↪ '0x6007e74cd82e037b800186422fc2da167c747ef045e5d18a5f5d4300f8e1a029');
> "0x2c7536E3605D9C16a7a3D7b1898e529396a65c23"
```

8.8 encrypt

```
web3.eth.accounts.encrypt(privateKey, password);
```

Encrypts a private key to the web3 keystore v3 standard.

8.8.1 Parameters

1. `privateKey` - String: The private key to encrypt.
2. `password` - String: The password used for encryption.

8.8.2 Returns

Object: The encrypted keystore v3 JSON.

8.8.3 Example

```
web3.eth.accounts.encrypt (
  ↪ '0x4c0883a69102937d6231471b5dbb6204fe5129617082792ae468d01a3f362318', 'test!')
> {
  version: 3,
  id: '04e9bcbb-96fa-497b-94d1-14df4cd20af6',
  address: '2c7536e3605d9c16a7a3d7b1898e529396a65c23',
  crypto: {
    ciphertext: 'a1c25da3ecde4e6a24f3697251dd15d6208520efc84ad97397e906e6df24d251
  ↪',
    cipherparams: { iv: '2885df2b63f7ef247d753c82fa20038a' },
    cipher: 'aes-128-ctr',
    kdf: 'scrypt',
    kdfparams: {
      dklen: 32,
      salt: '4531b3c174cc3ff32a6a7a85d6761b410db674807b2d216d022318ceee50be10',
      n: 262144,
      r: 8,
      p: 1
    },
    mac: 'b8b010fff37f9ae5559a352a185e86f9b9c1d7f7a9f1bd4e82a5dd35468fc7f6'
  }
}
```

8.9 decrypt

```
web3.eth.accounts.decrypt(keystoreJsonV3, password);
```

Decrypts a keystore v3 JSON, and creates the account.

8.9.1 Parameters

1. encryptedPrivateKey - String: The encrypted private key to decrypt.
2. password - String: The password used for encryption.

8.9.2 Returns

Object: The decrypted account.

8.9.3 Example

```
web3.eth.accounts.decrypt({
  version: 3,
  id: '04e9bcbb-96fa-497b-94d1-14df4cd20af6',
  address: '2c7536e3605d9c16a7a3d7b1898e529396a65c23',
  crypto: {
    ciphertext: 'a1c25da3ecde4e6a24f3697251dd15d6208520efc84ad97397e906e6df24d251
→',
    cipherparams: { iv: '2885df2b63f7ef247d753c82fa20038a' },
    cipher: 'aes-128-ctr',
    kdf: 'scrypt',
    kdfparams: {
      dklen: 32,
      salt: '4531b3c174cc3ff32a6a7a85d6761b410db674807b2d216d022318ceee50be10',
      n: 262144,
      r: 8,
      p: 1
    },
    mac: 'b8b010fff37f9ae5559a352a185e86f9b9c1d7f7a9f1bd4e82a5dd35468fc7f6'
  }
}, 'test!');
> {
  address: "0x2c7536E3605D9C16a7a3D7b1898e529396a65c23",
  privateKey: "0x4c0883a69102937d6231471b5dbb6204fe5129617082792ae468d01a3f362318",
  signTransaction: function(tx){...},
  sign: function(data){...},
  encrypt: function(password){...}
}
```

8.10 wallet

```
web3.eth.accounts.wallet;
```

Contains an in memory wallet with multiple accounts. These accounts can be used when using `web3.eth.sendTransaction()`.

8.10.1 Example

```
web3.eth.accounts.wallet;
> Wallet {
  0: {...}, // account by index
  "0xF0109fC8DF283027b6285cc889F5aA624EaC1F55": {...}, // same account by address
  "0xf0109fc8df283027b6285cc889f5aa624eac1f55": {...}, // same account by address_
→lowercase
  1: {...},
  "0xD0122fC8DF283027b6285cc889F5aA624EaC1d23": {...},
  "0xd0122fc8df283027b6285cc889f5aa624eac1d23": {...},

  add: function() {},
  remove: function() {},
  save: function() {},
  load: function() {},
  clear: function() {},
}
```

(continues on next page)

(continued from previous page)

```
length: 2,
}
```

8.11 wallet.create

```
web3.eth.accounts.wallet.create(numberOfAccounts [, entropy]);
```

Generates one or more accounts in the wallet. If wallets already exist they will not be overridden.

8.11.1 Parameters

1. `numberOfAccounts` - Number: Number of accounts to create. Leave empty to create an empty wallet.
2. `entropy` - String (optional): A string with random characters as additional entropy when generating accounts. If given it should be at least 32 characters.

8.11.2 Returns

Object: The wallet object.

8.11.3 Example

```
web3.eth.accounts.wallet.create(2, '54674321$3456764321$345674321$3453647544±±±±$±±±±!
↪!!43534534534534');
> Wallet {
  0: {...},
  "0xF0109fC8DF283027b6285cc889F5aA624EaC1F55": {...},
  "0xf0109fc8df283027b6285cc889f5aa624eac1f55": {...},
  ...
}
```

8.12 wallet.add

```
web3.eth.accounts.wallet.add(account);
```

Adds an account using a private key or account object to the wallet.

8.12.1 Parameters

1. `account` - String|Object: A private key or account object created with [web3.eth.accounts.create\(\)](#).

8.12.2 Returns

Object: The added account.

8.12.3 Example

```
web3.eth.accounts.wallet.add(
  ↪ '0x4c0883a69102937d6231471b5dbb6204fe5129617082792ae468d01a3f362318');
> {
  index: 0,
  address: '0x2c7536E3605D9C16a7a3D7b1898e529396a65c23',
  privateKey: '0x4c0883a69102937d6231471b5dbb6204fe5129617082792ae468d01a3f362318',
  signTransaction: function(tx){...},
  sign: function(data){...},
  encrypt: function(password){...}
}

web3.eth.accounts.wallet.add({
  privateKey: '0x348ce564d427a3311b6536bbcff9390d69395b06ed6c486954e971d960fe8709',
  address: '0xb8CE9ab6943e0eCED004cDe8e3bBed6568B2Fa01'
});
> {
  index: 0,
  address: '0xb8CE9ab6943e0eCED004cDe8e3bBed6568B2Fa01',
  privateKey: '0x348ce564d427a3311b6536bbcff9390d69395b06ed6c486954e971d960fe8709',
  signTransaction: function(tx){...},
  sign: function(data){...},
  encrypt: function(password){...}
}
```

8.13 wallet.remove

```
web3.eth.accounts.wallet.remove(account);
```

Removes an account from the wallet.

8.13.1 Parameters

1. account - String|Number: The account address, or index in the wallet.

8.13.2 Returns

Boolean: true if the wallet was removed. false if it couldn't be found.

8.13.3 Example

```
web3.eth.accounts.wallet;  
> Wallet {  
  0: {...},  
  "0xF0109fC8DF283027b6285cc889F5aA624EaC1F55": {...}  
  1: {...},  
  "0xb8CE9ab6943e0eCED004cDe8e3bBed6568B2Fa01": {...}  
  ...  
}  
  
web3.eth.accounts.wallet.remove('0xF0109fC8DF283027b6285cc889F5aA624EaC1F55');  
> true  
  
web3.eth.accounts.wallet.remove(3);  
> false
```

8.14 wallet.clear

```
web3.eth.accounts.wallet.clear();
```

Securely empties the wallet and removes all its accounts.

8.14.1 Parameters

none

8.14.2 Returns

Object: The wallet object.

8.14.3 Example

```
web3.eth.accounts.wallet.clear();  
> Wallet {  
  add: function() {},  
  remove: function() {},  
  save: function() {},  
  load: function() {},  
  clear: function() {},  
  
  length: 0  
}
```

8.15 wallet.encrypt

```
web3.eth.accounts.wallet.encrypt(password);
```

Encrypts all wallet accounts to an array of encrypted keystore v3 objects.

8.15.1 Parameters

1. password - String: The password which will be used for encryption.

8.15.2 Returns

Array: The encrypted keystore v3.

8.15.3 Example

```
web3.eth.accounts.wallet.encrypt('test');
> [ { version: 3,
  id: 'dcf8ab05-a314-4e37-b972-bf9b86f91372',
  address: '06f702337909c06c82b09b7a22f0a2f0855d1f68',
  crypto:
    { ciphertext: '0de804dc63940820f6b3334e5a4bfc8214e27fb30bb7e9b7b74b25cd7eb5c604',
      cipherparams: [Object],
      cipher: 'aes-128-ctr',
      kdf: 'scrypt',
      kdfparams: [Object],
      mac: 'b2aac1485bd6ee1928665642bf8eae9ddfb039c3a673658933d320bac6952e3' } },
  { version: 3,
    id: '9e1c7d24-b919-4428-b10e-0f3ef79f7cf0',
    address: 'b5d89661b59a9af0b34f58d19138baa2de48baaf',
    crypto:
      { ciphertext: 'd705ebed2a136d9e4db7e5ae70ed1f69d6a57370d5fbe06281eb07615f404410',
        cipherparams: [Object],
        cipher: 'aes-128-ctr',
        kdf: 'scrypt',
        kdfparams: [Object],
        mac: 'af9eca5eb01b0f70e909f824f0e7cdb90c350a802f04a9f6afe056602b92272b' } }
]
```

8.16 wallet.decrypt

```
web3.eth.accounts.wallet.decrypt(keystoreArray, password);
```

Decrypts keystore v3 objects.

8.16.1 Parameters

1. keystoreArray - Array: The encrypted keystore v3 objects to decrypt.
2. password - String: The password which will be used for encryption.

8.16.2 Returns

Object: The wallet object.

8.16.3 Example

```
web3.eth.accounts.wallet.decrypt([
  { version: 3,
    id: '83191a81-aaca-451f-b63d-0c5f3b849289',
    address: '06f702337909c06c82b09b7a22f0a2f0855d1f68',
    crypto:
      { ciphertext: '7d34deae112841fba86e3e6cf08f5398dda323a8e4d29332621534e2c4069e8d',
        cipherparams: { iv: '497f4d26997a84d570778eae874b2333' },
        cipher: 'aes-128-ctr',
        kdf: 'scrypt',
        kdfparams:
          { dklen: 32,
            salt: '208dd732a27aa4803bb760228dff18515d5313fd085bbce60594a3919ae2d88d',
            n: 262144,
            r: 8,
            p: 1 },
          mac: '0062a853de302513c57bfe3108ab493733034bf3cb313326f42cf26ea2619cf9' } },
    { version: 3,
      id: '7d6b91fa-3611-407b-b16b-396efb28f97e',
      address: 'b5d89661b59a9af0b34f58d19138baa2de48baaf',
      crypto:
        { ciphertext: 'cb9712d1982ff89f571fa5dbef447f14b7e5f142232bd2a913aac833730eeb43',
          cipherparams: { iv: '8cccb91cb84e435437f7282ec2ffd2db' },
          cipher: 'aes-128-ctr',
          kdf: 'scrypt',
          kdfparams:
            { dklen: 32,
              salt: '08ba6736363c5586434cd5b895e6fe41ea7db4785bd9b901dedce77a1514e8b8',
              n: 262144,
              r: 8,
              p: 1 },
            mac: 'd2eb068b37e2df55f56fa97a2bf4f55e072bef0dd703bfd917717d9dc54510f0' } }
  ], 'test');
> Wallet {
  0: {...},
  1: {...},
  "0xF0109fC8DF283027b6285cc889F5aA624EaC1F55": {...},
  "0xD0122fC8DF283027b6285cc889F5aA624EaC1d23": {...}
  ...
}
```

8.17 wallet.save

```
web3.eth.accounts.wallet.save(password [, keyName]);
```

Stores the wallet encrypted and as string in local storage.

Note: Browser only.

8.17.1 Parameters

1. password - String: The password to encrypt the wallet.
2. keyName - String: (optional) The key used for the local storage position, defaults to "web3js_wallet".

8.17.2 Returns

Boolean

8.17.3 Example

```
web3.eth.accounts.wallet.save('test#!$');  
> true
```

8.18 wallet.load

```
web3.eth.accounts.wallet.load(password [, keyName]);
```

Loads a wallet from local storage and decrypts it.

Note: Browser only.

8.18.1 Parameters

1. password - String: The password to decrypt the wallet.
2. keyName - String: (optional) The key used for the localstorage position, defaults to "web3js_wallet".

8.18.2 Returns

Object: The wallet object.

8.18.3 Example

```
web3.eth.accounts.wallet.load('test#!$', 'myWalletKey');
> Wallet {
  0: {...},
  1: {...},
  "0xF0109fC8DF283027b6285cc889F5aA624EaC1F55": {...},
  "0xD0122fC8DF283027b6285cc889F5aA624EaC1d23": {...}
  ...
}
```


CHAPTER 9

web3.eth.personal

The `web3-eth-personal` package allows you to interact with the Ethereum node's accounts.

Note: Many of these functions send sensitive information like passwords. Never call these functions over a unsecured Websocket or HTTP provider, as your password will be sent in plain text!

```
var Personal = require('web3-eth-personal');

// "Personal.providers.givenProvider" will be set if in an Ethereum supported browser.
var personal = new Personal(Personal.givenProvider || 'ws://some.local-or-remote.
↪node:8546');

// or using the web3 umbrella package

var Web3 = require('web3');
var web3 = new Web3(Web3.givenProvider || 'ws://some.local-or-remote.node:8546');

// -> web3.eth.personal
```

9.1 setProvider

```
web3.setProvider(myProvider)
web3.eth.setProvider(myProvider)
web3.shh.setProvider(myProvider)
web3.bzz.setProvider(myProvider)
...
```

Will change the provider for its module.

Note: When called on the umbrella package web3 it will also set the provider for all sub modules web3.eth, web3.shh, etc. EXCEPT web3.bzz which needs a separate provider at all times.

9.1.1 Parameters

1. Object - myProvider: a valid provider.

9.1.2 Returns

Boolean

9.1.3 Example: Local Geth Node

```
var Web3 = require('web3');
var web3 = new Web3('http://localhost:8545');
// or
var web3 = new Web3(new Web3.providers.HttpProvider('http://localhost:8545'));

// change provider
web3.setProvider('ws://localhost:8546');
// or
web3.setProvider(new Web3.providers.WebsocketProvider('ws://localhost:8546'));

// Using the IPC provider in node.js
var net = require('net');
var web3 = new Web3('/Users/myuser/Library/Ethereum/geth.ipc', net); // mac os path
// or
var web3 = new Web3(new Web3.providers.IpcProvider('/Users/myuser/Library/Ethereum/
↳geth.ipc', net)); // mac os path
// on windows the path is: "\\.\pipe\geth.ipc"
// on linux the path is: "/users/myuser/.ethereum/geth.ipc"
```

9.1.4 Example: Remote Node Provider

```
// Using a remote node provider, like Alchemy (https://www.alchemyapi.io/supernode),
↳is simple.
var Web3 = require('web3');
var web3 = new Web3("https://eth-mainnet.alchemyapi.io/v2/your-api-key");
```

9.2 providers

```
web3.providers
web3.eth.providers
web3.shh.providers
web3.bzz.providers
...
```

Contains the current available providers.

9.2.1 Value

Object with the following providers:

- Object - `HttpProvider`: The HTTP provider is **deprecated**, as it won't work for subscriptions.
- Object - `WebsocketProvider`: The Websocket provider is the standard for usage in legacy browsers.
- Object - `IpcProvider`: The IPC provider is used node.js dapps when running a local node. Gives the most secure connection.

9.2.2 Example

```
var Web3 = require('web3');
// use the given Provider, e.g in Mist, or instantiate a new websocket provider
var web3 = new Web3(Web3.givenProvider || 'ws://remotenode.com:8546');
// or
var web3 = new Web3(Web3.givenProvider || new Web3.providers.WebsocketProvider('ws://
↪remotenode.com:8546'));

// Using the IPC provider in node.js
var net = require('net');

var web3 = new Web3('/Users/myuser/Library/Ethereum/geth.ipc', net); // mac os path
// or
var web3 = new Web3(new Web3.providers.IpcProvider('/Users/myuser/Library/Ethereum/
↪geth.ipc', net)); // mac os path
// on windows the path is: "\\.\pipe\geth.ipc"
// on linux the path is: "/users/myuser/.ethereum/geth.ipc"
```

9.2.3 Configuration

```
// ====
// Http
// ====

var Web3HttpProvider = require('web3-providers-http');

var options = {
  keepAlive: true,
  withCredentials: false,
  timeout: 20000, // ms
  headers: [
    {
      name: 'Access-Control-Allow-Origin',
      value: '*'
    },
    {
      ...
    }
  ],
  agent: {
```

(continues on next page)

(continued from previous page)

```
        http: http.Agent(...),
        baseUrl: ''
    }
};

var provider = new Web3HttpProvider('http://localhost:8545', options);

// =====
// Websockets
// =====

var Web3WsProvider = require('web3-providers-ws');

var options = {
    timeout: 30000, // ms

    // Useful for credentialed urls, e.g: ws://username:password@localhost:8546
    headers: {
        authorization: 'Basic username:password'
    },

    clientConfig: {
        // Useful if requests are large
        maxReceivedFrameSize: 100000000, // bytes - default: 1MiB
        maxReceivedMessageSize: 100000000, // bytes - default: 8MiB

        // Useful to keep a connection alive
        keepalive: true,
        keepaliveInterval: 60000 // ms
    },

    // Enable auto reconnection
    reconnect: {
        auto: true,
        delay: 5000, // ms
        maxAttempts: 5,
        onTimeout: false
    }
};

var ws = new Web3WsProvider('ws://localhost:8546', options);
```

More information for the Http and Websocket provider modules can be found here:

- [HttpProvider](#)
- [WebsocketProvider](#)

9.3 givenProvider

```
web3.givenProvider
web3.eth.givenProvider
web3.shh.givenProvider
```

(continues on next page)

(continued from previous page)

```
web3.bzz.givenProvider  
...
```

When using web3.js in an Ethereum compatible browser, it will set with the current native provider by that browser. Will return the given provider by the (browser) environment, otherwise `null`.

9.3.1 Returns

Object: The given provider set or `null`;

9.3.2 Example

9.4 currentProvider

```
web3.currentProvider  
web3.eth.currentProvider  
web3.shh.currentProvider  
web3.bzz.currentProvider  
...
```

Will return the current provider, otherwise `null`.

9.4.1 Returns

Object: The current provider set or `null`.

9.4.2 Example

9.5 BatchRequest

```
new web3.BatchRequest()  
new web3.eth.BatchRequest()  
new web3.shh.BatchRequest()  
new web3.bzz.BatchRequest()
```

Class to create and execute batch requests.

9.5.1 Parameters

none

9.5.2 Returns

Object: With the following methods:

- `add(request)`: To add a request object to the batch call.
- `execute()`: Will execute the batch request.

9.5.3 Example

```
var contract = new web3.eth.Contract(abi, address);

var batch = new web3.BatchRequest();
batch.add(web3.eth.getBalance.request('0x0000000000000000000000000000000000000000',
  ↳ 'latest', callback));
batch.add(contract.methods.balance(address).call.request({from:
  ↳ '0x0000000000000000000000000000000000000000'}, callback2));
batch.execute();
```

9.6 extend

```
web3.extend(methods)
web3.eth.extend(methods)
web3.shh.extend(methods)
web3.bzz.extend(methods)
...
```

Allows extending the web3 modules.

Note: You also have `*.extend.formatters` as additional formatter functions to be used for input and output formatting. Please see the [source file](#) for function details.

9.6.1 Parameters

1. **methods - Object:** Extension object with array of methods description objects as follows:

- **property - String:** (optional) The name of the property to add to the module. If no property is set it will be added to the module directly.
- **methods - Array:** The array of method descriptions:
 - **name - String:** Name of the method to add.
 - **call - String:** The RPC method name.
 - **params - Number:** (optional) The number of parameters for that function. Default 0.
 - **inputFormatter - Array:** (optional) Array of inputformatter functions. Each array item responds to a function parameter, so if you want some parameters not to be formatted, add a null instead.
 - **outputFormatter - ``Function:** (optional) Can be used to format the output of the method.

9.6.2 Returns

Object: The extended module.

9.6.3 Example

```
web3.extend({
  property: 'myModule',
  methods: [{
    name: 'getBalance',
    call: 'eth_getBalance',
    params: 2,
    inputFormatter: [web3.extend.formatters.inputAddressFormatter, web3.extend.
    ↪formatters.inputDefaultBlockNumberFormatter],
    outputFormatter: web3.utils.hexToNumberString
  }, {
    name: 'getGasPriceSuperFunction',
    call: 'eth_gasPriceSuper',
    params: 2,
    inputFormatter: [null, web3.utils.numberToHex]
  }]
});

web3.extend({
  methods: [{
    name: 'directCall',
    call: 'eth_callForFun',
  }]
});

console.log(web3);
> Web3 {
  myModule: {
    getBalance: function() {},
    getGasPriceSuperFunction: function() {}
  },
  directCall: function() {},
  eth: Eth {...},
  bzz: Bzz {...},
  ...
}
```

9.7 newAccount

```
web3.eth.personal.newAccount(password, [callback])
```

Creates a new account.

Note: Never call this function over a unsecured Websocket or HTTP provider, as your password will be sent in plain text!

9.7.1 Parameters

1. `password - String`: The password to encrypt this account with.

9.7.2 Returns

Promise returns `String`: The address of the newly created account.

9.7.3 Example

```
web3.eth.personal.newAccount('!@superpassword')
  .then(console.log);
> '0x1234567891011121314151617181920212223456'
```

9.8 sign

```
web3.eth.personal.sign(dataToSign, address, password [, callback])
```

The sign method calculates an Ethereum specific signature with:

```
sign(keccak256("\x19Ethereum Signed Message:\n" + dataToSign.length + dataToSign)))
```

Adding a prefix to the message makes the calculated signature recognisable as an Ethereum specific signature.

If you have the original message and the signed message, you can discover the signing account address using `web3.eth.personal.ecRecover`. See example below.

Note: Sending your account password over an unsecured HTTP RPC connection is highly insecure.

9.8.1 Parameters

1. `String` - Data to sign. If `String` it will be converted using *`web3.utils.utf8ToHex`*.
2. `String` - Address to sign data with.
3. `String` - The password of the account to sign data with.
4. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

9.8.2 Returns

Promise returns `String` - The signature.

9.8.3 Example

```

web3.eth.personal.sign("Hello world", "0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe",
↳ "test password!")
.then(console.log);
>
↳ "0x30755ed65396facf86c53e6217c52b4daebe72aa4941d89635409de4c9c7f9466d4e9aaec7977f05e923889b33c0d0d
↳ "

// the below is the same
web3.eth.personal.sign(web3.utils.utf8ToHex("Hello world"),
↳ "0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe", "test password!")
.then(console.log);
>
↳ "0x30755ed65396facf86c53e6217c52b4daebe72aa4941d89635409de4c9c7f9466d4e9aaec7977f05e923889b33c0d0d
↳ "

// recover the signing account address using original message and signed message
web3.eth.personal.ecRecover("Hello world", "0x30755ed65396...etc...")
.then(console.log);
> "0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe"

```

9.9 ecRecover

```
web3.eth.personal.ecRecover(dataThatWasSigned, signature [, callback])
```

Recovers the account that signed the data.

9.9.1 Parameters

1. String - Data that was signed. If String it will be converted using *web3.utils.utf8ToHex*.
2. String - The signature.
3. Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

9.9.2 Returns

Promise returns String - The account.

9.9.3 Example

```

web3.eth.personal.ecRecover("Hello world",
↳ "0x30755ed65396facf86c53e6217c52b4daebe72aa4941d89635409de4c9c7f9466d4e9aaec7977f05e923889b33c0d0d
↳ ")
.then(console.log);
> "0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe"

```


9.11 sendTransaction

```
web3.eth.personal.sendTransaction(transactionOptions, password [, callback])
```

This method sends a transaction over the management API.

Note: Sending your account password over an unsecured HTTP RPC connection is highly unsecure.

9.11.1 Parameters

1. **Object** - The transaction options
2. **String** - The passphrase for the current account
3. **Function** - (optional) Optional callback, returns an error object as first parameter and the result as second.

9.11.2 Returns

Promise<string> - The transaction hash.

9.11.3 Example

[illegible]

9.12 unlockAccount

```
web3.eth.personal.unlockAccount(address, password, unlockDuration [, callback])
```

Signs data using a specific account.

Note: Sending your account password over an unsecured HTTP RPC connection is highly insecure.

9.12.1 Parameters

1. `address - String`: The account address.
2. `password - String` - The password of the account.

3. `unlockDuration` - Number - The duration for the account to remain unlocked.

9.12.2 Example

```
web3.eth.personal.unlockAccount("0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe", "test_
↪password!", 600)
.then(console.log('Account unlocked!'));
> "Account unlocked!"
```

9.13 lockAccount

```
web3.eth.personal.lockAccount(address [, callback])
```

Locks the given account.

Note: Sending your account password over an unsecured HTTP RPC connection is highly unsecure.

9.13.1 Parameters

1. `address` - String: The account address.
4. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

9.13.2 Returns

Promise<boolean>

9.13.3 Example

```
web3.eth.personal.lockAccount("0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe")
.then(console.log('Account locked!'));
> "Account locked!"
```

9.14 getAccounts

```
web3.eth.personal.getAccounts([callback])
```

Returns a list of accounts the node controls by using the provider and calling the RPC method `personal_listAccounts`. Using `web3.eth.accounts.create()` will not add accounts into this list. For that use `web3.eth.personal.newAccount()`.

The results are the same as `web3.eth.getAccounts()` except that calls the RPC method `eth_accounts`.

9.14.1 Returns

Promise<Array> - An array of addresses controlled by node.

9.14.2 Example

```
web3.eth.personal.getAccounts()  
.then(console.log);  
> ["0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe",  
  ↪ "0xDCc6960376d6C6dEa93647383FfB245CfCed97Cf"]
```

9.15 importRawKey

```
web3.eth.personal.importRawKey(privateKey, password)
```

Imports the given private key into the key store, encrypting it with the passphrase.

Returns the address of the new account.

Note: Sending your account password over an unsecured HTTP RPC connection is highly unsecure.

9.15.1 Parameters

1. `privateKey` - String - An unencrypted private key (hex string).
2. `password` - String - The password of the account.

9.15.2 Returns

Promise<string> - The address of the account.

9.15.3 Example

```
web3.eth.personal.importRawKey(  
  ↪ "cd3376bb711cb332ee3fb2ca04c6a8b9f70c316fcd7a1f44ef4c7999483295e", "password1234")  
.then(console.log);  
> "0x8f337bf484b2fc75e4b0436645dcc226ee2ac531"
```


CHAPTER 10

web3.eth.ens

The `web3.eth.ens` functions let you interact with ENS. We recommend reading the [ENS documentation](#) to get deeper insights about the internals of the name service.

10.1 registryAddress

```
web3.eth.ens.registryAddress;
```

The `registryAddress` property can be used to define a custom registry address when you are connected to an unknown chain.

Note: If no address is defined will it try to detect the registry on the chain you are currently connected with and on the call of `setProvider` in the `Eth` module will it keep the defined address and use it for the ENS module.

10.1.1 Returns

`String` - The address of the custom registry.

10.1.2 Example

```
web3.eth.ens.registryAddress;  
> "0x314159265dD8dbb310642f98f50C066173C1259b"
```

10.2 registry

```
web3.eth.ens.registry;
```

Returns the network specific ENS registry.

10.2.1 Returns

Registry - The current ENS registry.

- `contract`: `Contract` - The Registry contract with the interface we know from the [Contract](#) object.
- `owner(name, callback)`: `Promise` - **Deprecated** please use `getOwner`
- `getOwner(name, callback)`: `Promise`
- `setOwner(name, address, txConfig, callback)`: `PromiEvent`
- `resolver(name, callback)`: `Promise` - **Deprecated** please use `getResolver`
- `getResolver(name, callback)`: `Promise`
- `setResolver(name, address, txConfig, callback)`: `PromiEvent`
- `getTTL(name, callback)`: `Promise`
- `setTTL(name, ttl, txConfig, callback)`: `PromiEvent`
- `setSubnodeOwner(name, label, address, txConfig, callback)`: `PromiEvent`
- `setRecord(name, owner, resolver, ttl, txConfig, callback)`: `PromiEvent`
- `setSubnodeRecord(name, label, owner, resolver, ttl, txConfig, callback)`: `PromiEvent`
- `setApprovalForAll(operator, approved, txConfig, callback)`: `PromiEvent`
- `isApprovedForAll(owner, operator, callback)`: `Promise`
- `recordExists(name, callback)`: `Promise`

10.2.2 Example

```
web3.eth.ens.registry;  
> {  
  contract: Contract,  
  owner: Function(name, callback), // Deprecated  
  getOwner: Function(name, callback),  
  setOwner: Function(name, address, txConfig, callback),  
  resolver: Function(name, callback), // Deprecated  
  getResolver: Function(name, callback),  
  setResolver: Function(name, address, txConfig, callback),  
  getTTL: Function(name, callback),  
  setTTL: Function(name, ttl, txConfig, callback),  
  setSubnodeOwner: Function(name, label, address, txConfig, callback),  
  setRecord(name, owner, resolver, ttl, txConfig, callback),  
  setSubnodeRecord(name, label, owner, resolver, ttl, txConfig, callback),  
  setApprovalForAll(operator, approved, txConfig, callback),  
  isApprovedForAll(owner, operator, txConfig, callback),  
}
```

(continues on next page)

(continued from previous page)

```
recordExists(name, callback)
}
```

10.3 resolver

```
web3.eth.ens.resolver(name [, callback]);
```

Returns the resolver contract to an Ethereum address.

Note: This method is deprecated please use `getResolver`

10.3.1 Parameters

1. `name` - String: The ENS name.
2. `callback` - Function: (optional) Optional callback

10.3.2 Returns

Promise<Resolver> - The ENS resolver for this name.

10.3.3 Example

```
web3.eth.ens.resolver('ethereum.eth').then(function (contract) {
  console.log(contract);
});
> Contract<Resolver>
```

10.4 getResolver

```
web3.eth.ens.getResolver(name [, callback]);
```

Returns the resolver contract to an Ethereum address.

10.4.1 Parameters

1. `name` - String: The ENS name.
2. `callback` - Function: (optional) Optional callback

10.4.2 Returns

Promise<Resolver> - The ENS resolver for this name.

10.4.3 Example

```
web3.eth.ens.getResolver('ethereum.eth').then(function (contract) {
  console.log(contract);
});
> Contract<Resolver>
```

10.5 setResolver

```
web3.eth.ens.setResolver(name, address [, txConfig ] [, callback]);
```

Sets the resolver contract address of a name.

10.5.1 Parameters

1. name - String: The ENS name.
2. address - String: The contract address of the deployed Resolver contract.
3. txConfig - Object: (optional) The transaction options as described [here](#)
4. callback - Function: (optional) Optional callback

10.5.2 Returns

PromiEvent<TransactionReceipt | TransactionRevertInstructionError>

10.5.3 Example

```
web3.eth.ens.setResolver('ethereum.eth', '0x...', {...}).then(function (receipt) {
  console.log(receipt);
});
> {...}
```

10.6 getOwner

```
web3.eth.ens.getOwner(name [, callback]);
```

Returns the owner of a name.

10.6.1 Parameters

1. name - String: The ENS name.
2. callback - Function: (optional) Optional callback

10.6.2 Returns

Promise<String> - The address of the registrar (EOA or CA).

10.6.3 Example

```
web3.eth.ens.getOwner('ethereum.eth').then(function (owner) {  
  console.log(owner);  
});  
> '0x...'
```

10.7 setOwner

```
web3.eth.ens.setOwner(name [, txConfig ] [, callback]);
```

Sets the owner of the given name.

10.7.1 Parameters

1. name - String: The ENS name.
2. txConfig - Object: (optional) The transaction options as described [here](#)
3. callback - Function: (optional) Optional callback

10.7.2 Returns

PromiEvent<TransactionReceipt | TransactionRevertInstructionError>

10.7.3 Example

```
web3.eth.ens.setOwner('ethereum.eth', {...}).then(function (receipt) {  
  console.log(receipt);  
});  
> {...}
```

10.8 getTTL

```
web3.eth.ens.getTTL(name [, callback]);
```

Returns the caching TTL (time-to-live) of a name.

10.8.1 Parameters

1. `name` - String: The ENS name.
2. `callback` - Function: (optional) Optional callback

10.8.2 Returns

Promise<Number>

10.8.3 Example

```
web3.eth.ens.getTTL('ethereum.eth').then(function (ttl) {  
  console.log(ttl);  
});  
> 100000
```

10.9 setTTL

```
web3.eth.ens.setTTL(name, ttl [, txConfig ] [, callback]);
```

Sets the caching TTL (time-to-live) of a name.

10.9.1 Parameters

1. `name` - String: The ENS name.
2. `ttl` - Number: The TTL value (uint64)
3. `txConfig` - Object: (optional) The transaction options as described [here](#)
4. `callback` - Function: (optional) Optional callback

10.9.2 Returns

PromiEvent<TransactionReceipt | TransactionRevertInstructionError>

10.9.3 Example

```
web3.eth.ens.setTTL('ethereum.eth', 10000, {...}).then(function (receipt) {
  console.log(receipt);
});
> {...}
```

10.10 setSubnodeOwner

```
web3.eth.ens.setSubnodeOwner(name, label, address [, txConfig ] [, callback]);
```

Creates a new subdomain of the given node, assigning ownership of it to the specified owner.

10.10.1 Parameters

1. name - String: The ENS name.
2. label - String: The name of the sub-domain or the sha3 hash of it.
3. address - String: The registrar of this sub-domain.
4. txConfig - Object: (optional) The transaction options as described [here](#).
5. callback - Function: (optional) Optional callback.

10.10.2 Returns

PromiEvent<TransactionReceipt | TransactionRevertInstructionError>

10.10.3 Example

```
web3.eth.ens.setSubnodeOwner('ethereum.eth', 'web3', '0x...', {...}).then(function_
↪(receipt) {
  console.log(receipt); // successfully defined the owner of web3.ethereum.eth
});
> {...}
```

10.11 setRecord

```
web3.eth.ens.setRecord(name, owner, resolver, ttl, [, txConfig ] [, callback]);
```

Sets the owner, resolver, and TTL for an ENS record in a single operation.

10.11.1 Parameters

1. name - String: The ENS name.
2. owner - String: The owner of the name record.
3. resolver - String: The resolver address of the name record.
4. ttl - String | Number: Time to live value (uint64).
5. txConfig - Object: (optional) The transaction options as described [here](#).
6. callback - Function: (optional) Optional callback.

10.11.2 Returns

PromiEvent<TransactionReceipt | TransactionRevertInstructionError>

10.11.3 Example

```
web3.eth.ens.setRecord('ethereum.eth', '0x...', '0x...', 1000000, {...}).  
  ↪then(function (receipt) {  
    console.log(receipt); // successfully registered ethereum.eth  
  });  
> {...}
```

10.12 setSubnodeRecord

```
web3.eth.ens.setSubnodeRecord(name, label, owner, resolver, ttl, [, txConfig ] [,   
  ↪callback]);
```

Sets the owner, resolver and TTL for a subdomain, creating it if necessary.

10.12.1 Parameters

1. name - String: The ENS name.
2. label - String: The name of the sub-domain or the sha3 hash of it.
3. owner - String: The owner of the name record.
4. resolver - String: The resolver address of the name record.
5. ttl - String | Number: Time to live value (uint64).
6. txConfig - Object: (optional) The transaction options as described [here](#).
7. callback - Function: (optional) Optional callback.

10.12.2 Returns

PromiEvent<TransactionReceipt | TransactionRevertInstructionError>

10.12.3 Example

```
web3.eth.ens.setSubnodeRecord('ethereum.eth', 'web3', '0x...', '0x...', 1000000, {...})
  →).then(function (receipt) {
    console.log(receipt); // successfully registered web3.ethereum.eth
  });
> {...}
```

10.13 setApprovalForAll

```
web3.eth.ens.setApprovalForAll(operator, approved, [, txConfig ] [, callback]);
```

Sets or clears an approval. Approved accounts can execute all ENS registry operations on behalf of the caller.

10.13.1 Parameters

1. operator - String: The operator address
2. approved - Boolean
3. txConfig - Object: (optional) The transaction options as described [here](#)
4. callback - Function: (optional) Optional callback

10.13.2 Returns

PromiEvent<TransactionReceipt | TransactionRevertInstructionError>

10.13.3 Example

```
web3.eth.ens.setApprovalForAll('0x...', true, {...}).then(function (receipt) {
  console.log(receipt);
});
> {...}
```

10.14 isApprovedForAll

```
web3.eth.ens.isApprovedForAll(owner, operator [, callback]);
```

Returns `true` if the operator is approved to make ENS registry operations on behalf of the owner.

10.14.1 Parameters

1. `owner - String`: The owner address.
2. `operator - String`: The operator address.
3. `callback - Function`: (optional) Optional callback

10.14.2 Returns

Promise<Boolean>

10.14.3 Example

```
web3.eth.ens.isApprovedForAll('0x0...', '0x0...').then(function (isApproved) {  
  console.log(isApproved);  
})  
> true
```

10.15 recordExists

```
web3.eth.ens.recordExists(name [, callback]);
```

Returns `true` if node exists in this ENS registry. This will return `false` for records that are in the legacy ENS registry but have not yet been migrated to the new one.

10.15.1 Parameters

1. `name - String`: The ENS name.
2. `callback - Function`: (optional) Optional callback

10.15.2 Returns

Promise<Boolean>

10.15.3 Example

```
web3.eth.ens.recordExists('0x0...', '0x0...').then(function (isExisting) {  
  console.log(isExisting);  
})  
> true
```

10.16 getAddress

```
web3.eth.ens.getAddress(ENSName [, callback]);
```

Resolves an ENS name to an Ethereum address.

10.16.1 Parameters

1. ENSName - String: The ENS name to resolve.
2. callback - Function: (optional) Optional callback

10.16.2 Returns

String - The Ethereum address of the given name.

10.16.3 Example

```
web3.eth.ens.getAddress('ethereum.eth').then(function (address) {  
  console.log(address);  
})  
> 0xfB6916095ca1df60bB79Ce92cE3Ea74c37c5d359
```

10.17 setAddress

```
web3.eth.ens.setAddress(ENSName, address [, txConfig ] [, callback]);
```

Sets the address of an ENS name in this resolver.

10.17.1 Parameters

1. ENSName - String: The ENS name.
2. address - String: The address to set.
3. txConfig - Object: (optional) The transaction options as described [here](#)
4. callback - Function: (optional) Optional callback

Emits an AddrChanged event.

10.17.2 Returns

PromiEvent<TransactionReceipt | TransactionRevertInstructionError>

10.17.3 Example

```
web3.eth.ens.setAddress(
  'ethereum.eth',
  '0xfB6916095ca1df60bB79Ce92cE3Ea74c37c5d359',
  {
    from: '0x9CC9a2c777605Af16872E0997b3Aeb91d96D5D8c'
  }
).then(function (result) {
  console.log(result.events);
});
> AddrChanged(...)

// Or using the event emitter

web3.eth.ens.setAddress(
  'ethereum.eth',
  '0xfB6916095ca1df60bB79Ce92cE3Ea74c37c5d359',
  {
    from: '0x9CC9a2c777605Af16872E0997b3Aeb91d96D5D8c'
  }
)
.on('transactionHash', function (hash) {
  ...
})
.on('confirmation', function (confirmationNumber, receipt) {
  ...
})
.on('receipt', function (receipt) {
  ...
})
.on('error', console.error);

// Or listen to the AddrChanged event on the resolver

web3.eth.ens.resolver('ethereum.eth').then(function (resolver) {
  resolver.events.AddrChanged({fromBlock: 0}, function (error, event) {
    console.log(event);
  })
  .on('data', function (event) {
    console.log(event);
  })
  .on('changed', function (event) {
    // remove event from local database
  })
  .on('error', console.error);
});
```

For further information on the handling of contract events please see [here](#).

10.18 getPubkey

```
web3.eth.ens.getPubkey(ENSName [, callback]);
```

Returns the X and Y coordinates of the curve point for the public key.

10.18.1 Parameters

1. ENSName - String: The ENS name.
2. callback - Function: (optional) Optional callback

10.18.2 Returns

Promise<Object<String, String>> - The X and Y coordinates.

10.18.3 Example

```
web3.eth.ens.getPubkey('ethereum.eth').then(function (result) {
  console.log(result)
});
> {
  "0": "0x0000000000000000000000000000000000000000000000000000000000000000",
  "1": "0x0000000000000000000000000000000000000000000000000000000000000000",
  "x": "0x0000000000000000000000000000000000000000000000000000000000000000",
  "y": "0x0000000000000000000000000000000000000000000000000000000000000000"
}
```

10.19 setPubkey

```
web3.eth.ens.setPubkey(ENSName, x, y [, txConfig ] [, callback]);
```

Sets the SECP256k1 public key associated with an ENS node.

10.19.1 Parameters

1. ENSName - String: The ENS name.
2. x - String: The X coordinate of the public key.
3. y - String: The Y coordinate of the public key.
4. txConfig - Object: (optional) The transaction options as described [here](#)
5. callback - Function: (optional) Optional callback

Emits an PubkeyChanged event.

10.19.2 Returns

PromiEvent<TransactionReceipt | TransactionRevertInstructionError>

10.19.3 Example

```
web3.eth.ens.setPubkey(
  'ethereum.eth',
  '0x0000000000000000000000000000000000000000000000000000000000000000',
  '0x0000000000000000000000000000000000000000000000000000000000000000',
  {
    from: '0x9CC9a2c777605Af16872E0997b3Aeb91d96D5D8c'
  }
).then(function (result) {
  console.log(result.events);
});
> PubkeyChanged(...)

// Or using the event emitter

web3.eth.ens.setPubkey(
  'ethereum.eth',
  '0x0000000000000000000000000000000000000000000000000000000000000000',
  '0x0000000000000000000000000000000000000000000000000000000000000000',
  {
    from: '0x9CC9a2c777605Af16872E0997b3Aeb91d96D5D8c'
  }
)
.on('transactionHash', function (hash) {
  ...
})
.on('confirmation', function (confirmationNumber, receipt) {
  ...
})
.on('receipt', function (receipt) {
  ...
})
.on('error', console.error);

// Or listen to the PubkeyChanged event on the resolver

web3.eth.ens.resolver('ethereum.eth').then(function (resolver) {
  resolver.events.PubkeyChanged({fromBlock: 0}, function (error, event) {
    console.log(event);
  })
  .on('data', function (event) {
    console.log(event);
  })
  .on('changed', function (event) {
    // remove event from local database
  })
  .on('error', console.error);
});
```

For further information on the handling of contract events please see [here](#).

10.20 getContent

```
web3.eth.ens.getContent(ENSName [, callback]);
```

Returns the content hash associated with an ENS node.

10.20.1 Parameters

1. ENSName - String: The ENS name.
2. callback - Function: (optional) Optional callback

10.20.2 Returns

Promise<String> - The content hash associated with an ENS node.

10.20.3 Example

```
web3.eth.ens.getContent('ethereum.eth').then(function (result) {
  console.log(result);
});
> "0x0000000000000000000000000000000000000000000000000000000000000000"
```

10.21 setContent

```
web3.eth.ens.setContent(ENSName, hash [, txConfig ] [, callback]);
```

Sets the content hash associated with an ENS node.

10.21.1 Parameters

1. ENSName - String: The ENS name.
2. hash - String: The content hash to set.
3. txConfig - Object: (optional) The transaction options as described [here](#)
4. callback - Function: (optional) Optional callback

Emits an ContentChanged event.

10.21.2 Returns

PromiEvent<TransactionReceipt | TransactionRevertInstructionError>

10.21.3 Example

```
web3.eth.ens.setContent (
  'ethereum.eth',
  '0x0000000000000000000000000000000000000000000000000000000000000000',
  {
    from: '0x9CC9a2c777605Af16872E0997b3Aeb91d96D5D8c'
  }
).then(function (result) {
  console.log(result.events);
});
> ContentChanged(...)

// Or using the event emitter

web3.eth.ens.setContent (
  'ethereum.eth',
  '0x0000000000000000000000000000000000000000000000000000000000000000',
  {
    from: '0x9CC9a2c777605Af16872E0997b3Aeb91d96D5D8c'
  }
)
.on('transactionHash', function(hash) {
  ...
})
.on('confirmation', function(confirmationNumber, receipt){
  ...
})
.on('receipt', function(receipt){
  ...
})
.on('error', console.error);

// Or listen to the ContentChanged event on the resolver

web3.eth.ens.resolver('ethereum.eth').then(function (resolver) {
  resolver.events.ContentChanged({fromBlock: 0}, function(error, event) {
    console.log(event);
  })
  .on('data', function(event){
    console.log(event);
  })
  .on('changed', function(event){
    // remove event from local database
  })
  .on('error', console.error);
});
```

For further information on the handling of contract events please see [here](#).

10.22 getContenthash

```
web3.eth.ens.getContenthash(ENSName [, callback]);
```

Returns the content hash object associated with an ENS node.

10.22.1 Parameters

1. ENSName - String: The ENS name.
2. callback - Function: (optional) Optional callback

10.22.2 Returns

Promise<Object> - The content hash object associated with an ENS node.

10.22.3 Example

```
web3.eth.ens.getContenthash('ethereum.eth').then(function (result) {
  console.log(result);
});
> {
  "protocolType": "ipfs",
  "decoded": "QmaEBknbGT4bTQiQoe2VNgBJbRfygQGktnaW5TbuKixjYL"
}
```

10.23 setContenthash

```
web3.eth.ens.setContenthash(ENSName, hash [, txConfig ] [, callback]);
```

Sets the content hash associated with an ENS node.

10.23.1 Parameters

1. ENSName - String: The ENS name.
2. hash - String: The content hash to set.
3. txConfig - Object: (optional) The transaction options as described [here](#)
4. callback - Function: (optional) Optional callback

Emits a ContenthashChanged event.

Supports the following protocols as valid hash inputs:

1. ipfs:// - ipfs://QmaEBknbGT4bTQiQoe2VNgBJbRfygQGktnaW5TbuKixjYL
2. /ipfs/ - /ipfs/QmaEBknbGT4bTQiQoe2VNgBJbRfygQGktnaW5TbuKixjYL
3. bzz:// - bzz://d1de9994b4d039f6548d191eb26786769f580809256b4685ef316805265ea162
4. onion:// - onion://3g2upl4pq6kufc4m
5. onion3:// - onion3://p53lf57qovyuvwsc6xnrppyply3vtqm7l6pcobkmyqsiofyeznfu5uqd

10.23.2 Returns

PromiEvent<TransactionReceipt | TransactionRevertInstructionError>

10.23.3 Example

```
web3.eth.ens.setContenthash(
  'ethereum.eth',
  'ipfs://QmaEBknbgT4bTQiQoe2VNgBJbRfygQGktnaW5TbuKixjYL',
  {
    from: '0x9CC9a2c777605Af16872E0997b3Aeb91d96D5D8c'
  }
).then(function (result) {
  console.log(result.events);
});
> ContenthashChanged(...)

// Or using the event emitter

web3.eth.ens.setContenthash(
  'ethereum.eth',
  'ipfs://QmaEBknbgT4bTQiQoe2VNgBJbRfygQGktnaW5TbuKixjYL',
  {
    from: '0x9CC9a2c777605Af16872E0997b3Aeb91d96D5D8c'
  }
)
.on('transactionHash', function (hash) {
  ...
})
.on('confirmation', function (confirmationNumber, receipt) {
  ...
})
.on('receipt', function (receipt) {
  ...
})
.on('error', console.error);

// Or listen to the ContenthashChanged event on the resolver

web3.eth.ens.resolver('ethereum.eth').then(function (resolver) {
  resolver.events.ContenthashChanged({fromBlock: 0}, function (error, event) {
    console.log(event);
  })
  .on('data', function (event) {
    console.log(event);
  })
  .on('changed', function (event) {
    // remove event from local database
  })
  .on('error', console.error);
});
```

For further information on the handling of contract events please see [here](#).

10.24 getMultihash

```
web3.eth.ens.getMultihash(ENSName [, callback]);
```

Returns the multihash associated with an ENS node.

10.24.1 Parameters

1. ENSName - String: The ENS name.
2. callback - Function: (optional) Optional callback

10.24.2 Returns

Promise<String> - The associated multihash.

10.24.3 Example

```
web3.eth.ens.getMultihash('ethereum.eth').then(function (result) {
  console.log(result);
});
> 'QmXpSwxdmgWaYrgMUzuDWCnjsZo5RxphE3oW7VhTMSCoKK'
```

10.25 supportsInterface

```
web3.eth.ens.supportsInterface(name, interfaceId [, callback]);
```

Returns `true` if the related Resolver does support the given signature or interfaceId.

10.25.1 Parameters

1. name - String: The ENS name.
2. interfaceId - String: The signature of the function or the interfaceId as described in the ENS documentation
3. callback - Function: (optional) Optional callback

10.25.2 Returns

Promise<Boolean>

10.25.3 Example

```
web3.eth.ens.supportsInterface('ethereum.eth', 'addr(bytes32)').then(function (result)
↪ {
  console.log(result);
});
> true
```

10.26 setMultihash

```
web3.eth.ens.setMultihash(ENSName, hash [, txConfig ] [, callback]);
```

Sets the multihash associated with an ENS node.

10.26.1 Parameters

1. ENSName - String: The ENS name.
2. hash - String: The multihash to set.
3. txConfig - Object: (optional) The transaction options as described [here](#)
4. callback - Function: (optional) Optional callback

Emits an “MultihashChanged” event.

10.26.2 Returns

PromiEvent<TransactionReceipt | TransactionRevertInstructionError>

10.26.3 Example

```
web3.eth.ens.setMultihash(
  'ethereum.eth',
  'QmXpSwxdmgWaYrgMUzuDWCnjsZo5RxphE3oW7VhTMSCoKK',
  {
    from: '0x9CC9a2c777605Af16872E0997b3Aeb91d96D5D8c'
  }
).then(function (result) {
  console.log(result.events);
});
> MultihashChanged(...)

// Or using the event emitter

web3.eth.ens.setMultihash(
  'ethereum.eth',
  'QmXpSwxdmgWaYrgMUzuDWCnjsZo5RxphE3oW7VhTMSCoKK',
  {
    from: '0x9CC9a2c777605Af16872E0997b3Aeb91d96D5D8c'
  }
)
.on('transactionHash', function(hash) {
  ...
})
.on('confirmation', function(confirmationNumber, receipt){
  ...
})
.on('receipt', function(receipt) {
  ...
})
.on('error', console.error);
```

For further information on the handling of contract events please see [here](#).

10.27 ENS events

The ENS API provides the possibility for listening to all ENS related events.

10.27.1 Known resolver events

1. AddrChanged(node bytes32, a address) 1. ContentChanged(node bytes32, hash bytes32) 1. NameChanged(node bytes32, name string) 1. ABIChanged(node bytes32, contentType uint256) 1. PubkeyChanged(node bytes32, x bytes32, y bytes32)

10.27.2 Returns

PromiEvent<TransactionReceipt | TransactionRevertInstructionError>

10.27.3 Example

```
web3.eth.ens.resolver('ethereum.eth').then(function (resolver) {
  resolver.events.AddrChanged({fromBlock: 0}, function(error, event) {
    console.log(event);
  })
  .on('data', function(event) {
    console.log(event);
  })
  .on('changed', function(event) {
    // remove event from local database
  })
  .on('error', console.error);
});
> {
  returnValues: {
    node: '0x123456789...',
    a: '0x123456789...',
  },
  raw: {
    data: '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385',
    topics: [
      '0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
      '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385'
    ]
  },
  event: 'AddrChanged',
  signature: '0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
  logIndex: 0,
  transactionIndex: 0,
  transactionHash:
  → '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385',
  blockHash: '0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
  blockNumber: 1234,
```

(continues on next page)

(continued from previous page)

```
    address: '0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'
  }
```

10.27.4 Known registry events

1. Transfer(node bytes32, owner address) 1. NewOwner(node bytes32, label bytes32, owner address) 1. NewResolver(node bytes32, resolver address) 1. NewTTL(node bytes32, ttl uint64)

10.27.5 Example

```
web3.eth.ens.resistry.then(function (registry) {
  registry.events.Transfer({fromBlock: 0}, , function(error, event) {
    console.log(event);
  })
  .on('data', function(event) {
    console.log(event);
  })
  .on('changed', function(event) {
    // remove event from local database
  })
  .on('error', console.error);
});
> {
  returnValues: {
    node: '0x123456789...',
    owner: '0x123456789...',
  },
  raw: {
    data: '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385',
    topics: [
      '0xfd43adelc09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
      '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385'
    ]
  },
  event: 'Transfer',
  signature: '0xfd43adelc09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
  logIndex: 0,
  transactionIndex: 0,
  transactionHash:
  → '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385',
  blockHash: '0xfd43adelc09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
  blockNumber: 1234,
  address: '0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'
}
```

For further information on the handling of contract events please see [here](#).

CHAPTER 11

web3.eth.Iban

The `web3.eth.Iban` function converts Ethereum addresses from and to IBAN and BBAN.

11.1 Iban instance

This instance of Iban.

```
> Iban { _iban: 'XE73380073KYGTWWZN0F2WZ0R8PX5ZPPZS' }
```

11.2 Iban contructor

```
new web3.eth.Iban(ibanAddress)
```

Generates a iban object with conversion methods and validity checks.

Also has singleton functions for conversion like:

- *Iban.toAddress()*
- *Iban.toIban()*
- *Iban.fromAddress()*
- *Iban.fromBban()*
- *Iban.createIndirect()*
- *Iban.isValid()*

11.2.1 Parameters

1. `String`: the IBAN address to instantiate an `Iban` instance from.

11.2.2 Returns

`Object` - The `Iban` instance.

11.2.3 Example

```
var iban = new web3.eth.Iban("XE73380073KYGTWWZN0F2WZ0R8PX5ZPPZS");
> Iban { _iban: 'XE73380073KYGTWWZN0F2WZ0R8PX5ZPPZS' }
```

11.3 toAddress

Static function.

```
web3.eth.Iban.toAddress(ibanAddress)
```

Singleton: Converts a direct IBAN address into an Ethereum address.

Note: This method also exists on the `IBAN` instance.

11.3.1 Parameters

1. `String`: the IBAN address to convert.

11.3.2 Returns

`String` - The Ethereum address.

11.3.3 Example

```
web3.eth.Iban.toAddress("XE73380073KYGTWWZN0F2WZ0R8PX5ZPPZS");
> "0x00c5496aEe77C1bA1f0854206A26DdA82a81D6D8"
```

11.4 toIban

Static function.

```
web3.eth.Iban.toIban(address)
```

Singleton: Converts an Ethereum address to a direct IBAN address.

11.4.1 Parameters

1. `String`: the Ethereum address to convert.

11.4.2 Returns

`String` - The IBAN address.

11.4.3 Example

```
web3.eth.Iban.toIban("0x00c5496aEe77C1bA1f0854206A26DdA82a81D6D8");  
> "XE73380073KYGTWWZN0F2WZ0R8PX5ZPPZS"
```

11.5 fromAddress

Static function, returns IBAN instance.

```
web3.eth.Iban.fromAddress(address)
```

Singleton: Converts an Ethereum address to a direct IBAN instance.

11.5.1 Parameters

1. `String`: the Ethereum address to convert.

11.5.2 Returns

`Object` - The IBAN instance.

11.5.3 Example

```
web3.eth.Iban.fromAddress("0x00c5496aEe77C1bA1f0854206A26DdA82a81D6D8");  
> Iban {_iban: "XE73380073KYGTWWZN0F2WZ0R8PX5ZPPZS"}
```

static function, return IBAN instance

11.6 fromBban

```
web3.eth.Iban.fromBban(bbanAddress)
```

Singleton: Converts an BBAN address to a direct IBAN instance.

11.6.1 Parameters

1. `String`: the BBAN address to convert.

11.6.2 Returns

`Object` - The IBAN instance.

11.6.3 Example

```
web3.eth.Iban.fromBban('ETHXREGGAVOFYORK');  
> Iban {_iban: "XE73380073KYGTWWZN0F2WZ0R8PX5ZPPZS"}
```

static function, return IBAN instance

11.7 createIndirect

```
web3.eth.Iban.createIndirect(options)
```

Singleton: Creates an indirect IBAN address from an institution and identifier.

11.7.1 Parameters

1. **Object**: the options object as follows:
 - `institution` - `String`: the institution to be assigned.
 - `identifier` - `String`: the identifier to be assigned.

11.7.2 Returns

`Object` - The IBAN instance.

11.7.3 Example

```
web3.eth.Iban.createIndirect({  
  institution: "XREG",  
  identifier: "GAVOFYORK"  
});  
> Iban {_iban: "XE73380073KYGTWWZN0F2WZ0R8PX5ZPPZS"}
```

Static function, returns boolean.

11.8 isValid

```
web3.eth.Iban.isValid(ibanAddress)
```

Singleton: Checks if an IBAN address is valid.

Note: This method also exists on the IBAN instance.

11.8.1 Parameters

1. `String`: the IBAN address to check.

11.8.2 Returns

Boolean

11.8.3 Example

```
web3.eth.Iban.isValid("XE81ETHXREGGAVOFYORK");  
> true  
  
web3.eth.Iban.isValid("XE82ETHXREGGAVOFYORK");  
> false // because the checksum is incorrect
```

11.9 prototype.isValid

Method of Iban instance.

```
web3.eth.Iban.prototype.isValid()
```

Singleton: Checks if an IBAN address is valid.

Note: This method also exists on the IBAN instance.

11.9.1 Parameters

1. `String`: the IBAN address to check.

11.9.2 Returns

Boolean

11.9.3 Example

```
var iban = new web3.eth.Iban("XE81ETHXREGGAVOYORK");
iban.isValid();
> true
```

11.10 prototype.isDirect

Method of Iban instance.

```
web3.eth.Iban.prototype.isDirect()
```

Checks if the IBAN instance is direct.

11.10.1 Parameters

none

11.10.2 Returns

Boolean

11.10.3 Example

```
var iban = new web3.eth.Iban("XE81ETHXREGGAVOYORK");
iban.isDirect();
> false
```

11.11 prototype.isIndirect

Method of Iban instance.

```
web3.eth.Iban.prototype.isIndirect()
```

Checks if the IBAN instance is indirect.

11.11.1 Parameters

none

11.11.2 Returns

Boolean

11.11.3 Example

```
var iban = new web3.eth.Iban("XE81ETHXREGGAVOFYORK");
iban.isIndirect();
> true
```

11.12 prototype.checksum

Method of Iban instance.

```
web3.eth.Iban.prototype.checksum()
```

Returns the checksum of the IBAN instance.

11.12.1 Parameters

none

11.12.2 Returns

String: The checksum of the IBAN

11.12.3 Example

```
var iban = new web3.eth.Iban("XE81ETHXREGGAVOFYORK");
iban.checksum();
> "81"
```

11.13 prototype.institution

Method of Iban instance.

```
web3.eth.Iban.prototype.institution()
```

Returns the institution of the IBAN instance.

11.13.1 Parameters

none

11.13.2 Returns

String: The institution of the IBAN

11.13.3 Example

```
var iban = new web3.eth.Iban("XE81ETHXREGGAVOXYORK");
iban.institution();
> 'XREG'
```

11.14 prototype.client

Method of Iban instance.

```
web3.eth.Iban.prototype.client()
```

Returns the client of the IBAN instance.

11.14.1 Parameters

none

11.14.2 Returns

String: The client of the IBAN

11.14.3 Example

```
var iban = new web3.eth.Iban("XE81ETHXREGGAVOXYORK");
iban.client();
> 'GAVOXYORK'
```

11.15 prototype.toString

Method of Iban instance.

```
web3.eth.Iban.prototype.toString()
```

Returns the Ethereum address of the IBAN instance.

11.15.1 Parameters

none

11.15.2 Returns

String: The Ethereum address of the IBAN

11.15.3 Example

```
var iban = new web3.eth.Iban('XE73380073KYGTWWZN0F2WZ0R8PX5ZPPZS');
iban.toAddress();
> '0x00c5496aEe77C1bA1f0854206A26DdA82a81D6D8'
```

11.16 prototype.toString

Method of Iban instance.

```
web3.eth.Iban.prototype.toString()
```

Returns the IBAN address of the IBAN instance.

11.16.1 Parameters

none

11.16.2 Returns

String: The IBAN address.

11.16.3 Example

```
var iban = new web3.eth.Iban('XE73380073KYGTWWZN0F2WZ0R8PX5ZPPZS');
iban.toString();
> 'XE73380073KYGTWWZN0F2WZ0R8PX5ZPPZS'
```


CHAPTER 12

web3.eth.abi

The `web3.eth.abi` functions let you encode and decode parameters to ABI (Application Binary Interface) for function calls to the EVM (Ethereum Virtual Machine).

12.1 encodeFunctionSignature

```
web3.eth.abi.encodeFunctionSignature(functionName);
```

Encodes the function name to its ABI signature, which are the first 4 bytes of the sha3 hash of the function name including types.

12.1.1 Parameters

1. `functionName` - `String|Object`: The function name to encode. or the *JSON interface* object of the function. If string it has to be in the form `function(type,type,...)`, e.g: `myFunction(uint256,uint32[],bytes10,bytes)`

12.1.2 Returns

`String` - The ABI signature of the function.

12.1.3 Example

```
// From a JSON interface object
web3.eth.abi.encodeFunctionSignature({
  name: 'myMethod',
```

(continues on next page)

(continued from previous page)

```
type: 'function',
inputs: [{
  type: 'uint256',
  name: 'myNumber'
},{
  type: 'string',
  name: 'myString'
}]
})
> 0x24ee0097

// Or string
web3.eth.abi.encodeFunctionSignature('myMethod(uint256,string)')
> '0x24ee0097'
```

12.2 encodeEventSignature

```
web3.eth.abi.encodeEventSignature(eventName);
```

Encodes the event name to its ABI signature, which are the sha3 hash of the event name including input types.

12.2.1 Parameters

1. `eventName` - `String|Object`: The event name to encode. or the *JSON interface* object of the event. If string it has to be in the form `event (type,type,...)`, e.g: `myEvent (uint256,uint32[],bytes10,bytes)`

12.2.2 Returns

`String` - The ABI signature of the event.

12.2.3 Example

```
web3.eth.abi.encodeEventSignature('myEvent(uint256,bytes32)')
> 0xf2eeb729e636a8cb783be044acf6b7b1e2c5863735b60d6daae84c366ee87d97

// or from a json interface object
web3.eth.abi.encodeEventSignature({
  name: 'myEvent',
  type: 'event',
  inputs: [{
    type: 'uint256',
    name: 'myNumber'
  }, {
    type: 'bytes32',
    name: 'myBytes'
  }]
})
> 0xf2eeb729e636a8cb783be044acf6b7b1e2c5863735b60d6daae84c366ee87d97
```

12.3 encodeParameter

```
web3.eth.abi.encodeParameter(type, parameter);
```

Encodes a parameter based on its type to its ABI representation.

12.3.1 Parameters

1. `type` - `String|Object`: The type of the parameter, see the [solidity documentation](#) for a list of types.
2. `parameter` - `Mixed`: The actual parameter to encode.

12.3.2 Returns

String - The ABI encoded parameter.

12.3.3 Example

```
web3.eth.abi.encodeParameter('uint256', '2345675643');
> "0x00000000000000000000000000000000000000000000000000000000000008bd02b7b"

web3.eth.abi.encodeParameter('uint256', '2345675643');
> "0x00000000000000000000000000000000000000000000000000000000000008bd02b7b"

web3.eth.abi.encodeParameter('bytes32', '0xdf3234');
> "0xdf3234000000000000000000000000000000000000000000000000000000000000"

web3.eth.abi.encodeParameter('bytes', '0xdf3234');
>
↳ "0x00000000000000000000000000000000000000000000000000000000000002000000000000000000000000000000000000000000000000000000000000000000"
↳ ""

web3.eth.abi.encodeParameter('bytes32[]', ['0xdf3234', '0xfdfd']);
>
↳ "00000000000000000000000000000000000000000000000000000000000002000000000000000000000000000000000000000000000000000000000000000000"
↳ ""

web3.eth.abi.encodeParameter(
{
  "ParentStruct": {
    "propertyOne": 'uint256',
    "propertyTwo": 'uint256',
    "childStruct": {
      "propertyOne": 'uint256',
      "propertyTwo": 'uint256'
    }
  },
  {
    "propertyOne": 42,
    "propertyTwo": 56,
    "childStruct": {
      "propertyOne": 45,
```

(continues on next page)

(continued from previous page)

[illegible]

12.4 encodeParameters

```
web3.eth.abi.encodeParameters(typesArray, parameters);
```

Encodes a function parameters based on its *JSON interface* object.

12.4.1 Parameters

1. `typesArray` - `Array<String|Object>|Object`: An array with types or a *JSON interface* of a function. See the [solidity documentation](#) for a list of types.
2. `parameters` - `Array`: The parameters to encode.

12.4.2 Returns

String - The ABI encoded parameters.

12.4.3 Example

```
web3.eth.abi.encodeParameters(['uint256','string'], ['2345675643', 'Hello!%']);  
>  
↪ "0x00000000000000000000000000000000000000000000000000000008bd02b7b000000000000000000000000000000000000  
↪ "  
  
web3.eth.abi.encodeParameters(['uint8[]','bytes32'], [['34','434'], '0x324567fff']);  
> "0x0  
  
web3.eth.abi.encodeParameters(  
    [  
        'uint8[]',  
        {  
            "ParentStruct": {  
                "propertyOne": 'uint256',  
                "propertyTwo": 'uint256',  
                "ChildStruct": {  
                    "propertyOne": 'uint256',  
                    "propertyTwo": 'uint256'  
                }  
            }  
        ]
```

(continues on next page)

12.6 decodeParameter

```
web3.eth.abi.decodeParameter(type, hexString);
```

Decodes an ABI encoded parameter to its JavaScript type.

12.6.1 Parameters

1. `type - String|Object`: The type of the parameter, see the [solidity documentation](#) for a list of types.
2. `hexString - String`: The ABI byte code to decode.

12.6.2 Returns

Mixed - The decoded parameter.

12.6.3 Example

[illegible]

(continues on next page)

(continued from previous page)

```
'0': '42',
'1': '56',
'2': {
  '0': '45',
  '1': '78',
  'propertyOne': '45',
  'propertyTwo': '78'
},
'childStruct': {
  '0': '45',
  '1': '78',
  'propertyOne': '45',
  'propertyTwo': '78'
},
'propertyOne': '42',
'propertyTwo': '56'
},
'ParentStruct': {
  '0': '42',
  '1': '56',
  '2': {
    '0': '45',
    '1': '78',
    'propertyOne': '45',
    'propertyTwo': '78'
  },
  'childStruct': {
    '0': '45',
    '1': '78',
    'propertyOne': '45',
    'propertyTwo': '78'
  },
  'propertyOne': '42',
  'propertyTwo': '56'
}
}
```

12.7 decodeParameters

```
web3.eth.abi.decodeParameters(typesArray, hexString);
```

Decodes ABI encoded parameters to its JavaScript types.

12.7.1 Parameters

1. `typesArray` - `Array<String|Object>|Object`: An array with types or a *JSON interface* outputs array. See the [solidity documentation](#) for a list of types.
2. `hexString` - `String`: The ABI byte code to decode.

12.7.2 Returns

Object - The result object containing the decoded parameters.

12.7.3 Example

```
web3.eth.abi.decodeParameters(['string', 'uint256'],  
↪ '0x0000000000000000000000000000000000000000000000000000000000000000400000000000000000000000000000000000000');  
↪ ');  
> Result { '0': 'Hello!%!', '1': '234' }  
  
web3.eth.abi.decodeParameters([  
  type: 'string',  
  name: 'myString'  
, {  
  type: 'uint256',  
  name: 'myNumber'  
}],  
↪ '0x0000000000000000000000000000000000000000000000000000000000000000400000000000000000000000000000000000000');  
↪ ');  
> Result {  
  '0': 'Hello!%!',  
  '1': '234',  
  myString: 'Hello!%!',  
  myNumber: '234'  
}  
  
web3.eth.abi.decodeParameters([  
  'uint8[]',  
  {  
    "ParentStruct": {  
      "propertyOne": 'uint256',  
      "propertyTwo": 'uint256',  
      "childStruct": {  
        "propertyOne": 'uint256',  
        "propertyTwo": 'uint256'  
      }  
    }  
  },  
],  
↪ '0x0000000000000000000000000000000000000000000000000000000000000000a00000000000000000000000000000000000000');  
↪ ');  
> Result {  
  '0': ['42', '24'],  
  '1': {  
    '0': '42',  
    '1': '56',  
    '2': {  
      '0': '45',  
      '1': '78',  
      'propertyOne': '45',  
      'propertyTwo': '78'  
    },  
    'childStruct': {
```

(continues on next page)

(continued from previous page)

```
'0': 'Hello%!',  
'1': '62224',  
'2': '16',  
myString: 'Hello%!',  
myNumber: '62224',  
mySmallNumber: '16'  
}
```

CHAPTER 13

web3.*.net

The web3-net package allows you to interact with an Ethereum node's network properties.

```
var Net = require('web3-net');

// "Personal.providers.givenProvider" will be set if in an Ethereum supported browser.
var net = new Net(Net.givenProvider || 'ws://some.local-or-remote.node:8546');

// or using the web3 umbrella package

var Web3 = require('web3');
var web3 = new Web3(Web3.givenProvider || 'ws://some.local-or-remote.node:8546');

// -> web3.eth.net
// -> web3.bzz.net
// -> web3.shh.net
```

13.1 getid

```
web3.eth.net.getId([callback])
web3.bzz.net.getId([callback])
web3.shh.net.getId([callback])
```

Gets the current network ID.

13.1.1 Parameters

none

13.1.2 Returns

Promise **returns** Number: The network ID.

13.1.3 Example

```
web3.eth.net.getId()  
.then(console.log);  
> 1
```

13.2 isListening

```
web3.eth.net.isListening([callback])  
web3.bzz.net.isListening([callback])  
web3.shh.net.isListening([callback])
```

Checks if the node is listening for peers.

13.2.1 Parameters

none

13.2.2 Returns

Promise **returns** Boolean

13.2.3 Example

```
web3.eth.net.isListening()  
.then(console.log);  
> true
```

13.3 getPeerCount

```
web3.eth.net.getPeerCount([callback])  
web3.bzz.net.getPeerCount([callback])  
web3.shh.net.getPeerCount([callback])
```

Get the number of peers connected to.

13.3.1 Parameters

none

13.3.2 Returns

Promise **returns** Number

13.3.3 Example

```
web3.eth.net.getPeerCount()  
.then(console.log);  
> 25
```


CHAPTER 14

web3.bzz

Note: This API might change over time.

The `web3-bzz` package allows you to interact with swarm, the decentralized file store. For more see the [Swarm Docs](#).

```
var Bzz = require('web3-bzz');

// will autodetect if the "ethereum" object is present and will either connect to the
↳ local swarm node, or the swarm-gateways.net.
// Optional you can give your own provider URL; If no provider URL is given it will
↳ use "http://swarm-gateways.net"
var bzz = new Bzz(Bzz.givenProvider || 'http://swarm-gateways.net');

// or using the web3 umbrella package

var Web3 = require('web3');
var web3 = new Web3(Web3.givenProvider || 'ws://some.local-or-remote.node:8546');

// -> web3.bzz.currentProvider // if Web3.givenProvider was an ethereum provider it
↳ will set: "http://localhost:8500" otherwise it will set: "http://swarm-gateways.net"

// set the provider manually if necessary
web3.bzz.setProvider("http://localhost:8500");
```

14.1 setProvider

```
web3.bzz.setProvider(myProvider)
```

Will change the provider for its module.

Note: When called on the umbrella package `web3` it will also set the provider for all sub modules `web3.eth`, `web3.shh`, etc. EXCEPT `web3.bzz` which needs a separate provider at all times.

14.1.1 Parameters

1. Object - `myProvider`: a valid provider.

14.1.2 Returns

Boolean

14.1.3 Example

```
var Bzz = require('web3-bzz');
var bzz = new Bzz('http://localhost:8500');

// change provider
bzz.setProvider('http://swarm-gateways.net');
```

14.2 givenProvider

```
web3.bzz.givenProvider
```

When using `web3.js` in an Ethereum compatible browser, it will set with the current native provider by that browser. Returns the given provider by the (browser) environment, otherwise `null`.

14.2.1 Returns

Object: The given provider set or `null`;

14.2.2 Example

```
bzz.givenProvider;
> {
  send: function(),
  on: function(),
  bzz: "http://localhost:8500",
  shh: true,
  ...
}
```

(continues on next page)

(continued from previous page)

```

}

bzz.setProvider(bzz.givenProvider || "http://swarm-gateways.net");

```

14.3 currentProvider

```
bzz.currentProvider
```

Returns the current provider URL, otherwise null.

14.3.1 Returns

Object: The current provider URL or null.

14.3.2 Example

```

bzz.currentProvider;
> "http://localhost:8500"

if(!bzz.currentProvider) {
  bzz.setProvider("http://swarm-gateways.net");
}

```

14.4 upload

```
web3.bzz.upload(mixed)
```

Uploads files, folders or raw data to swarm.

14.4.1 Parameters

1. **mixed - String|Buffer|Uint8Array|Object:** The data to upload, can be a file content, file Buffer/Uint8Array, or

- **String|Buffer|Uint8Array:** A file content, file Uint8Array or Buffer to upload, or
- **Object:**

1. **Multiple key values for files and directories.** The paths will be kept the same:

- **key** must be the files path, or name, e.g. `"/foo.txt"` and its value is an object with:

* **type:** The mime-type of the file, e.g. `"text/html"`.

* data: A file content, file Uint8Array or Buffer to upload.

2. Upload a file or a directory from disk in Node.js. Requires and object with the following properties:

- path: The path to the file or directory.
- kind: The type of the source "directory", "file" or "data".
- defaultFile (optional): Path of the “defaultFile” when "kind": "directory", e.g. "/index.html".

3. Upload file or folder in the browser. Requires and object with the following properties:

- pick: The file picker to launch. Can be "file", "directory" or "data".

14.4.2 Returns

Promise returning String: Returns the content hash of the manifest.

14.4.3 Example

```
var bzz = web3.bzz;

// raw data
bzz.upload("test file").then(function(hash) {
  console.log("Uploaded file. Address:", hash);
})

// raw directory
var dir = {
  "/foo.txt": {type: "text/plain", data: "sample file"},
  "/bar.txt": {type: "text/plain", data: "another file"}
};
bzz.upload(dir).then(function(hash) {
  console.log("Uploaded directory. Address:", hash);
});

// upload from disk in node.js
bzz.upload({
  path: "/path/to/thing",           // path to data / file / directory
  kind: "directory",                // could also be "file" or "data"
  defaultFile: "/index.html"       // optional, and only for kind === "directory"
})
.then(console.log)
.catch(console.log);

// upload from disk in the browser
bzz.upload({pick: "file"}) // could also be "directory" or "data"
.then(console.log);
```

14.5 download

```
web3.bzz.download(bzzHash [, localpath])
```

Downloads files and folders from swarm as buffer or to disk (only node.js).

14.5.1 Parameters

1. `bzzHash` - String: The file or directory to download. If the hash is a raw file it will return a Buffer, if a manifest file, it will return the directory structure. If the `localpath` is given, it will return that path where it downloaded the files to.
2. `localpath` - String: The local folder to download the content into. (only node.js)

14.5.2 Returns

Promise returning Buffer|Object|String: The Buffer of the file downloaded, an object with the directory structure, or the path where it was downloaded to.

14.5.3 Example

```
var bzz = web3.bzz;

// download raw file
var fileHash = "a5c10851ef054c268a2438f10a21f6efe3dc3dcdcc2ea0e6a1a7a38bf8c91e23";
bzz.download(fileHash).then(function(buffer) {
  console.log("Downloaded file:", buffer.toString());
});

// download directory, if the hash is manifest file.
var dirHash = "7e980476df218c05ecfcb0a2ca73597193a34c5a9d6da84d54e295ecd8e0c641";
bzz.download(dirHash).then(function(dir) {
  console.log("Downloaded directory:");
  > {
    'bar.txt': { type: 'text/plain', data: <Buffer 61 6e 6f 74 68 65 72 20 66 69
↪6c 65> },
    'foo.txt': { type: 'text/plain', data: <Buffer 73 61 6d 70 6c 65 20 66 69 6c
↪65> }
  }
});

// download file/directory to disk (only node.js)
var dirHash = "a5c10851ef054c268a2438f10a21f6efe3dc3dcdcc2ea0e6a1a7a38bf8c91e23";
bzz.download(dirHash, "/target/dir")
  .then(path => console.log(`Downloaded directory to ${path}.`))
  .catch(console.log);
```

14.6 pick

```
web3.bzz.pick.file()
web3.bzz.pick.directory()
web3.bzz.pick.data()
```

Opens a file picker in the browser to select file(s), directory or data.

14.6.1 Parameters

none

14.6.2 Returns

Promise returning Object: Returns the file or multiple files.

14.6.3 Example

```
web3.bzz.pick.file()
  .then(console.log);
> {
  ...
}
```

CHAPTER 15

web3.shh

The `web3-shh` package allows you to interact with the whisper protocol for broadcasting. For more see [Whisper Overview](#).

```
var Shh = require('web3-shh');

// "Shh.providers.givenProvider" will be set if in an Ethereum supported browser.
var shh = new Shh(Shh.givenProvider || 'ws://some.local-or-remote.node:8546');

// or using the web3 umbrella package

var Web3 = require('web3');
var web3 = new Web3(Web3.givenProvider || 'ws://some.local-or-remote.node:8546');

// -> web3.shh
```

15.1 setProvider

```
web3.setProvider(myProvider)
web3.eth.setProvider(myProvider)
web3.shh.setProvider(myProvider)
web3.bzz.setProvider(myProvider)
...
```

Will change the provider for its module.

Note: When called on the umbrella package `web3` it will also set the provider for all sub modules `web3.eth`, `web3.shh`, etc. EXCEPT `web3.bzz` which needs a separate provider at all times.

15.1.1 Parameters

1. Object - myProvider: a valid provider.

15.1.2 Returns

Boolean

15.1.3 Example: Local Geth Node

```
var Web3 = require('web3');
var web3 = new Web3('http://localhost:8545');
// or
var web3 = new Web3(new Web3.providers.HttpProvider('http://localhost:8545'));

// change provider
web3.setProvider('ws://localhost:8546');
// or
web3.setProvider(new Web3.providers.WebsocketProvider('ws://localhost:8546'));

// Using the IPC provider in node.js
var net = require('net');
var web3 = new Web3('/Users/myuser/Library/Ethereum/geth.ipc', net); // mac os path
// or
var web3 = new Web3(new Web3.providers.IpcProvider('/Users/myuser/Library/Ethereum/
↳ geth.ipc', net)); // mac os path
// on windows the path is: "\\.\pipe\geth.ipc"
// on linux the path is: "/users/myuser/.ethereum/geth.ipc"
```

15.1.4 Example: Remote Node Provider

```
// Using a remote node provider, like Alchemy (https://www.alchemyapi.io/supernode),
↳ is simple.
var Web3 = require('web3');
var web3 = new Web3("https://eth-mainnet.alchemyapi.io/v2/your-api-key");
```

15.2 providers

```
web3.providers
web3.eth.providers
web3.shh.providers
web3.bzz.providers
...
```

Contains the current available providers.

15.2.1 Value

Object with the following providers:

- Object - `HttpProvider`: The HTTP provider is **deprecated**, as it won't work for subscriptions.
- Object - `WebsocketProvider`: The Websocket provider is the standard for usage in legacy browsers.
- Object - `IpcProvider`: The IPC provider is used node.js dapps when running a local node. Gives the most secure connection.

15.2.2 Example

```
var Web3 = require('web3');
// use the given Provider, e.g in Mist, or instantiate a new websocket provider
var web3 = new Web3(Web3.givenProvider || 'ws://remotenode.com:8546');
// or
var web3 = new Web3(Web3.givenProvider || new Web3.providers.WebsocketProvider('ws://
↪remotenode.com:8546'));

// Using the IPC provider in node.js
var net = require('net');

var web3 = new Web3('/Users/myuser/Library/Ethereum/geth.ipc', net); // mac os path
// or
var web3 = new Web3(new Web3.providers.IpcProvider('/Users/myuser/Library/Ethereum/
↪geth.ipc', net)); // mac os path
// on windows the path is: "\\.\pipe\geth.ipc"
// on linux the path is: "/users/myuser/.ethereum/geth.ipc"
```

15.2.3 Configuration

```
// ====
// Http
// ====

var Web3HttpProvider = require('web3-providers-http');

var options = {
  keepAlive: true,
  withCredentials: false,
  timeout: 20000, // ms
  headers: [
    {
      name: 'Access-Control-Allow-Origin',
      value: '*'
    },
    {
      ...
    }
  ],
  agent: {
    http: http.Agent(...),
    baseUrl: ''
  }
}
```

(continues on next page)

(continued from previous page)

```
};

var provider = new Web3HttpProvider('http://localhost:8545', options);

// =====
// Websockets
// =====

var Web3WsProvider = require('web3-providers-ws');

var options = {
  timeout: 30000, // ms

  // Useful for credentialed urls, e.g: ws://username:password@localhost:8546
  headers: {
    authorization: 'Basic username:password'
  },

  clientConfig: {
    // Useful if requests are large
    maxReceivedFrameSize: 100000000, // bytes - default: 1MiB
    maxReceivedMessageSize: 100000000, // bytes - default: 8MiB

    // Useful to keep a connection alive
    keepalive: true,
    keepaliveInterval: 60000 // ms
  },

  // Enable auto reconnection
  reconnect: {
    auto: true,
    delay: 5000, // ms
    maxAttempts: 5,
    onTimeout: false
  }
};

var ws = new Web3WsProvider('ws://localhost:8546', options);
```

More information for the Http and Websocket provider modules can be found here:

- [HttpProvider](#)
 - [WebsocketProvider](#)
-

15.3 givenProvider

```
web3.givenProvider
web3.eth.givenProvider
web3.shh.givenProvider
web3.bzz.givenProvider
...
```

When using web3.js in an Ethereum compatible browser, it will set with the current native provider by that browser. Will return the given provider by the (browser) environment, otherwise `null`.

15.3.1 Returns

Object: The given provider set or null;

15.3.2 Example

15.4 currentProvider

```
web3.currentProvider
web3.eth.currentProvider
web3.shh.currentProvider
web3.bzz.currentProvider
...
```

Will return the current provider, otherwise null.

15.4.1 Returns

Object: The current provider set or null.

15.4.2 Example

15.5 BatchRequest

```
new web3.BatchRequest ()
new web3.eth.BatchRequest ()
new web3.shh.BatchRequest ()
new web3.bzz.BatchRequest ()
```

Class to create and execute batch requests.

15.5.1 Parameters

none

15.5.2 Returns

Object: With the following methods:

- `add(request)`: To add a request object to the batch call.
- `execute()`: Will execute the batch request.

15.5.3 Example

```
var contract = new web3.eth.Contract(abi, address);

var batch = new web3.BatchRequest();
batch.add(web3.eth.getBalance.request('0x0000000000000000000000000000000000000000',
  ↪ 'latest', callback));
batch.add(contract.methods.balance(address).call.request({from:
  ↪ '0x0000000000000000000000000000000000000000'}, callback2));
batch.execute();
```

15.6 extend

```
web3.extend(methods)
web3.eth.extend(methods)
web3.shh.extend(methods)
web3.bzz.extend(methods)
...
```

Allows extending the web3 modules.

Note: You also have `*.extend.formatters` as additional formatter functions to be used for input and output formatting. Please see the [source file](#) for function details.

15.6.1 Parameters

1. **methods - Object:** Extension object with array of methods description objects as follows:

- **property - String:** (optional) The name of the property to add to the module. If no property is set it will be added to the module directly.
- **methods - Array:** The array of method descriptions:
 - **name - String:** Name of the method to add.
 - **call - String:** The RPC method name.
 - **params - Number:** (optional) The number of parameters for that function. Default 0.
 - **inputFormatter - Array:** (optional) Array of inputformatter functions. Each array item responds to a function parameter, so if you want some parameters not to be formatted, add a null instead.
 - **outputFormatter - Function:** (optional) Can be used to format the output of the method.

15.6.2 Returns

Object: The extended module.

15.6.3 Example

```
web3.extend({
  property: 'myModule',
  methods: [{
    name: 'getBalance',
    call: 'eth_getBalance',
    params: 2,
    inputFormatter: [web3.extend.formatters.inputAddressFormatter, web3.extend.
    ↪formatters.inputDefaultBlockNumberFormatter],
    outputFormatter: web3.utils.hexToNumberString
  }, {
    name: 'getGasPriceSuperFunction',
    call: 'eth_gasPriceSuper',
    params: 2,
    inputFormatter: [null, web3.utils.numberToHex]
  }]
});

web3.extend({
  methods: [{
    name: 'directCall',
    call: 'eth_callForFun',
  }]
});

console.log(web3);
> Web3 {
  myModule: {
    getBalance: function() {},
    getGasPriceSuperFunction: function() {}
  },
  directCall: function() {},
  eth: Eth {...},
  bzz: Bzz {...},
  ...
}
```

15.7 getId

```
web3.eth.net.getId([callback])
web3.bzz.net.getId([callback])
web3.shh.net.getId([callback])
```

Gets the current network ID.

15.7.1 Parameters

none

15.7.2 Returns

Promise **returns** Number: The network ID.

15.7.3 Example

```
web3.eth.net.getId()  
.then(console.log);  
> 1
```

15.8 isListening

```
web3.eth.net.isListening([callback])  
web3.bzz.net.isListening([callback])  
web3.shh.net.isListening([callback])
```

Checks if the node is listening for peers.

15.8.1 Parameters

none

15.8.2 Returns

Promise **returns** Boolean

15.8.3 Example

```
web3.eth.net.isListening()  
.then(console.log);  
> true
```

15.9 getPeerCount

```
web3.eth.net.getPeerCount([callback])  
web3.bzz.net.getPeerCount([callback])  
web3.shh.net.getPeerCount([callback])
```

Get the number of peers connected to.

15.9.1 Parameters

none

15.9.2 Returns

Promise **returns** Number

15.9.3 Example

```
web3.eth.net.getPeerCount()  
.then(console.log);  
> 25
```

15.10 getVersion

```
web3.shh.getVersion([callback])
```

Returns the version of the running whisper.

15.10.1 Parameters

1. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

15.10.2 Returns

`String` - The version of the current whisper running.

15.10.3 Example

```
web3.shh.getVersion()  
.then(console.log);  
> "5.0"
```

15.11 getInfo

```
web3.shh.getInfo([callback])
```

Gets information about the current whisper node.

15.11.1 Parameters

1. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

15.11.2 Returns

Object - The information of the node with the following properties:

- `messages` - Number: Number of currently floating messages.
- `maxMessageSize` - Number: The current message size limit in bytes.
- `memory` - Number: The memory size of the floating messages in bytes.
- `minPow` - Number: The current minimum PoW requirement.

15.11.3 Example

```
web3.shh.getInfo()  
.then(console.log);  
> {  
  "minPow": 0.8,  
  "maxMessageSize": 12345,  
  "memory": 1234335,  
  "messages": 20  
}
```

15.12 setMaxMessageSize

```
web3.shh.setMaxMessageSize(size, [callback])
```

Sets the maximal message size allowed by this node. Incoming and outgoing messages with a larger size will be rejected. Whisper message size can never exceed the limit imposed by the underlying P2P protocol (10 Mb).

15.12.1 Parameters

1. Number - Message size in bytes.
2. Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

15.12.2 Returns

Boolean - `true` on success, error on failure.

15.12.3 Example

```
web3.shh.setMaxMessageSize(1234565)  
.then(console.log);  
> true
```

15.13 setMinPoW

```
web3.shh.setMinPoW(pow, [callback])
```

Sets the minimal PoW required by this node.

This experimental function was introduced for the future dynamic adjustment of PoW requirement. If the node is overwhelmed with messages, it should raise the PoW requirement and notify the peers. The new value should be set relative to the old value (e.g. double). The old value can be obtained via [web3.shh.getInfo\(\)](#).

15.13.1 Parameters

1. `Number` - The new PoW requirement.
2. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

15.13.2 Returns

Boolean - `true` on success, error on failure.

15.13.3 Example

```
web3.shh.setMinPoW(0.9)
  .then(console.log);
> true
```

15.14 markTrustedPeer

```
web3.shh.markTrustedPeer(enode, [callback])
```

Marks specific peer trusted, which will allow it to send historic (expired) messages.

Note: This function is not adding new nodes, the node needs to be an existing peer.

15.14.1 Parameters

1. `String` - Enode of the trusted peer.
2. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

15.14.2 Returns

Boolean - `true` on success, error on failure.

15.14.3 Example

```
web3.shh.markTrustedPeer()  
.then(console.log);  
> true
```

15.15 newKeyPair

```
web3.shh.newKeyPair([callback])
```

Generates a new public and private key pair for message decryption and encryption.

15.15.1 Parameters

1. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

15.15.2 Returns

`String` - Key ID on success and an error on failure.

15.15.3 Example

```
web3.shh.newKeyPair()  
.then(console.log);  
> "5e57b9ffc2387e18636e0a3d0c56b023264c16e78a2adcba1303cefc685e610f"
```

15.16 addPrivateKey

```
web3.shh.addPrivateKey(privateKey, [callback])
```

Stores a key pair derived from a private key, and returns its ID.

15.16.1 Parameters

1. `String` - The private key as HEX bytes to import.
2. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

15.16.2 Returns

`String` - Key ID on success and an error on failure.

15.16.3 Example

```
web3.shh.addPrivateKey(
  ↪ '0x8bda3abeb454847b515fa9b404cede50b1cc63cfdeddd4999d074284b4c21e15')
.then(console.log);
> "3e22b9ffc2387e18636e0a3d0c56b023264c16e78a2adcba1303cefc685e610f"
```

15.17 deleteKeyPair

```
web3.shh.deleteKeyPair(id, [callback])
```

Deletes the specifies key if it exists.

15.17.1 Parameters

1. String - The key pair ID, returned by the creation functions (`shh.newKeyPair` and `shh.addPrivateKey`).
2. Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

15.17.2 Returns

Boolean - `true` on success, error on failure.

15.17.3 Example

```
web3.shh.deleteKeyPair(
  ↪ '3e22b9ffc2387e18636e0a3d0c56b023264c16e78a2adcba1303cefc685e610f')
.then(console.log);
> true
```

15.18 hasKeyPair

```
web3.shh.hasKeyPair(id, [callback])
```

Checks if the whisper node has a private key of a key pair matching the given ID.

15.18.1 Parameters

1. String - The key pair ID, returned by the creation functions (`shh.newKeyPair` and `shh.addPrivateKey`).
2. Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

15.18.2 Returns

Boolean - `true` on if the key pair exist in the node, `false` if not. Error on failure.

15.18.3 Example

```
web3.shh.hasKeyPair('fe22b9ffc2387e18636e0a3d0c56b023264c16e78a2adcba1303cefc685e610f')
  ↪
.then(console.log);
> true
```

15.19 getPublicKey

```
web3.shh.getPublicKey(id, [callback])
```

Returns the public key for a key pair ID.

15.19.1 Parameters

1. String - The key pair ID, returned by the creation functions (`shh.newKeyPair` and `shh.addPrivateKey`).
2. Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

15.19.2 Returns

String - Public key on success and an error on failure.

15.19.3 Example

```
web3.shh.getPublicKey(
  ↪ '3e22b9ffc2387e18636e0a3d0c56b023264c16e78a2adcba1303cefc685e610f')
.then(console.log);
>
  ↪ "0x04d1574d4eab8f3dde4d2dc7ed2c4d699d77cbbdd09167b8fffa099652ce4df00c4c6e0263eafe05007a46fdf0c8d32b"
  ↪ "
```

15.20 getPrivateKey

```
web3.shh.getPrivateKey(id, [callback])
```

Returns the private key for a key pair ID.

15.20.1 Parameters

1. `String` - The key pair ID, returned by the creation functions (`shh.newKeyPair` and `shh.addPrivateKey`).
2. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

15.20.2 Returns

`String` - Private key on success and an error on failure.

15.20.3 Example

```
web3.shh.getPrivateKey(  
  ↪ '3e22b9ffc2387e18636e0a3d0c56b023264c16e78a2adcba1303cefc685e610f')  
  .then(console.log);  
> "0x234234e22b9ffc2387e18636e0534534a3d0c56b0243567432453264c16e78a2adc"
```

15.21 newSymKey

```
web3.shh.newSymKey([callback])
```

Generates a random symmetric key and stores it under an ID, which is then returned. Will be used for encrypting and decrypting of messages where the sym key is known to both parties.

15.21.1 Parameters

1. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

15.21.2 Returns

`String` - Key ID on success and an error on failure.

15.21.3 Example

```
web3.shh.newSymKey()  
  .then(console.log);  
> "cec94d139ff51d7df1d228812b90c23ec1f909afa0840ed80f1e04030bb681e4"
```

15.22 addSymKey

```
web3.shh.addSymKey(symKey, [callback])
```

Stores the key, and returns its ID.

15.22.1 Parameters

1. `String` - The raw key for symmetric encryption as HEX bytes.
2. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

15.22.2 Returns

`String` - Key ID on success and an error on failure.

15.22.3 Example

```
web3.shh.addSymKey('0x5e11b9ffc2387e18636e0a3d0c56b023264c16e78a2adcba1303cefc685e610f
↪')
.then(console.log);
> "fea94d139ff51d7df1d228812b90c23ec1f909afa0840ed80f1e04030bb681e4"
```

15.23 generateSymKeyFromPassword

```
web3.shh.generateSymKeyFromPassword(password, [callback])
```

Generates the key from password, stores it, and returns its ID.

15.23.1 Parameters

1. `String` - A password to generate the sym key from.
2. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

15.23.2 Returns

`Promise<string>|undefined` - Returns the Key ID as Promise or undefined if a callback is defined.

15.23.3 Example

```
web3.shh.generateSymKeyFromPassword('Never use this password - password!')
.then(console.log);
> "2e57b9ffc2387e18636e0a3d0c56b023264c16e78a2adcba1303cefc685e610f"
```

15.24 hasSymKey

```
web3.shh.hasSymKey(id, [callback])
```

Checks if there is a symmetric key stored with the given ID.

15.24.1 Parameters

1. `String` - The key pair ID, returned by the creation functions (`shh.newSymKey`, `shh.addSymKey` or `shh.generateSymKeyFromPassword`).
2. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

15.24.2 Returns

`Boolean` - `true` on if the symmetric key exist in the node, `false` if not. Error on failure.

15.24.3 Example

```
web3.shh.hasSymKey('f6dcf21ed6a17bd78d8c4c63195ab997b3b65ea683705501eae82d32667adc92')  
.then(console.log);  
> true
```

15.25 getSymKey

```
web3.shh.getSymKey(id, [callback])
```

Returns the symmetric key associated with the given ID.

15.25.1 Parameters

1. `String` - The key pair ID, returned by the creation functions (`shh.newKeyPair` and `shh.addPrivateKey`).
2. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

15.25.2 Returns

`String` - The raw symmetric key on success and an error on failure.

15.25.3 Example

```
web3.shh.getSymKey('af33b9ffc2387e18636e0a3d0c56b023264c16e78a2adcba1303cefc685e610f')
.then(console.log);
> "0xa82a520aff70f7a989098376e48ec128f25f767085e84d7fb995a9815eebff0a"
```

15.26 deleteSymKey

```
web3.shh.deleteSymKey(id, [callback])
```

Deletes the symmetric key associated with the given ID.

15.26.1 Parameters

1. `String` - The key pair ID, returned by the creation functions (`shh.newKeyPair` and `shh.addPrivateKey`).
2. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

15.26.2 Returns

`Boolean` - `true` on if the symmetric key was deleted, error on failure.

15.26.3 Example

```
web3.shh.deleteSymKey(
  ↪ 'bf31b9ffc2387e18636e0a3d0c56b023264c16e78a2adcba1303cefc685e610f')
.then(console.log);
> true
```

15.27 post

```
web3.shh.post(object [, callback])
```

This method should be called, when we want to post whisper a message to the network.

15.27.1 Parameters

1. `Object` - The post object:

- `symKeyID` - `String` (optional): ID of symmetric key for message encryption (Either `symKeyID` or `pubKey` must be present. Can not be both.).
- `pubKey` - `String` (optional): The public key for message encryption (Either `symKeyID` or `pubKey` must be present. Can not be both.).

- `sig` - String (optional): The ID of the signing key.
 - `ttl` - Number: Time-to-live in seconds.
 - `topic` - String: 4 Bytes (mandatory when key is symmetric): Message topic.
 - `payload` - String: The payload of the message to be encrypted.
 - `padding` - Number (optional): Padding (byte array of arbitrary length).
 - `powTime` - Number (optional)?: Maximal time in seconds to be spent on proof of work.
 - `powTarget` - Number (optional)?: Minimal PoW target required for this message.
 - `targetPeer` - Number (optional): Peer ID (for peer-to-peer message only).
2. `callback` - Function: (optional) Optional callback, returns an error object as first parameter and the result as second.

15.27.2 Returns

Promise - returns a promise. Upon success, the `then` function will be passed a string representing the hash of the sent message. On error, the `catch` function will be passed a string containing the reason for the error.

15.27.3 Example

```
var identities = {};
var subscription = null;

Promise.all([
  web3.shh.newSymKey().then((id) => {identities.symKey = id;}),
  web3.shh.newKeyPair().then((id) => {identities.keyPair = id;})
]).then(() => {

  // will receive also its own message send, below
  subscription = web3.shh.subscribe("messages", {
    symKeyID: identities.symKey,
    topics: ['0xffaadd11']
  }).on('data', console.log);

}).then(() => {
  web3.shh.post({
    symKeyID: identities.symKey, // encrypts using the sym key ID
    sig: identities.keyPair, // signs the message using the keyPair ID
    ttl: 10,
    topic: '0xffaadd11',
    payload: '0xffffffffdddd1122',
    powTime: 3,
    powTarget: 0.5
  }).then(h => console.log(`Message with hash ${h} was successfully sent`))
  .catch(err => console.log("Error: ", err));
});
```

15.28 subscribe

```
web3.shh.subscribe('messages', options [, callback])
```

Subscribe for incoming whisper messages.

15.28.1 Parameters

1. "messages" - String: Type of the subscription.
2. **Object** - The subscription options:
 - symKeyID - String: ID of symmetric key for message decryption.
 - privateKeyID - String: ID of private (asymmetric) key for message decryption.
 - sig - String (optional): Public key of the signature, to verify.
 - topics - Array (optional when "privateKeyID" key is given): Filters messages by this topic(s). Each topic must be a 4 bytes HEX string.
 - minPow - Number (optional): Minimal PoW requirement for incoming messages.
 - allowP2P - Boolean (optional): Indicates if this filter allows processing of direct peer-to-peer messages (which are not to be forwarded any further, because they might be expired). This might be the case in some very rare cases, e.g. if you intend to communicate to MailServers, etc.
3. callback - Function: (optional) Optional callback, returns an error object as first parameter and the result as second. Will be called for each incoming subscription, and the subscription itself as 3 parameter.

15.28.2 Notification Returns

Object - The incoming message:

- hash - String: Hash of the enveloped message.
- sig - String: Public key which signed this message.
- recipientPublicKey - String: The recipients public key.
- timestamp - String: Unix timestamp of the message generation.
- ttl - Number: Time-to-live in seconds.
- topic - String: 4 Bytes HEX string message topic.
- payload - String: Decrypted payload.
- padding - Number: Optional padding (byte array of arbitrary length).
- pow - Number: Proof of work value.

15.28.3 Example

```
web3.shh.subscribe('messages', {
  symKeyID: 'bf31b9ffc2387e18636e0a3d0c56b023264c16e78a2adcba1303cefc685e610f',
  sig:
    '0x04d1574d4eab8f3dde4d2dc7ed2c4d699d77cbbdd09167b8fffa099652ce4df00c4c6e0263eafe05007a46fdf0c8d321',
  topics: [''],
  minPow: 1,
  allowP2P: true,
  callback: function (error, subscription) {
    if (error) {
      console.log('Error: ', error);
    } else {
      console.log('Subscription: ', subscription);
    }
  }
});
```

(continues on next page)

(continued from previous page)

```

    ttl: 20,
    topics: ['0xffddaa11'],
    minPow: 0.8,
  }, function(error, message, subscription){

    console.log(message);
    > {
      "hash": "0x4158eb81ad8e30cfcee67f20b1372983d388f1243a96e39f94fd2797b1e9c78e",
      "padding":
↪ "0xc15f786f34e5cef0fef6ce7c1185d799ecdb5ebca72b3310648c5588db2e99a0d73301c7a8d90115a91213f0bc9c7223",
↪ ",
      "payload": "0xdeadbeaf",
      "pow": 0.5371803278688525,
      "recipientPublicKey": null,
      "sig": null,
      "timestamp": 1496991876,
      "topic": "0x01020304",
      "ttl": 50
    }
  })
// or
.on('data', function(message){ ... });

```

15.29 clearSubscriptions

```
web3.shh.clearSubscriptions()
```

Resets subscriptions.

Note: This will not reset subscriptions from other packages like `web3-eth`, as they use their own `requestManager`.

15.29.1 Parameters

1. Boolean: If `true` it keeps the "syncing" subscription.

15.29.2 Returns

Boolean

15.29.3 Example

```

web3.shh.subscribe('messages', {...}, function(){ ... });

...

web3.shh.clearSubscriptions();

```

15.30 newMessageFilter

```
web3.shh.newMessageFilter(options)
```

Create a new filter within the node. This filter can be used to poll for new messages that match the set of criteria.

15.30.1 Parameters

1. Object: See *web3.shh.subscribe() options* for details.

15.30.2 Returns

String: The filter ID.

15.30.3 Example

```
web3.shh.newMessageFilter()  
.then(console.log);  
> "2b47fbafb3cce24570812a82e6e93cd9e2551bbc4823f6548ff0d82d2206b326"
```

15.31 deleteMessageFilter

```
web3.shh.deleteMessageFilter(id)
```

Deletes a message filter in the node.

15.31.1 Parameters

1. String: The filter ID created with `shh.newMessageFilter()`.

15.31.2 Returns

Boolean: `true` on success, `error` on failure.

15.31.3 Example

```
web3.shh.deleteMessageFilter(  
  ↪ '2b47fbafb3cce24570812a82e6e93cd9e2551bbc4823f6548ff0d82d2206b326')  
)  
.then(console.log);  
> true
```

15.32 getFilterMessages

```
web3.shh.getFilterMessages(id)
```

Retrieve messages that match the filter criteria and are received between the last time this function was called and now.

15.32.1 Parameters

1. String: The filter ID created with `shh.newMessageFilter()`.

15.32.2 Returns

Array: Returns an array of message objects like *web3.shh.subscribe() notification returns*

15.32.3 Example

```
web3.shh.getFilterMessages (
  ↪ '2b47fbafb3cce24570812a82e6e93cd9e2551bbc4823f6548ff0d82d2206b326')
  .then(console.log);
> [{
  "hash": "0x4158eb81ad8e30cfcee67f20b1372983d388f1243a96e39f94fd2797b1e9c78e",
  "padding":
  ↪ "0xc15f786f34e5cef0fef6ce7c1185d799ecdb5ebca72b3310648c5588db2e99a0d73301c7a8d90115a91213f0bc9c722",
  ↪ ",
  "payload": "0xdeadbeaf",
  "pow": 0.5371803278688525,
  "recipientPublicKey": null,
  "sig": null,
  "timestamp": 1496991876,
  "topic": "0x01020304",
  "ttl": 50
}, {...}]
```


This package provides utility functions for Ethereum dapps and other web3.js packages.

16.1 Bloom Filters

16.1.1 What are bloom filters?

A Bloom filter is a probabilistic, space-efficient data structure used for fast checks of set membership. That probably doesn't mean much to you yet, and so let's explore how bloom filters might be used.

Imagine that we have some large set of data, and we want to be able to quickly test if some element is currently in that set. The naive way of checking might be to query the set to see if our element is in there. That's probably fine if our data set is relatively small. Unfortunately, if our data set is really big, this search might take a while. Luckily, we have tricks to speed things up in the ethereum world!

A bloom filter is one of these tricks. The basic idea behind the Bloom filter is to hash each new element that goes into the data set, take certain bits from this hash, and then use those bits to fill in parts of a fixed-size bit array (e.g. set certain bits to 1). This bit array is called a bloom filter.

Later, when we want to check if an element is in the set, we simply hash the element and check that the right bits are in the bloom filter. If at least one of the bits is 0, then the element definitely isn't in our data set! If all of the bits are 1, then the element might be in the data set, but we need to actually query the database to be sure. So we might have false positives, but we'll never have false negatives. This can greatly reduce the number of database queries we have to make.

Real Life Example

An ethereum real life example in where this is useful is if you want to update a users balance on every new block so it stays as close to real time as possible. Without using a bloom filter on every new block you would have to force the balances even if that user may not of had any activity within that block. But if you use the logBlooms from the block you can test the bloom filter against the users ethereum address before you do any more slow operations, this will dramatically decrease the amount of calls you do as you will only be doing those extra operations if that

ethereum address is within that block (minus the false positives outcome which will be negligible). This will be highly performant for your app.

16.1.2 Functions

- `web3.utils.isBloom`
- `web3.utils.isUserEthereumAddressInBloom`
- `web3.utils.isContractAddressInBloom`
- `web3.utils.isTopic`
- `web3.utils.isTopicInBloom`
- `web3.utils.isInBloom`

Note: Please raise any issues [here](#)

16.2 randomHex

```
web3.utils.randomHex(size)
```

The `randomHex` library to generate cryptographically strong pseudo-random HEX strings from a given byte size.

16.2.1 Parameters

1. `size` - Number: The byte size for the HEX string, e.g. 32 will result in a 32 bytes HEX string with 64 characters prefixed with "0x".

16.2.2 Returns

String: The generated random HEX string.

16.2.3 Example

```
web3.utils.randomHex(32)
> "0xa5b9d60f32436310afebcfda832817a68921beb782fabf7915cc0460b443116a"

web3.utils.randomHex(4)
> "0x6892ffc6"

web3.utils.randomHex(2)
> "0x99d6"

web3.utils.randomHex(1)
> "0x9a"
```

(continues on next page)

(continued from previous page)

```
web3.utils.randomHex(0)
> "0x"
```

16.3 `_`

```
web3.utils._()
```

The [underscore](#) library for many convenience JavaScript functions.

See the [underscore API reference](#) for details.

16.3.1 Example

```
var _ = web3.utils._;

_.union([1,2],[3]);
> [1,2,3]

_.each({my: 'object'}, function(value, key) { ... })

...
```

16.4 `BN`

```
web3.utils.BN(mixed)
```

The [BN.js](#) library for calculating with big numbers in JavaScript. See the [BN.js documentation](#) for details.

Note: For safe conversion of many types, incl [BigNumber.js](#) use [utils.toBN](#)

16.4.1 Parameters

1. `mixed - String|Number`: A number, number string or HEX string to convert to a BN object.

16.4.2 Returns

Object: The [BN.js](#) instance.

16.4.3 Example

```
var BN = web3.utils.BN;

new BN(1234).toString();
> "1234"

new BN('1234').add(new BN('1')).toString();
> "1235"

new BN('0xea').toString();
> "234"
```

16.5 isBN

```
web3.utils.isBN(bn)
```

Checks if a given value is a [BN.js](#) instance.

16.5.1 Parameters

1. bn - Object: An [BN.js](#) instance.

16.5.2 Returns

Boolean

16.5.3 Example

```
var number = new BN(10);

web3.utils.isBN(number);
> true
```

16.6 isBigNumber

```
web3.utils.isBigNumber(bignumber)
```

Checks if a given value is a [BigNumber.js](#) instance.

16.6.1 Parameters

1. bignumber - Object: A [BigNumber.js](#) instance.

16.6.2 Returns

Boolean

16.6.3 Example

```
var number = new BigNumber(10);

web3.utils.isBigNumber(number);
> true
```

16.7 sha3

```
web3.utils.sha3(string)
web3.utils.keccak256(string) // ALIAS
```

Will calculate the sha3 of the input.

Note: To mimic the sha3 behaviour of solidity use *soliditySha3*

16.7.1 Parameters

1. string - String: A string to hash.

16.7.2 Returns

String: the result hash.

16.7.3 Example

```
web3.utils.sha3('234'); // taken as string
> "0xc1912fee45d61c87cc5ea59dae311904cd86b84fee17cc96966216f811ce6a79"

web3.utils.sha3(new BN('234'));
> "0xbc36789e7a1e281436464229828f817d6612f7b477d66591ff96a9e064bcc98a"

web3.utils.sha3(234);
> null // can't calculate the hash of a number

web3.utils.sha3(0xea); // same as above, just the HEX representation of the number
> null

web3.utils.sha3('0xea'); // will be converted to a byte array first, and then hashed
> "0x2f20677459120677484f7104c76deb6846a2c071f9b3152c103bb12cd54d1a4a"
```

16.8 sha3Raw

```
web3.utils.sha3Raw(string)
```

Will calculate the sha3 of the input but does return the hash value instead of `null` if for example a empty string is passed.

Note: Further details about this function can be seen here [sha3](#)

16.9 soliditySha3

```
web3.utils.soliditySha3(param1 [, param2, ...])
```

Will calculate the sha3 of given input parameters in the same way solidity would. This means arguments will be ABI converted and tightly packed before being hashed.

Warning: This method poses a security risk where multiple inputs can compute to the same hash. Provided in the example code are multiple cases of this security risk

16.9.1 Parameters

1. paramX - Mixed: Any type, or an object with `{type: 'uint', value: '123456'}` or `{t: 'bytes', v: '0xfff456'}`. Basic types are autodetected as follows:

- String non numerical UTF-8 string is interpreted as string.
- String|Number|BN|HEX positive number is interpreted as uint256.
- String|Number|BN negative number is interpreted as int256.
- Boolean as bool.
- String HEX string with leading 0x is interpreted as bytes.
- HEX HEX number representation is interpreted as uint256.

16.9.2 Returns

String: the result hash.

16.9.3 Example

```
// As a short example of the non-distinguished nature of
// Solidity tight-packing (which is why it is inappropriate
// for many things from a security point of view), consider
// the following examples are all equal, despite representing
// very different values and layouts.
```

(continues on next page)

(continued from previous page)

```

web3.utils.soliditySha3('hello','world01')
// "0xfb0a9d38c4dc568cbd105866540986fabf3c08c1bfb78299ce21aa0e5c0c586b"
web3.utils.soliditySha3({type: 'string', value: 'helloworld'}, {type: 'string', value:
  ↪ '01'})
// "0xfb0a9d38c4dc568cbd105866540986fabf3c08c1bfb78299ce21aa0e5c0c586b"
web3.utils.soliditySha3({type: 'string', value: 'hell'}, {type: 'string', value:
  ↪ 'oworld'}, {type: 'uint16', value: 0x3031})
// "0xfb0a9d38c4dc568cbd105866540986fabf3c08c1bfb78299ce21aa0e5c0c586b"
web3.utils.soliditySha3({type: 'uint96', value: '32309054545061485574011236401'})
// "0xfb0a9d38c4dc568cbd105866540986fabf3c08c1bfb78299ce21aa0e5c0c586b"

web3.utils.soliditySha3('234564535', '0xffff23243', true, -10);
// auto detects:      uint256,      bytes,      bool,      int256
> "0x3e27a893dc40ef8a7f0841d96639de2f58a132be5ae466d40087a2cfa83b7179"

web3.utils.soliditySha3('Hello!%'); // auto detects: string
> "0x661136a4267dba9ccdf6bfddb7c00e714de936674c4bdb065a531cf1cb15c7fc"

web3.utils.soliditySha3('234'); // auto detects: uint256
> "0x61c831beab28d67d1bb40b5ae1a11e2757fa842f031a2d0bc94a7867bc5d26c2"

web3.utils.soliditySha3(0xea); // same as above
> "0x61c831beab28d67d1bb40b5ae1a11e2757fa842f031a2d0bc94a7867bc5d26c2"

web3.utils.soliditySha3(new BN('234')); // same as above
> "0x61c831beab28d67d1bb40b5ae1a11e2757fa842f031a2d0bc94a7867bc5d26c2"

web3.utils.soliditySha3({type: 'uint256', value: '234'})); // same as above
> "0x61c831beab28d67d1bb40b5ae1a11e2757fa842f031a2d0bc94a7867bc5d26c2"

web3.utils.soliditySha3({t: 'uint', v: new BN('234')})); // same as above
> "0x61c831beab28d67d1bb40b5ae1a11e2757fa842f031a2d0bc94a7867bc5d26c2"

web3.utils.soliditySha3('0x407D73d8a49eeb85D32Cf465507dd71d507100c1');
> "0x4e8ebbefa452077428f93c9520d3edd60594ff452a29ac7d2ccc11d47f3ab95b"

web3.utils.soliditySha3({t: 'bytes', v: '0x407D73d8a49eeb85D32Cf465507dd71d507100c1'}
  ↪ );
> "0x4e8ebbefa452077428f93c9520d3edd60594ff452a29ac7d2ccc11d47f3ab95b" // same result
  ↪ as above

web3.utils.soliditySha3({t: 'address', v: '0x407D73d8a49eeb85D32Cf465507dd71d507100c1'
  ↪ });
> "0x4e8ebbefa452077428f93c9520d3edd60594ff452a29ac7d2ccc11d47f3ab95b" // same as
  ↪ above, but will do a checksum check, if its multi case

web3.utils.soliditySha3({t: 'bytes32', v: '0x407D73d8a49eeb85D32Cf465507dd71d507100c1'
  ↪ });
> "0x3c69a194aaf415ba5d6afca734660d0a3d45acdc05d54cd1ca89a8988e7625b4" // different
  ↪ result as above

```

(continues on next page)

(continued from previous page)

```
web3.utils.soliditySha3({t: 'string', v: 'Hello!'}, {t: 'int8', v: -23}, {t: 'address  
→', v: '0x85F43D8a49eeB85d32Cf465507DD71d507100C1d'}));  
> "0xa13b31627c1ed7aaded5aecec71baf02fe123797fffd45e662eac8e06fbe4955"
```

16.10 soliditySha3Raw

```
web3.utils.soliditySha3Raw(param1 [, param2, ...])
```

Will calculate the sha3 of given input parameters in the same way solidity would. This means arguments will be ABI converted and tightly packed before being hashed. The difference between this function and the `soliditySha3` function is that it will return the hash value instead of `null` if for example a empty string is given.

Note: Further details about this function can be seen here [soliditySha3](#)

16.11 isHex

```
web3.utils.isHex(hex)
```

Checks if a given string is a HEX string.

16.11.1 Parameters

1. `hex - String|HEX`: The given HEX string.

16.11.2 Returns

Boolean

16.11.3 Example

```
web3.utils.isHex('0xc1912');  
> true  
  
web3.utils.isHex(0xc1912);  
> true  
  
web3.utils.isHex('c1912');  
> true  
  
web3.utils.isHex(345);  
> true // this is tricky, as 345 can be a a HEX representation or a number, be_  
→ careful when not having a 0x in front!
```

(continues on next page)

(continued from previous page)

```
web3.utils.isHex('0xZ1912');  
> false  
  
web3.utils.isHex('Hello');  
> false
```

16.12 isHexStrict

```
web3.utils.isHexStrict(hex)
```

Checks if a given string is a HEX string. Difference to `web3.utils.isHex()` is that it expects HEX to be prefixed with `0x`.

16.12.1 Parameters

1. `hex` - `String|HEX`: The given HEX string.

16.12.2 Returns

Boolean

16.12.3 Example

```
web3.utils.isHexStrict('0xc1912');  
> true  
  
web3.utils.isHexStrict(0xc1912);  
> false  
  
web3.utils.isHexStrict('c1912');  
> false  
  
web3.utils.isHexStrict(345);  
> false // this is tricky, as 345 can be a a HEX representation or a number, be_  
↪ careful when not having a 0x in front!  
  
web3.utils.isHexStrict('0xZ1912');  
> false  
  
web3.utils.isHex('Hello');  
> false
```

16.13 isAddress

```
web3.utils.isAddress(address)
```

Checks if a given string is a valid Ethereum address. It will also check the checksum, if the address has upper and lowercase letters.

16.13.1 Parameters

1. address - String: An address string.

16.13.2 Returns

Boolean

16.13.3 Example

```
web3.utils.isAddress('0xc1912fee45d61c87cc5ea59dae31190fffff232d');
> true

web3.utils.isAddress('c1912fee45d61c87cc5ea59dae31190fffff232d');
> true

web3.utils.isAddress('0XC1912FEE45D61C87CC5EA59DAE31190FFFFFF232D');
> true // as all is uppercase, no checksum will be checked

web3.utils.isAddress('0xc1912fEE45d61C87Cc5EA59DaE31190FFFFf232d');
> true

web3.utils.isAddress('0xC1912fEE45d61C87Cc5EA59DaE31190FFFFf232d');
> false // wrong checksum
```

16.14 toChecksumAddress

```
web3.utils.toChecksumAddress(address)
```

Will convert an upper or lowercase Ethereum address to a checksum address.

16.14.1 Parameters

1. address - String: An address string.

16.14.2 Returns

String: The checksum address.

16.14.3 Example

```
web3.utils.toChecksumAddress('0xc1912fee45d61c87cc5ea59dae31190fffff232d');  
> "0xc1912fEE45d61C87Cc5EA59DaE31190FFFFf232d"  
  
web3.utils.toChecksumAddress('0XC1912FEE45D61C87CC5EA59DAE31190FFFFFF232D');  
> "0xc1912fEE45d61C87Cc5EA59DaE31190FFFFf232d" // same as above
```

16.15 checkAddressChecksum

```
web3.utils.checkAddressChecksum(address)
```

Checks the checksum of a given address. Will also return false on non-checksum addresses.

16.15.1 Parameters

1. address - String: An address string.

16.15.2 Returns

Boolean: true when the checksum of the address is valid, false if its not a checksum address, or the checksum is invalid.

16.15.3 Example

```
web3.utils.checkAddressChecksum('0xc1912fEE45d61C87Cc5EA59DaE31190FFFFf232d');  
> true
```

16.16 toHex

```
web3.utils.toHex(mixed)
```

Will auto convert any given value to HEX. Number strings will interpreted as numbers. Text strings will be interpreted as UTF-8 strings.

16.16.1 Parameters

1. mixed - String|Number|BN|BigNumber: The input to convert to HEX.

16.16.2 Returns

String: The resulting HEX string.

16.16.3 Example

```
web3.utils.toHex('234');  
> "0xea"  
  
web3.utils.toHex(234);  
> "0xea"  
  
web3.utils.toHex(new BN('234'));  
> "0xea"  
  
web3.utils.toHex(new BigNumber('234'));  
> "0xea"  
  
web3.utils.toHex('I have 100€');  
> "0x49206861766520313030e282ac"
```

16.17 stripHexPrefix

Returns provided string without 0x prefix.

16.17.1 Parameters

1. str - string: Input string

16.17.2 Returns

String: The input string without 0x prefix.

16.17.3 Example

```
web3.utils.stripHexPrefix('234');  
> "234"  
  
web3.utils.stripHexPrefix('0x234');  
> "234"  
  
web3.utils.stripHexPrefix(42);  
> 42
```

16.18 toBN

```
web3.utils.toBN(number)
```

Will safely convert any given value (including `BigNumber.js` instances) into a `BN.js` instance, for handling big numbers in JavaScript.

Note: For just the `BN.js` class use `utils.BN`

16.18.1 Parameters

1. `number - String|Number|HEX`: Number to convert to a big number.

16.18.2 Returns

Object: The `BN.js` instance.

16.18.3 Example

```
web3.utils.toBN(1234).toString();
> "1234"

web3.utils.toBN('1234').add(web3.utils.toBN('1')).toString();
> "1235"

web3.utils.toBN('0xea').toString();
> "234"
```

16.19 hexToNumberString

```
web3.utils.hexToNumberString(hex)
```

Returns the number representation of a given HEX value as a string.

16.19.1 Parameters

1. `hexString - String|HEX`: A string to hash.

16.19.2 Returns

String: The number as a string.

16.19.3 Example

```
web3.utils.hexToNumberString('0xea');
> "234"
```

16.20 hexToNumber

```
web3.utils.hexToNumber(hex)
web3.utils.toDecimal(hex) // ALIAS, deprecated
```

Returns the number representation of a given HEX value.

Note: This is not useful for big numbers, rather use *utils.toBN* instead.

16.20.1 Parameters

1. `hexString` - `String|HEX`: A string to hash.

16.20.2 Returns

Number

16.20.3 Example

```
web3.utils.hexToNumber('0xea');
> 234
```

16.21 numberToHex

```
web3.utils.numberToHex(number)
web3.utils.fromDecimal(number) // ALIAS, deprecated
```

Returns the HEX representation of a given number value.

16.21.1 Parameters

1. `number` - `String|Number|BN|BigNumber`: A number as string or number.

16.21.2 Returns

String: The HEX value of the given number.

16.21.3 Example

```
web3.utils.numberToHex('234');
> '0xea'
```

16.22 hexToUtf8

```
web3.utils.hexToUtf8(hex)
web3.utils.hexToString(hex) // ALIAS
web3.utils.toUtf8(hex) // ALIAS, deprecated
```

Returns the UTF-8 string representation of a given HEX value.

16.22.1 Parameters

1. `hex - String`: A HEX string to convert to a UTF-8 string.

16.22.2 Returns

`String`: The UTF-8 string.

16.22.3 Example

```
web3.utils.hexToUtf8('0x49206861766520313030e282ac');
> "I have 100€"
```

16.23 hexToAscii

```
web3.utils.hexToAscii(hex)
web3.utils.toAscii(hex) // ALIAS, deprecated
```

Returns the ASCII string representation of a given HEX value.

16.23.1 Parameters

1. `hex - String`: A HEX string to convert to a ASCII string.

16.23.2 Returns

`String`: The ASCII string.

16.23.3 Example

```
web3.utils.hexToAscii('0x4920686176652031303021');
> "I have 100!"
```

16.24 utf8ToHex

```
web3.utils.utf8ToHex(string)
web3.utils.stringToHex(string) // ALIAS
web3.utils.fromUtf8(string) // ALIAS, deprecated
```

Returns the HEX representation of a given UTF-8 string.

16.24.1 Parameters

1. `string` - String: A UTF-8 string to convert to a HEX string.

16.24.2 Returns

String: The HEX string.

16.24.3 Example

```
web3.utils.utf8ToHex('I have 100€');
> "0x49206861766520313030e282ac"
```

16.25 asciiToHex

```
web3.utils.asciiToHex(string)
web3.utils.fromAscii(string) // ALIAS, deprecated
```

Returns the HEX representation of a given ASCII string.

16.25.1 Parameters

1. `string` - String: A ASCII string to convert to a HEX string.

16.25.2 Returns

String: The HEX string.

16.25.3 Example

```
web3.utils.asciiToHex('I have 100!');
> "0x4920686176652031303021"
```

16.26 hexToBytes

```
web3.utils.hexToBytes(hex)
```

Returns a byte array from the given HEX string.

16.26.1 Parameters

1. `hex` - `String`|`HEX`: A HEX to convert.

16.26.2 Returns

`Array`: The byte array.

16.26.3 Example

```
web3.utils.hexToBytes('0x000000ea');  
> [ 0, 0, 0, 234 ]  
  
web3.utils.hexToBytes(0x000000ea);  
> [ 234 ]
```

16.27 bytesToHex

```
web3.utils.bytesToHex(byteArray)
```

Returns a HEX string from a byte array.

16.27.1 Parameters

1. `byteArray` - `Array`: A byte array to convert.

16.27.2 Returns

`String`: The HEX string.

16.27.3 Example

```
web3.utils.bytesToHex([ 72, 101, 108, 108, 111, 33, 36 ]);  
> "0x48656c6c6f2125"
```

16.28 toWei

```
web3.utils.toWei(number [, unit])
```

Converts any [ether value](#) value into [wei](#).

Note: “wei” are the smallest ether unit, and you should always make calculations in wei and convert only for display reasons.

16.28.1 Parameters

1. **number** - `String|BN`: The value.
2. **unit** - `String` (optional, defaults to "ether"): The ether to convert from. Possible units are:

- `noether`: '0'
- `wei`: '1'
- `kwei`: '1000'
- `Kwei`: '1000'
- `babbage`: '1000'
- `femtoether`: '1000'
- `mwei`: '1000000'
- `Mwei`: '1000000'
- `lovelace`: '1000000'
- `picoether`: '1000000'
- `gwei`: '1000000000'
- `Gwei`: '1000000000'
- `shannon`: '1000000000'
- `nanoether`: '1000000000'
- `nano`: '1000000000'
- `szabo`: '1000000000000'
- `microether`: '1000000000000'
- `micro`: '1000000000000'
- `finney`: '1000000000000000'
- `milliether`: '1000000000000000'
- `milli`: '1000000000000000'
- `ether`: '1000000000000000000'
- `kether`: '1000000000000000000000'
- `grand`: '1000000000000000000000'
- `meth`: '1000000000000000000000000'

- ### 16.28.2 Returns

16.28.3 Example

16.29 fromWei

Note: “wei” are the smallest ether unit, and you should always make calculations in wei and convert only for display reasons.

1. **number** - `String|BN`: The value in wei.
2. **unit** - `String` (optional, defaults to `"ether"`): The ether to convert to. Possible units are:
 - `noether`: `'0'`
 - `wei`: `'1'`
 - `kwei`: `'1000'`
 - `Kwei`: `'1000'`
 - `babbage`: `'1000'`
 - `femtoether`: `'1000'`
 - `mwei`: `'1000000'`
 - `Mwei`: `'1000000'`

- lovelace: '1000000'
- picoether: '1000000'
- gwei: '1000000000'
- Gwei: '1000000000'
- shannon: '1000000000'
- nanoether: '1000000000'
- nano: '1000000000'
- szabo: '1000000000000'
- microether: '1000000000000'
- micro: '1000000000000'
- finney: '1000000000000000'
- milliether: '1000000000000000'
- milli: '1000000000000000'
- ether: '1000000000000000000'
- kether: '1000000000000000000000'
- grand: '1000000000000000000000'
- mether: '1000000000000000000000000'
- gether: '1000000000000000000000000000'
- tether: '1000000000000000000000000000000'

16.29.2 Returns

String: It always returns a string number.

16.29.3 Example

```
web3.utils.fromWei('1', 'ether');  
> "0.000000000000000001"  
  
web3.utils.fromWei('1', 'finney');  
> "0.0000000000000001"  
  
web3.utils.fromWei('1', 'szabo');  
> "0.000000000001"  
  
web3.utils.fromWei('1', 'shannon');  
> "0.00000001"
```

16.30 unitMap

```
web3.utils.unitMap
```

Shows all possible ether value and their amount in wei.

16.30.1 Return value

- **Object with the following properties:**

- noether: '0'
- wei: '1'
- kwei: '1000'
- Kwei: '1000'
- babbage: '1000'
- femtoether: '1000'
- mwei: '1000000'
- Mwei: '1000000'
- lovelace: '1000000'
- picoether: '1000000'
- gwei: '1000000000'
- Gwei: '1000000000'
- shannon: '1000000000'
- nanoether: '1000000000'
- nano: '1000000000'
- szabo: '1000000000000'
- microether: '1000000000000'
- micro: '1000000000000'
- finney: '1000000000000000'
- milliether: '1000000000000000'
- milli: '1000000000000000'
- ether: '1000000000000000000'
- kether: '1000000000000000000000'
- grand: '1000000000000000000000'
- mether: '1000000000000000000000000'
- gether: '1000000000000000000000000000'
- tether: '1000000000000000000000000000000'

16.30.2 Example

```
web3.utils.unitMap
> {
  noether: '0',
  wei:     '1',
  kwei:    '1000',
  Kwei:    '1000',
  babbage: '1000',
  femtoether: '1000',
  mwei:     '1000000',
  Mwei:     '1000000',
  lovelace: '1000000',
  picoether: '1000000',
  gwei:     '1000000000',
  Gwei:     '1000000000',
  shannon:  '1000000000',
  nanoether: '1000000000',
  nano:     '1000000000',
  szabo:    '1000000000000',
  microether: '1000000000000',
  micro:    '1000000000000',
  finney:   '1000000000000000',
  milliether: '1000000000000000',
  milli:    '1000000000000000',
  ether:    '1000000000000000000',
  kether:   '1000000000000000000000',
  grand:    '1000000000000000000000',
  mether:   '1000000000000000000000000',
  gether:   '1000000000000000000000000',
  tether:   '1000000000000000000000000'
}
```

16.31 padLeft

```
web3.utils.padLeft(string, characterAmount [, sign])
web3.utils.leftPad(string, characterAmount [, sign]) // ALIAS
```

Adds a padding on the left of a string. Useful for adding paddings to HEX strings.

16.31.1 Parameters

1. `string` - `String`: The string to add padding on the left.
2. `characterAmount` - `Number`: The number of characters the total string should have.
3. `sign` - `String` (optional): The character sign to use, defaults to "0".

16.31.2 Returns

`String`: The padded string.

16.31.3 Example

```
web3.utils.padLeft('0x3456ff', 20);
> "0x000000000000000000003456ff"

web3.utils.padLeft(0x3456ff, 20);
> "0x000000000000000000003456ff"

web3.utils.padLeft('Hello', 20, 'x');
> "xxxxxxxxxxxxxxxxxxHello"
```

16.32 padRight

```
web3.utils.padRight(string, characterAmount [, sign])
web3.utils.rightPad(string, characterAmount [, sign]) // ALIAS
```

Adds a padding on the right of a string, Useful for adding paddings to HEX strings.

16.32.1 Parameters

1. string - String: The string to add padding on the right.
2. characterAmount - Number: The number of characters the total string should have.
3. sign - String (optional): The character sign to use, defaults to "0".

16.32.2 Returns

String: The padded string.

16.32.3 Example

```
web3.utils.padRight('0x3456ff', 20);
> "0x3456ff0000000000000000"

web3.utils.padRight(0x3456ff, 20);
> "0x3456ff0000000000000000"

web3.utils.padRight('Hello', 20, 'x');
> "Helloxxxxxxxxxxxxxxxxxx"
```

16.33 toTwosComplement

```
web3.utils.toTwosComplement(number)
```

Converts a negative number into a two's complement.

16.33.1 Parameters

1. `number` - `Number|String|BigNumber`: The number to convert.

16.33.2 Returns

`String`: The converted hex string.

16.33.3 Example

```
web3.utils.toTwosComplement('-1');  
> "0xfffffffffffffffffffffffffffffffffffffffffffffffffffff"  
  
web3.utils.toTwosComplement(-1);  
> "0xfffffffffffffffffffffffffffffffffffffffffffffffffffff"  
  
web3.utils.toTwosComplement('0x1');  
> "0x0000000000000000000000000000000000000000000000000000000000000001"  
  
web3.utils.toTwosComplement(-15);  
> "0xfffffffffffffffffffffffffffffffffffffffffffffffffffff1"  
  
web3.utils.toTwosComplement('-0x1');  
> "0xfffffffffffffffffffffffffffffffffffffffffffffffffffff"
```

Special thanks to [Netlify](#) for providing build and deploy services for our end-to-end integration tests.

C

contract deploy, [75](#)

J

JSON interface, [67](#)

N

npm, [3](#)

Y

yarn, [3](#)